
P. FOLEY.

SHOE.

No. 282,184.

Patented July 31, 1883.

Fi_{9:}1.



Іп√епtпр.

Patrick Foley:

UNITED STATES PATENT OFFICE.

PATRICK FOLEY, OF BOSTON, MASSACHUSETTS, ASSIGNOR TO FREDERICK PHINNEY, OF SAME PLACE, AND WILLIAM A. FROST, OF CAMBRIDGE-PORT, MASSACHUSETTS.

SHOE.

SPECIFICATION forming part of Letters Patent No. 282,184, dated July 31, 1883.

Application filed June 5, 1883. (No model.)

To all whom it may concern:

Be it known that I, PATRICK FOLEY, of Boston, in the county of Suffolk, of the Commonwealth of Massachusetts, have invented a new and useful Improvement in Shoes; and I do hereby declare the same to be described in the following specification and represented in the accompanying drawings, of which—

Figure 1 is a top view, Fig 2 a side elevation, and Fig. 3 a rear view, of a shoe of my improved kind. Fig. 4 is a top view of a piece of leather forming the body of the shoe, except the instep portion thereof, a top view of which is shown in Fig. 5.

This shoe is made of two pieces only of leather or other material, they being marked A and B. The part A, the pattern of which is shown in Fig. 4, is crowned or convex at the toe, as shown at a b c, and also at the heel, as represented at d e f, and is otherwise formed as shown at c g h i k l d a g' h' i' k' l' f.

In making the shoe the piece of leather A, shaped substantially as represented, is to have the edges c g and a g' turned up against and sewed to the toe part a b c. The edges g h and

g'h' are also to be sewed together. Next the edges d l and f l' are to be turned against and stitched to the edge d e f, and the edges k l and k'l' are to be sewed together. Next the instep portion B is to be inserted between the 30 edges him and h'i'm' and sewed thereto. The pieces so connected are next to be wet, and afterward to be lasted upon a last of proper form and allowed to dry thereon, they being subsequently properly trimmed and finished.

I claim as an improved manufacture—
The shoe made substantially as described—
viz., of the two pieces of material A and B,
formed, arranged, and connected essentially
as represented, and having edge portions of 40
the part B brought and sewed together at the
toe, and from thence to the instep, and also
having the rear edge portions of said part A
brought and sewed together at the base and
back of the heel, as explained.

PATRICK FOLEY.

Witnesses:

R. H. Eddy,

E. B. PRATT.