

(No Model.)

J. WEIDENMANN.
T-SQUARE.

No. 282,248.

Patented July 31, 1883.





Fig. 2.




Fig. 3.




Fig. 4.




Fig. 5.




Fig. 6.

WITNESSES:

Jos. H. Rosenbaum.
Richard Feichmann

INVENTOR

Jacob Weidenmann
BY *Paul Goepfer*
ATTORNEY

UNITED STATES PATENT OFFICE.

JACOB WEIDENMANN, OF NEW YORK, N. Y., ASSIGNOR TO KEUFFEL & ESSER, OF SAME PLACE.

T-SQUARE.

SPECIFICATION forming part of Letters Patent No. 232,248, dated July 31, 1883.

Application filed March 24, 1882. (No model.)

To all whom it may concern:

Be it known that I, JACOB WEIDENMANN, of the city, county, and State of New York, have invented certain new and useful Improvements in T-Squares, of which the following is a specification.

This invention relates to an improved construction of a T-square used by architects, engineers, and draftsmen generally, the improvements being designed to relieve the body from the physical strain caused by stooping over the board, and to obviate the foreshortening of the lines and figures on the board when the same fall into an oblique position from the stand-point of the designer, so that the work of the draftsman is facilitated and rendered more agreeable and accurate.

The invention consists of a T-square, the blade of which is provided with a raised longitudinal guide-rib near the center of the blade, and with a second longitudinal rib near the lower edge of the same, while between the ribs an intermediate opening or openings for holding a pencil, eraser, or other article, are arranged.

In the accompanying drawings, Figure 1 represents a perspective view of a drawing-board with my improved T-square. Fig. 2 is a top view; Fig. 3, a vertical transverse section of the same on line *xx*, Fig. 2. Fig. 4 is a vertical longitudinal section on line *yy*, Fig. 2; and Figs. 5 and 6 are vertical transverse sections through the head of the T-square, respectively, on lines *ff* and *cc*, Fig. 2. Similar letters of reference indicate corresponding parts.

Referring to the drawings, A represents the head, and B the blade, of my improved T-square. The T-square is especially designed to be worked with a drawing-board which is not supported in a horizontal or slightly-inclined position, but which is supported in nearly upright position, as shown in Fig. 1.

To use the T-square with advantage on a drawing-board supported at such an inclination, the head of the T-square is provided with suitable adjusting and clamping means whereby the T-square may be readily retained at

any point of the board, wherever it may be required by the draftsman, the adjustment being made in such a manner as not to impede or obstruct the quick, convenient, and accurate use of the T-square. For this purpose a guide-strip, C, is secured, by means of a suitable fastening, *a*, to the left-hand side of the drawing-board, the guide-strip serving as a guide along which the head of the T-square is moved. The strip C is provided with a longitudinal groove of any suitable cross-section, for guide tongues or runners *b*, secured to the under side of the head A of the T-square. A friction stop or clamp, D, is arranged in a recess between the tongues *b*, at the middle portion of the head A. The friction-clamp D is pressed tightly against the guide-strip C by means of a strong spiral spring, *e*. The friction-clamp D is released, so as to admit the adjustment of the T-square, by means of a slide-button, *d'*, which is connected by a pivot-pin, *d*, to the friction-clamp at its opposite end.

The parts so far described have been used heretofore, and I do not claim the same.

By these means the T-square is securely retained at any desired point on the drawing-board, and quickly and conveniently adjusted.

The blade of the T-square is provided with two longitudinal ribs, *ff*—one near the middle of the blade and the other near the lower edge of the same—as shown clearly in Figs. 1 and 2. The body of the blade between the ribs *ff* is provided with openings *f'*, Fig. 2. The uppermost rib *f* serves as a guide for the little finger of the right hand, so as to steady the pencil or drawing-pen. The lower rib *f* and the intermediate opening, *f'*, serve to hold the pencil, eraser, or similar articles used by the draftsman, so as to have them always handy for use. The ribs serve to strengthen the body of the T-square, while the openings decrease the weight of the same.

Having thus described my invention, I claim as new and desire to secure by Letters Patent—

1. In a T-square, a blade provided with a longitudinal rib near the lower edge of the T-square, and with openings in the body of the

blade above said rib, substantially as and for the purpose set forth.

2. In a T-square, a blade provided with longitudinal ribs—one near the center and the
5 other near the lower edge—and with intermediate openings between the ribs, substantially as and for the purpose set forth.

In testimony that I claim the foregoing as my invention I have signed my name in presence of two subscribing witnesses.

JACOB WEIDENMANN.

Witnesses:

PAUL GOEPEL,
SIDNEY MANN.