

(No Model.)

J. C. BOGGS.

HASP LOCK.

No. 282,607.

Patented Aug. 7, 1883.

Fig. 1.




Fig. 2.





Fig. 3.



Witnesses,

Geo. H. Strong.

J. H. Nourse

Inventor

John C. Boggs
By
Dewey & Co.
Attorneys

UNITED STATES PATENT OFFICE.

JOHN C. BOGGS, OF AUBURN, CALIFORNIA.

HASP-LOCK.

SPECIFICATION forming part of Letters Patent No. 282,607, dated August 7, 1883.

Application filed February 27, 1883. (No model.)

To all whom it may concern:

Be it known that I, JOHN C. BOGGS, of Auburn, county of Placer, State of California, have invented an Improved Extensible Hasp; and I hereby declare the following to be a full, clear, and exact description thereof.

My invention relates to a new and useful improvement in that class of hasps that are capable of being extended longitudinally to adapt them to their staples with ease and accuracy; and it consists in pivoting the lock-pin to the sliding portion through a slot in the stationary portion, as hereinafter fully described, and more particularly pointed out in the claim.

The nature of my invention will be seen from the following description and accompanying drawings, to which reference is hereby made.

Figure 1 is a perspective view. Fig. 2 is an edge view. Fig. 3 is a front elevation.

A represents a plate, having a pivot-hole, *a*, in one end, a socket, *b*, in the other end, and

an elongated slot, *c*, in its center. B is a plate fitting through the socket *b*, and adapted to slide therein; and C is the lock-pin, pivoted by a small pin, D, passing through the slot *c*, and secured in the sliding plate B behind. In this manner, as the plate B is extended or withdrawn, the lock-pin C moves with it to be in position to engage with the staple, with which the plate B is adapted to engage by means of the usual slot, *e*, in its end.

Having thus described my invention, what I claim as new, and desire to secure by Letters Patent, is—

A hasp consisting of the plate A, having an end socket, *b*, and a central slot, *c*, the plate B, having staple-slot *e*, and the lock-pin C, all secured together by the pivot bolt or pin *d* in slot *c*, substantially as herein described.

In witness whereof I hereunto set my hand.

JOHN C. BOGGS.

Witnesses:

JOHN M. FULWEILER,
F. D. ADAMS.