

(No Model.)

W. B. TAYLOR.
HEAD REST FOR CAR SEATS.

No. 283,533.

Patented Aug. 21, 1883.

Fig. 1.





Fig. 2.



Witnesses:
John M. Trohoy
A. L. White

Inventor
W. B. Taylor
by Wright & Brown
Attys

UNITED STATES PATENT OFFICE.

WILLIAM BELL TAYLOR, OF WALTHAM, MASSACHUSETTS.

HEAD-REST FOR CAR-SEATS.

SPECIFICATION forming part of Letters Patent No. 283,533, dated August 21, 1883.

Application filed April 23, 1883. (No model.)

To all whom it may concern:

Be it known that I, WILLIAM BELL TAYLOR, of Waltham, in the county of Middlesex and State of Massachusetts, have invented certain Improvements in Head-Rests for Car-Seats, of which the following is a specification.

This invention has for its object to provide an improved head-rest adapted to be applied to and supported by the back of a car-seat, and afford an easy support for the head of the person sitting therein.

The invention consists in a stout metal rod bent to form a marginal frame or support for a cushion or pillow attached thereto, and having its ends formed to bestride the upper edge of the seat-back and support said cushion or pillow in a position elevated above the back, as I will now proceed to describe.

Of the accompanying drawings, forming a part of this specification, Figure 1 represents an end view of a car-seat back provided with my improved attachment. Fig. 2 represents a perspective view of the attachment removed.

The same letters of reference indicate the same parts in all the figures.

In carrying out my invention I take a stout rod, of steel or other suitable metal, and bend the same centrally, so as to form a marginal frame, *a*, of an inverted-U shape. I then bend the rod laterally at the lower ends of the frame *a*, as shown at 2 2, then upwardly, as shown at 3 3, then backwardly, as shown at 4 4, and then downwardly, as shown at 5 5. The lower ends of the frame *a* bear against the front surface of the seat-back *c*. The bent portions 2 2 extend in opposite directions and offset the portions 3 3 from the frame *a*, so that the portions 3 3 also bear against the front surface of the seat-back. The bent portions 4 4 extend over the upper edge of the seat-back, and the portions 5 5 bear against the rear surface of the seat-back.

To the frame *a*, I attach a pillow or cushion, *d*, composed of any suitable upholstery material, and preferably formed to cover said frame, as shown in the drawings.

It will be seen that when the attachment is in place on the seat-back the cushion *d* projects above the back, with its front surface about in line with the front surface of the back, so that the cushion forms virtually a continuation of the back, and affords an easy support for the head of the occupant of the seat. The elasticity of the metal rod permits the frame *a* to yield sufficiently to afford ease to the recliner.

The attachment, having no connection with the seat-back excepting that afforded by the yokes *b b*, as already described, can be readily removed to enable the position of the back *c* to be reversed.

This improved device is simple and durable, and can be manufactured at a small expense.

I claim—

The metal rod bent centrally to form an inverted-U-shaped frame, then bent laterally in an opposite direction at the lower ends of said frame, as at 2 2, then extended upwardly, as at 3 3, from the laterally-curved portions, then bent backwardly, as at 4 4, so as to pass over the upper edge of a car-seat, and then down, as at 5 5, in combination with the cushion *d*, the covering of which extends over and forms a covering for the central portion of the rod, which portion of the rod forms a frame or support for the cushion, all substantially as described.

In testimony whereof I have signed my name to this specification, in the presence of two subscribing witnesses, this 26th day of April, 1883.

WM. BELL TAYLOR.

Witnesses:

CHAS. R. WILBER,
C. F. BROWN.