
## A. M. REEVES.

## PAPER BAG AND TWINE HOLDER.

No. 288,116.

Patented Nov. 6, 1883.



## United States Patent Office.

ABBOTT M. REEVES, OF MANSFIELD, ILLINOIS, ASSIGNOR TO HIMSELF AND WILLIAM W. BEATY, OF SAME PLACE.

## PAPER-BAG AND TWINE HOLDER.

SPECIFICATION forming part of Letters Patent No. 288,116, dated November 6, 1883.

Application filed September 7, 1883. (No model.)

To all whom it may concern:

Be it known that I, ABBOTT M. REEVES, of Mansfield, in the county of Piatt and State of Illinois, have invented a new and Improved 5 Paper-Bag and Twine Holder, of which the following is a full, clear, and exact description.

The object of my invention is to provide a new and improved device for holding a ball of twine and different sizes of paper bags or wrappers.

The invention consists of the combination and arrangement of parts, substantially as hereinafter fully set forth and claimed.

Reference is to be had to the accompanying drawings, forming a part of this specification, in which similar letters of reference indicate corresponding parts in both the figures.

Figure 1 is a side view of my improved pa-20 per-bag and twine holder. Fig. 2 is a plan view of the same.

A ring, A, is suspended by means of wires or chains B from a swivel-joint, C, provided with a hook, C', for suspending it from the ceiling, &c. A series of wires, D, project upward and inward from the ring, and on the upper ends of the said wires rests the annular flange E of a cup, G, which cup is adapted to receive a ball of twine, H. The lower ends of the wires D form hooks J, from which bags K are suspended, bearing the numbers of the different sizes of paper bags or wrappers. Hooks L project downward from the ring A, and from the said hooks spring-pins M are

suspended, which are constructed in the man- 35 ner of safety-pins. The pins are passed through the paper bags or wrappers, which are thus suspended from the same.

Different sizes of paper bags or wrappers can be held on the rings. To fasten paper 4c bags or wrappers in the pins M, the pins are removed from the hooks L and are passed through the bags or wrappers, and are then replaced on the hooks L. The special advantage of my improved device is that the twine-45 holder, as well as the bag-holders, can be removed simply and very readily for renewing the supply of twine or of bags.

Having thus described my invention, I claim as new and desire to secure by Letters Patent—50

1. The combination, with the ring A, of the upwardly-projecting wires D, the cup G, resting on the same, the hooks L, and the springpins M, suspended from the same, substantially as herein shown and described.

2. The combination, with the ring A, of the upwardly-projecting wires D, the lower ends of which form hooks J, projecting from the ring A, the tags K, suspended from the hooks J, the cup G, resting on the wires D, the hooks 6c L on the ring A, and the spring-pins M, suspended from the hooks L, substantially as herein shown and described.

ABBOTT M. REEVES.

Witnesses:
W. W. BEATY,
H. C. HIDY.