

(Model.)

T. A. SIMMONS.

HARNESS PAD.

No. 298,246.

Patented May 6, 1884.

FIG. I.




FIG. II.





FIG. III.



ATTEST.

Edward Stear
Geo. Wheelock

INVENTOR

Thomas A. Simmons
By Knight Bros.
attys

UNITED STATES PATENT OFFICE.

THOMAS A. SIMMONS, OF WOOSTER, OHIO, ASSIGNOR OF TWO-THIRDS TO
WELLS A. UNDERWOOD AND DUNCAN McMILLAN, BOTH OF SAME PLACE.

HARNESS-PAD.

SPECIFICATION forming part of Letters Patent No. 298,246, dated May 6, 1884.

Application filed November 12, 1883. (Model.)

To all whom it may concern:

Be it known that I, THOMAS A. SIMMONS, a citizen of Canada, now a resident of Wooster, in the county of Wayne and State of Ohio, have invented certain new and useful Improvements in Coach-Pads or Gig-Saddles, of which the following is a specification.

The object of the present invention is to make a coach-pad or gig-saddle for harness in such a manner as to dispense with all extra leather and hair or other stuffing employed, and to so simplify the labor in making the pad as to produce the same more quickly and at much less cost than is the case in the manufacture of gig-saddles now in use. To this end I form a metallic tree or pad-plate, upon which the saddle is formed, with flanges of such shape as to fit the curves of the animal's back. In my improved saddle the pad is made in a manner similar to that in the ordinary saddle, being, however, lined with felt or similar material, and provided with a metallic or other hard center, on which the metallic flanges of the tree will bear, and thus be prevented from projecting through the pad to injure the animal. The pad is secured to the pad-plate at the lower end by stitching through perforations in the plate made for this purpose. At the center of the back the pad is provided with a recess to admit the nut of the check-hook, such recess going through the leather cover of the pad, but having beneath it a felt backing to protect the horse therefrom.

In order that my invention may be fully understood, I will proceed to describe it with reference to the accompanying drawings, in which—

Figure I is a front view of my improved saddle. Fig. II is a vertical section of the same. Fig. III is a vertical section at right angles to the line of Fig. II. Fig. IV is a view of the pad-plate or tree detached.

In the manufacture of my improved saddle the tree or pad-plate 1 is made of lead or other metal, and provided with flanges 2, so curved at their edges as to adapt them to fit the back of a horse. The said plate is provided with apertures 3 3^a 3^b, for the attachment of the

check-hook 4, the terret 5, and the pin 6, by means of which the skirt 7 and the housing 8 are fixed to the pad-plate. At its lower end eyelet-holes 9 are made in the pad-plate, to enable the stitching of the same to the pad 10, having a leather top, and being padded beneath with felt or similar material. In order that the saddle may present a neat appearance, the recess 11 is cut through the leather of the pad at the top of the back, which recess is occupied by the nut 12 of the check-hook, but is not of sufficient depth to enable said nut to chafe the back of the horse. The sides of the flanges of the pad-plate are covered with japan or leather, the latter being sewed to the said plate if employed. In that part of the pad beneath the extended portion of the flanges 2, I place a plate, 13, of metal or other hard material, to give an even bearing for the said flanges on the back of the horse and prevent the pad from sagging between the flanges.

In making the saddle I first form the pad-plate, as described, with flanges projecting down on each side, and then the pad, which is then secured to the plate by stitching at the lower end. The skirt and housing, then being put in place, are secured to the saddle by nuts 14, hook 4, terrets 5, and pin 6.

Having thus described my invention, the following is what I claim as new therein and desire to secure by Letters Patent:

1. A metallic coach-pad plate or tree formed with the downwardly-projecting flanges, whose lower edges are curved substantially as shown, to conform to the shape of the horse's back.

2. The combination, with a metallic pad-plate having downwardly-projecting side flanges for giving shape to the saddle, of a pad provided with a metallic or other hard center plate adapted to bridge over the space between the said flanges, as and for the purpose set forth.

THOMAS A. SIMMONS.

Witnesses:

J. D. ROBISON, Jr.,
A. BARNHART.