(No Model.)

## J. M. DEXTER.

SOLE OR HEEL PLATE FOR BOOTS AND SHOES.

No. 300,854.

Patented June 24, 1884.

Fig.1.





Fig. 2.






Fig.4.

Attest: Court A Croker Josephine Campbell. Inventor: By John & Freeman Alto

N. PETERS, Photo-Lithographer, Washington, D. C.

## United States Patent Office.

JOHN M. DEXTER, OF ELMIRA, NEW YORK.

## SOLE OR HEEL PLATE FOR BOOTS AND SHOES.

SPECIFICATION forming part of Letters Patent No. 300,854, dated June 24, 1884.

Application filed July 5, 1883. (No model.)

To all whom it may concern:

Be it known that I, John M. Dexter, of the city of Elmira, county of Chemung, and State of New York, have invented certain Improvements in Coverings for the Wearing-Surfaces of Shoes, of which the following is a specification.

My invention is a covering for the wearingsurfaces of shoes, boots, and overshoes, con-10 structed, as fully described hereinafter, so as to be readily applied, securely affixed, prevent the rapid and uneven wear of the shoe, and secure such a hold upon the pavement as to prevent slipping.

15 In the drawings, Figure 1 is a sectional elevation of a shoe illustrating my improvement. Fig. 2 is an inverted plan view; Fig. 3, a perspective view illustrating the construction of the heel and sole pieces; and Fig. 4 is a detached section of the plate enlarged.

The shoe-covering consists of a thin plate of metal, A, corresponding to the portion of the shoe to which it is to be applied, either flat, or with side flanges to embrace the sides of the sole or heel, and a covering of rubber or cement so applied as to adhere firmly to the lower, or to both the lower and upper, faces of the plate, and in some instances serving as a means of attaching the plate immovably to the shoe. The plate is preferably perforated, or may be of wire-cloth.

Before applying the cement or covering sheet or coating, the surface of the plate should be roughened in any suitable manner, as by 35 filing, stamping, eating with acids, or by using a plate formed of wire-cloth. If the cement is to be of rubber, a sheet of the latter may be pressed upon the roughened surface of the article already made, as described, or a rubber 40 coating may be applied as a paint, and the plate may then be applied to the outsole or heel of the shoe, and retained in this position while the rubber is vulcanized, thereby securing a firm and secure connection of the plate 45 to the shoe by means of the vulcanized rubber. The plate so applied not only prevents the rapid wear of the shoe, but also tends to obviate that uneven wearing thereof, which is more destructive than any other wear that 50 comes upon the shoe. As the plate is thin, it \

adds but little to the weight of the shoe, and is also flexible, so that the shoe will spring as readily under the movements of the wearer as any ordinary shoe with a heavy leather sole.

The letter A indicates the plate, b the cov- 55 ering, and e the opening in the plate, and i flanges, shown as being upon the heel-piece, but they may be upon the sole-piece when flexibility in the latter is not required.

Although I have referred to a rubber covering, coating, or sheet, any other suitable covering may be employed—as, for instance, a sheet of thin fabric coated with rubber cement and vulcanized between the plate and the shoe.

It will be apparent that the coated or covered plates may be manufactured as articles of sale, to be disposed of to manufacturers of shoes, by whom they may be applied and secured.

The plates may be made by cutting each to its proper shape and then coating it, or by first preparing sheets of wire cloth, or perforated plate covered with rubber, &c., and cutting the required articles therefrom. This I do not 75 here claim, as it may form the subject of a separate application for Letters Patent.

I am aware that shoes have been made with rubber soles and with plates embedded therein, and do not claim this, broadly, my inven- 80 tion being distinguished by the fact that the rubber-coated flexible plate is adapted to be applied to the outsoles or heels of completed shoes.

I claim--

As an article of manufacture, a thin metal plate having its lower surface covered with rubber or its equivalent, conforming to the sole or heel of a boot or shoe, and provided with suitable means whereby it may be ce-90 mented thereto to form an over-sole having an outer elastic facing, as set forth.

In testimony whereof I have signed my name to this specification in the presence of two subscribing witnesses.

JNO. M. DEXTER.

Witnesses:
N. P. Fossett,

W. L. SMITH.