




(No Model.)

0. BULKELEY.

BALING BOX.

No. 305,508.

Patented Sept. 23, 1884.



**WITNESSES:**

John B. Deemer  
to Sedgwick

**INVENTOR:**

O. Bulkeley

BY

Mum Co

ATTORNEYS.



# UNITED STATES PATENT OFFICE.

OLIVER BULKELEY, OF DEXTER, TEXAS.

## BALING-BOX.

SPECIFICATION forming part of Letters Patent No. 305,508, dated September 23, 1884.

Application filed January 29, 1884. (No model.)

*To all whom it may concern:*

Be it known that I, OLIVER BULKELEY, of Dexter, in the county of Cooke and State of Texas, have invented a new and Improved  
5 Baling-Box, of which the following is a full, clear, and exact description.

Reference is to be had to the accompanying drawings, forming a part of this specification, in which similar letters of reference indicate  
10 corresponding parts in all the figures.

Figure 1 is a perspective view of my new and improved baling-box arranged with bale cloth and cords ready to receive the cotton or other material to be baled. Fig. 2 is a plan  
15 view showing the box opened out for removing the bale, and Fig. 3 is a detailed sectional elevation showing the method of securing the upright end board, A', to the bottom board, A.

The invention will first be described in connection with the drawings, and then pointed out in the claims.

In the drawings, A represents the bottom of the box. This is provided upon its under side with the fixed cross-pieces or cleats B B, and upon its upper side at one end with the  
25 end board A' and standards C C, which cleats project into the sockets *f*, made in the bottom board, A, said sockets being beveled downward and outward, and the outer edges of the standards C being notched and beveled to correspond, as shown at *f'*, Fig. 3, so that the  
30 board A' may be detached from the bottom board, A, and replaced at pleasure. The upper ends of the standards C C project above the upper edge of the end board, A', as shown in Fig. 1, for receiving the holding loops or  
35 bands D D, as hereinafter described. The cross-pieces B B reach past the edges of the bottom board, A, and the side boards, E E', of the box are hinged to them by means of the cleats F' F' and bolts *a a*. The cleats F' F' reach above the upper edges of the side  
40 boards, E E', so that when the said side boards are raised to vertical position the said loops D D may be placed over the upper ends of the cleats F' and over the upper ends of the cleats C C, as shown in Fig. 1, for holding the  
45 said side pieces, E E', in vertical position for forming the bale. Hinged to the rear edge of the side board E' is the end board G, which is provided with the flange *g*, and is adapted to be closed when the side boards, E E', are brought to vertical position and locked by the  
50 flange *g* and the hooks *b b*, attached to the side

board E, thus making a complete box, as  
shown in Fig. 1. The flange *g* prevents side strain on the hooks *b*.

In using the box the side boards, E E', and end G will be brought to vertical positions and locked by the loops D and hooks *b*, as  
shown in Fig. 1. Then the bale-cords H will be placed in the box with the ends thereof reaching over the upper edges of the side  
boards, E E', as shown, and then the bale-cloth I will be put in the box with the ends thereof  
65 reaching over the upper edges of the end boards, A' G. The cotton or other material to be baled will then be packed in by tramping it in the box, and when full the ends of the cloth I will be brought over the bale and  
70 the whole tied by the cords H H, thus completing the bale, which may be removed from the box by removing the loops D D from the upper ends of the cleats F' C and lifting the hooks *b*, which will permit the side boards,  
75 E E', and end board G to open, thus leaving the bale free to be rolled off the box. The box will then be set again and the side boards and end board G secured, as before, ready to form another bale. In this manner it will  
8c be seen that the box is very convenient and adapted for quick and easy handling, and is cheap, durable, and practical.

Having thus fully described my invention, I claim as new and desire to secure by Letters  
85 Patent—

1. In a baling-box, the bottom board, A, having cleats B B, and end board A', and fixed standards C C, that reach above the end board A', in combination with the hinged side  
90 boards, E E', and end board G, hinged to board E', the boards E E' being provided with cleats F', that reach beyond the edges of the boards to receive the loops D, substantially as and for the purposes set forth.

2. In a baling-box, the end board A' and standards C, held to the bottom A, in combination with the hinged side boards, E E', provided with cleats F', the said standards and cleats being of greater length than the depth  
100 of the box, substantially as and for the purposes set forth.

OLIVER BULKELEY.

Witnesses:

S. C. BULKELEY,  
I. C. TETER,  
J. E. TETER.