




(No Model.)

G. W. JACKMAN.

SCREW DRIVER.

No. 306,491.

Patented Oct. 14, 1884.



Witnesses:  
John Buckler,  
Edward Jordan

Inventor:  
George W. Jackman.

# UNITED STATES PATENT OFFICE.

GEORGE W. JACKMAN, OF LITTLETON, NEW HAMPSHIRE.

## SCREW-DRIVER.

SPECIFICATION forming part of Letters Patent No. 306,491, dated October 14, 1884.

Application filed February 16, 1884. (No model.)

*To all whom it may concern:*

Be it known that I, GEORGE W. JACKMAN, of the village of Littleton, in the county of Grafton and State of New Hampshire, have  
5 invented a new and useful Improvement in Screw-Drivers, of which the following is a specification.

The invention relates to the means by which screw-drivers may be made to grasp  
10 and hold screws preparatory to and while being driven; and it consists in adapting and adjusting the jaws of the screw-driver to enter necks and clasp spines in the heads of screws, and thereby securely hold the latter. It is  
15 designed especially for screws invented by me, for which invention a patent was allowed July 8, 1884; but it may be applied to bolts and all other articles having heads similarly constructed and admitting of being clasped,  
20 held, and driven into position by the like means.

In the accompanying drawings, in which similar letters of reference indicate like parts. Figure 1 represents a screw-driver engaged  
25 with a screw as contemplated by my invention. A represents the handle; B B, the two jaws, which are made integral with the shank or tang that enters the handle, said jaws having lateral notches *a a* on the inner side of their  
30 lower extremities to embrace corresponding parts of the spine in the screw-head; and C, a lever rigidly attached to one of the jaws, and made integral therewith, by means whereof the jaws may be forced apart, so as to admit of their extremities being introduced into  
35 the nicks in the screw-head, and made to clasp and hold the spine therein. D is a slide for confining the end of the lever when required. E indicates the screw; *b b*, nicks in its head;  
40 *c*, the spine formed by the nicks on either side thereof, which are sunk into the top of the screw-head, extend across it, and are widened at bottom, as shown, in such manner as to leave a spine between them, also extending across  
45 the top of the screw-head and having a notch in each side below the crown. *c'* indicates the crown, and *c''* the base of the spine.

Fig. 2 represents a section of a screw-head transverse to the nicks and spine, and shows  
50 on a larger scale the engagement of the screw-driver with the screw in the same manner as is shown in Fig. 1.

Fig. 3 represents a like section of the screw-head and a like engagement of the screw-driver with the screw, except that here the  
55 notches in the extremities of the jaws, instead of being rectangular, are triangular in outline to adapt them to corresponding variations in the form of the spine. The jaws of the screw-driver are held together by force of  
60 the spring in the material of which they are composed, but are capable of being forced apart by means of the lever.

The jaws in the several figures of the drawings are represented with rectangular or tri-  
65 angular notches in their extremities; but, instead of these, grooves or recesses of any suitable form may be employed.

The advantage claimed for this invention is its adaptation to grasp, hold, and control a  
70 screw formed as described, and control the same while being applied to the object into which it is desired to insert it, and while it is being driven into its intended position, and to accomplish this with little danger of rup-  
75 turing the screw-head.

What is claimed as patentable in this invention is—

A screw-driver having a pair of jaws made integral with the shank or tang that enters the  
80 handle, the said jaws having lateral grooves or recesses on the inner side of their lower extremities, and being capable of being forced apart by means of a lever rigidly attached to one of the jaws and made integral therewith,  
85 all substantially as set forth and described.

GEORGE W. JACKMAN.

Witnesses:

E. C. STEVENS,  
B. F. ROBINSON,  
HENRY F. GREEN.