

(No Model.)

H. D. WARD.  
LEG BRACE FOR HORSES.

No. 308,114.

Patented Nov. 18, 1884.

FIG. 1.




FIG. 2.




FIG. 3.





FIG. 4.



Witnesses;  
Geo. Layne  
John C. Dewey.

Inventor;  
Henry D. Ward

# UNITED STATES PATENT OFFICE.

HENRY D. WARD, OF WORCESTER, MASSACHUSETTS.

## LEG-BRACE FOR HORSES.

SPECIFICATION forming part of Letters Patent No. 308,114, dated November 18, 1884.

Application filed June 23, 1884. (No model.)

*To all whom it may concern:*

Be it known that I, HENRY D. WARD, a citizen of the United States, residing at Worcester, in the county of Worcester and State of Massachusetts, have invented a new and useful Device for Straightening and Strengthening Horses' Legs, &c., of which the following is a full, clear, and exact description, reference being had to the accompanying drawings, making  
10 a part of this specification, in which—

Figure 1 represents a side view of the front leg of a horse with my device attached thereto. Fig. 2 represents on an enlarged scale a central longitudinal section through the device shown in Fig. 1; and Figs. 3 and 4 represent modifications of my device, as will be hereinafter fully described.

My invention relates to a device especially designed to be used for the purpose of straightening and strengthening horses' legs which have become knee-sprung or weakened from any cause. It is applied and attached to the leg of the horse in substantially the manner shown in Fig. 1 of the drawings; and it consists of two flat pieces of metal or other substance pivoted or hinged together, to allow of the bending of the leg, if desired, when the device is in place, and having one or more spiral springs or other suitable tension devices, said tension devices being secured to the said flat pieces in substantially the manner shown, for the purpose of drawing the said pieces toward each other and bringing a pressure to bear upon the knee when the device is in use.  
35 The flat pieces and the springs may be covered with leather or other suitable material, and are provided with straps or means for attaching the device in position and holding it in place when in use. A padding or filling may  
40 be used to furnish a cushion-surface to press against the leg.

In the drawings, A represents a horse's leg, and B my device attached thereto. The device B is made of two flat pieces of metal or other substance, C and D, of substantially the shape shown in the drawings, with their ends hinged or pivoted together, as shown at a, Fig. 3, so as to allow of their bending in either direction. A spiral spring, E, is secured to

the parts C and D in any suitable manner; 50 one end being fastened to the part C and the other end to the part D, so that the parts C and D, hinged together, will be drawn toward each other.

In Fig. 3 I have shown two spiral springs; 55 and three or more may be used, if desired, as I do not wish to limit myself to the use of a single spring or tension device.

In Fig. 4 I have shown one end of the spring attached to the part C or D by means 60 of an eye, b, passing over a bolt, c, provided with a thumb-nut, d, to allow of that end of the spring being raised or lowered, if desired.

In lieu of the spiral springs E shown in the drawings, any other equivalent and well-known 65 tension device may be used—as rubber bands, &c.—and the degree of tension may be varied as desired.

The parts C and D and the spring or springs E may be covered with leather, F, or any other 70 suitable material, as shown, to which are secured straps G; but said straps may be secured directly to the parts C and D, if preferred, and in lieu of said straps G any other suitable and well-known means may be employed for attaching the device B to the leg 75 of the wearer. A padding or filling, H, may be used to make a soft surface to press against the leg; but this padding may be dispensed with, if desired. The covering F may also be 80 dispensed with, and only the parts C and D, hinged together and provided with a tension device for drawing the parts toward each other, and means for attaching them to the wearer, be used. 85

I have stated that my device is especially designed to be used on horses' legs for straightening and strengthening them; but it may also be used, if desired, upon the legs of any other animals, and also upon the legs or arms 90 of human beings.

Having described my improved device for straightening and strengthening the legs of horses or other animals, what I claim as new and of my invention, and desire to secure by 95 a patent, is—

1. A straightening and strengthening device composed of two parts hinged or pivoted



together in substantially the manner shown,  
and having one or more spiral springs or ten-  
sion devices secured thereto, for the purpose  
stated, and means for attaching the device,  
5 substantially as shown and described.

2. The combination, with the parts C and  
D, hinged or pivoted together, and one or

more spiral springs, E, secured thereto, of the  
covering F and straps G, substantially as  
shown and described.

HENRY D. WARD.

Witnesses:

JOHN C. DEWEY,  
GEO. LAYNG.