
(No Model.)


J. C. HUTHER.


PLASTERING TROWEL.

No. 316,464.

Patented Apr. 28, 1885.







Attest: M. Turlong. G. S. Othitcoms.

Inventor John C. Huther. By E.B.Whitmore. Atty.

United States Patent Office.

JOHN C. HUTHER, OF ROCHESTER, NEW YORK.

PLASTERING-TROWEL.

SPECIFICATION forming part of Letters Patent No. 316,464, dated April 28, 1885.

Application filed January 17, 1885. (No model.)

To all whom it may concern:

Be it known that I, John C. Huther, of Rochester, in the county of Monroe and State of New York, have invented a new and useful Improvement in Plastering-Trowels, which improvement is fully set forth in the following specification, and shown in the accompanying drawings.

My invention relates to the handles of plasto tering-trowels; and it consists, substantially,
in constructing the handleso as to be adjustable
both vertically and longitudinally with reference to the blade, the invention being fully
described in the following specification, and
more particularly pointed out in the claims.

Referring to the drawings, Figure 1 is a side elevation of my improved plastering-trowel, showing the handle in various positions of adjustment in dotted lines; Fig. 2, a plan of the same; Fig. 3, an end elevation viewed as indicated by arrow in Fig. 2, drawn to show more fully the means by which the vertical adjustment of the handle is effected, parts being sectioned on the dotted line y; and Fig. 4, a transverse section of one of the standards b, taken on the dotted line x in Fig. 3, and viewed as indicated by arrows drawn to show

as indicated by arrow, drawn to show more fully the vertical groove or seat in said standard.

Referring to the parts, A is the blade of the trowel, and B the handle thereof. The blade is provided with a rigid longitudinal rib, k, having its sides cut under or dovetailed, as shown in cross-section in Fig. 3.

35 b are two similar standards rising from the blade to form supports for the handle B. The standards b are each provided with a horizontal foot, g, both of which feet are grooved upon their under surfaces to fit the undercut or dovetailed rib k, as shown, and are intended to slide along said rib to permit longitudinal adjustment of the handle. The standards b are each further provided with a vertical groove, e, on their outer faces. The handle B

is provided at each end with a plate or sup- 45 port, a, secured rigidly thereto, which supports, respectively, are made to fit and slide within the vertical grooves e of the standards, by means of which the handle may be vertically adjusted with reference to the standards 50 and the blade of the trowel. These supports are each provided with a vertical slot, f, through each of which a clamping screw or fastener, d, for the support passes, being secured in the standard back of the support. 55 These fasteners serve to hold the handle in positions of vertical adjustment. A screw, i, passing vertically through the foot g of one of the standards and bearing against the upper surface of the rib k, serves to secure the han- 60 dle in positions of longitudinal adjustment.

What I claim as my invention is—

1. The blade of a plastering-trowel, provided with an undercut or dovetail rib, k, secured thereto, in combination with standards 65 b b for the handle, adjustably fitted to the rib k, with a fastening device, i, for the said standards, and the vertically-adjustable handle B, secured to the adjustable standards b b, substantially as shown and described.

2. In combination with the standards b b, extending upward from the blade of a plastering-trowel, the handle B, provided at its ends with supports a, adjustably connected with said standards, substantially as and for 75 the purpose set forth.

3. The combination of the standards b b, rising from the blade of a plastering-trowel, provided with vertical grooves e e, and the handle B, provided with supports a a, fitted 80 to the grooves e, with fastening devices d d, to hold the standards and supports together, substantially as specified.

JOHN C. HUTHER.

Witnesses:

E. B. WHITMORE, M. E. FURLONG.