

(No Model.)

W. M. WALSH.

COFFIN.

No. 318,837.

Patented May 26, 1885.

FIG. 1.




FIG. 2.





FIG. 3.



ATTEST.  
J. Henry Kaiser  
Jacob Felbel.

INVENTOR.  
William M. Walsh.  
By  
J. N. M. Luntire  
Att'y.



# UNITED STATES PATENT OFFICE.

WILLIAM M. WALSH, OF PHILADELPHIA, PENNSYLVANIA, ASSIGNOR OF  
ONE-HALF TO WILLIAM KEHRER, OF SAME PLACE.

## COFFIN.

SPECIFICATION forming part of Letters Patent No. 318,837, dated May 26, 1885.

Application filed January 15, 1885. (No model.)

*To all whom it may concern:*

Be it known that I, WILLIAM M. WALSH, of Philadelphia, in the county of Philadelphia and State of Pennsylvania, have invented  
5 a new and useful Terra-Cotta Coffin-Box or Burial-Case; and I do hereby declare that the following is a full, clear, and exact description thereof, reference being had to the accompanying drawings, making part of this application.

10 Previous to my invention the more common practice has been to inclose the casket or coffin usually employed for burial purposes within a simple box of wood, although other materials have been sometimes employed as  
15 an exterior or enveloping case, and a coffin-case or burial-casket composed itself of terra-cotta has been suggested and patented for the purpose of greater preservation of the interred body.

20 My invention has for its main ends and objects to provide for general use (in the different qualities required, according to the pecuniary capacity of the purchaser) cases or boxes within which ordinary coffins and their  
25 contents can be hermetically sealed up, and which, while comparatively imperishable, can be readily and cheaply manufactured in various sizes, will not be too heavy to permit handling about as conveniently as the common  
30 boxes now in use for enveloping coffins and their contents, will not be liable, though composed of frangible material, to get broken under any usual conditions of handling and transportation, and shall, by reason of the  
35 presence of suitable handles or lifter devices, be rendered easy of carriage and management without any injurious strain on the frangible material composing the receptacle.

To these main ends and objects my invention  
40 may be said to consist in the novel construction of a terra-cotta coffin (or casket) receptacle which will be hereinafter fully described, and the novel features of which will be particularly pointed out and defined in the claims of this  
45 specification.

To enable those skilled in the art to which my invention relates to make and use the latter, I will now proceed to more fully describe it, referring by letters to the accompanying drawings, which form part of this specification,

and in which I have shown my invention carried out in the best form now known to me and as I propose to practice it.

In the drawings, Figure 1 is a perspective view of one of my coffin-cases or terra-cotta  
55 boxes in a closed or sealed condition. Fig. 2 is a vertical cross-section at the line *xx* of Fig. 1, and Fig. 3 is a detail partial horizontal section on an enlarged scale at *yy* of Fig. 2.

In the several figures the same part will be  
60 found designated by the same letter of reference.

A is the body or box portion of the case, and B the lid, each of which is manufactured of terra-cotta by the usual processes, and either  
65 the interior or exterior, or both, surfaces of which box portion and lid are glazed or vitrified, with the exception of the top edge of the portion A and so much of the inner surface of the lid B as is designed to come into con-  
70 tact with said top edge of A. The object of always leaving unglazed these portions is that they may be perfectly cemented together in the operation of closing up the case for interment of its contents, in order that the case  
75 may thus be hermetically sealed.

C C are two (more or less) metallic hoops, preferably iron, which surround the body portion A of the case exteriorly, and which are for the purpose of re-enforcing or strengthen-  
80 ing the portion A in order that it may be made much lighter—i. e., of much less material—than could be used were only the terra-cotta relied on to withstand all the torsional strain and sudden shocks to which the case  
85 may possibly be subjected in transportation and handling.

To render the action of the re-enforcing hoops or bands C C more effectual, they may be heated immediately before placing them  
90 around the case, so that they will shrink on, thus binding the case more securely.

D D are metallic bands to co-operate with another pair of somewhat similar devices, E E, in a manner to be presently explained, for the  
95 purpose of holding the lid B and the box portion A securely together, and at the same time strengthening or re-enforcing the entire case, when closed up, transversely. As clearly shown, each of the metallic bands D extend  
100



up each side of the box portion A to an extent preferably equal to about two-thirds of the height of said side, and each end of each band D has a laterally-projecting end portion, *d*, that is perforated for the accommodation of a short bolt, such as seen at *e*, which, together with its nut *f*, is used to draw together and securely unite said portion *d* of the band D, and a similar part, *g*, formed on each end of each of the bands E, and similarly perforated for the accommodation of said bolt. Preferably each of the bands D has formed in each of its leg-like portions a recess, as at *i*, (see Fig. 2,) to accommodate the lower one of the bands C, while in like manner each of the leg-like portions of the bands E is recessed to accommodate the upper one of the longitudinal bands C.

By reference to Fig. 3 it will be clearly seen that the size of the head *e*<sup>2</sup> of each bolt *e* is such, and the location of the hole in the part *d* of each band D is such, that when in place one side of the head *e*<sup>2</sup> of each bolt comes parallel with the leg-like part of D, and so near to it that the bolt *e* cannot turn round in its hole, by which arrangement the nut *f* (which is made enough smaller than the head *e*<sup>2</sup> to clear the leg-like part of the lid-band E while turning on the bolt *e*) may be readily turned by a wrench on the threaded portion of *e* to draw the portions *d* and *g* together, and force each pair of bands or straps D and E snugly home to their bearings for the double purpose of securely clamping on the lid B and re-enforcing the closed terra-cotta case or receptacle. Of course other modes of fastening together the adjacent ends of the pairs of bands D and E may be adopted.

For the sake of convenience in handling the case, especially when lowering it into a grave in the operation of interment, I have provided the upper one of the longitudinal metallic bands C at either side of the case with two (more or less) handles or hand-rings, *m m*. These devices may be made as shown, or they may be of any other desired construction, and, if desired, similar devices may be applied to either the lower one of the bands C, or to the bands D, or to both. Under any construction and arrangement of the hand-rings or handles, combined with any one or more of the metallic devices of the case, the latter may at any time or under any circumstances be lifted or carried without any such strain on the fragile material composing the case as would be liable to fracture it were hand-rings or any handle-like devices applied or secured directly to the terra-cotta material. It will be understood, of course, that in practicing my invention various modifications in the forms and precise arrangement shown of all the parts may be made according to the size and quality of the case, and as the experience of the manufacturer may dictate will be expedient.

In the manufacture of my improved cases the common brown glazed surface seen on the exterior of and the material used for

ordinary earthenware drain-pipes, may be adopted for a cheap article, while for a more expensive sample of my invention the finer grades of compounds coming under the generic head of "terra-cotta" may be employed, presenting the appearance and conditions of porcelain wares. In all cases, however, whether the manufacture be in the lower or higher grades of terra-cotta ware, care should be taken to avoid any vitrification or glazing of either the top edge of the body A or that portion of the surface of lid B designed to come in contact with said top edge, because I consider it quite important, for sanitary reasons, that these portions should present the best possible conditions for hermetically sealing the joint between the lid B and the body A. In sealing the joint between these parts any of the most approved materials for and processes of effecting a perfect and durable cementation of the parts together may be adopted.

Having now so fully explained my invention that those skilled in the art to which it relates can fully understand and practice it, what I claim as new, and desire to secure by Letters Patent, is—

1. A terra-cotta case or box adapted to the reception of the ordinary coffin or burial casket, and provided, as shown, with longitudinally-arranged metallic strengthening bands or hoops C C, all substantially as and for the purposes described.

2 A terra-cotta box or case adapted to the reception of a burial casket or coffin, and having its body portion and lid glazed or vitrified on either their interior or exterior surfaces, or both, with the exception, however, of the upper edge of the body portion A and that portion of the lowermost or inner surface of the lid B which comes directly opposite to the edge of said body portion, in order that a perfect cementation of the body portion and lid of the case may be effected, all as hereinbefore set forth.

3. In combination with the body or box portion A and the lid B of a terra-cotta case, longitudinal metallic hoops or bands C C, transversely arranged, clamping or securing bands D D and E E, and means for securing together the adjacent ends of the said transversely-arranged bands, all substantially as and for the purposes hereinbefore set forth.

4. In combination with a terra-cotta box or case provided with metallic strengthening and clamping devices substantially such as specified, a series of handle-like devices applied to some one or more of the said metallic devices, all substantially in the manner and for the purposes hereinbefore explained.

In witness whereof I have hereunto set my hand this 29th day of December, 1884.

WILLIAM M. WALSH.

In presence of—

F. P. KELRER,

WM. R. NICHOLSON.