
(No Model.)


## E. C. MERSHON. CUTTER HEAD.

No. 329,756.

Patented Nov. 3, 1885.



## Fig. 2.



MITNESSES Phillollasi. Bon. Furgitt.

INVENTOR

8.6. Mershou,

Ouders on & finith

his Attorneys

## United States Patent Office.

EDWARD C. MERSHON, OF EAST SAGINAW, MICHIGAN.

## CUTTER-HEAD.

SPECIFICATION forming part of Letters Patent No. 329,756, dated November 3, 1885.

Application filed June 17, 1885. Serial No. 168,979. (No model.)

To all whom it may concern:

Be it known that I, EDWARD C. MERSHON, a citizen of the United States, residing at East Saginaw, in the county of Saginaw and State of Michigan, have invented certain new and useful Improvements in Cylinders for Planing-Machines; and I do declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the art to which it appertains to make and use the same, reference being had to the accompanying drawings, and to letters or figures of reference marked thereon, which form a part of this specification.

Figure 1 of the drawings is a representation of an end elevation. Fig. 2 is a side eleva-

tion.

This invention relates to cylinders for planing-machines; and it consists in the construc-20 tion and novel combination of parts, as will be hereinafter fully described, and particu-

larly pointed out in the claim.

Referring by letter to the accompanying drawings, A designates a planing-cylinder, 25 which is made in sections of two or more heads, B, according to the size of the machine in which the planing-cylinder is used. Said heads B are fitted to an arbor, C, of the usual pattern. Spaces D are left between the heads, 30 instead of constructing them in one solid piece, as heretofore. The heads B are connected together by two or more longitudinal iron or steel bars, C' C' C' C', to secure the requisite strength and stiffness, and at the same time forming the same style or form of cutting-edge as is now provided in the old form of cylinder.

Edesignates the cutting-knives, which, with

this construction of cylinder, are held by being clamped between C'C'C'C' and cap F, and 40 may be made of very light, thin, and narrow strips of steel. Furthermore, by a different construction, the bars C' C' C' C' or the clamping-caps F may be dispensed with and knives of the common description used without de- 45 stroying the stiffness and strength of cylinder. Further, this construction admits of balancing each head separately, and thereby insuring a perfect balance and a lighter head, which will run steadier at the highest rate of 50 speed and will do more and better work than the cylinder now commonly used. This construction admits of the removal of two of the knives E and the substitution of beadingknives in making ceiling, or other shaped 55 knives in working moldings.

Having thus fully described my invention, what I claim as new, and desire to secure by Letters Patent of the United States, is—

A planing-machine cylinder comprising a 60 plurality of heads having central transverse apertures and threaded face-recesses, plain longitudinal bars having perforations arranged to coincide with the face-recesses of the said heads, bolts for securing the bars to 65 the heads, blade-clamping caps recessed on their under sides, and bolts for securing the caps to the heads, all combined and arranged for joint operation, substantially as specified.

In testimony whereof I affix my signature in 70 presence of two witnesses.

EDWARD C. MERSHON.

Witnesses:

WILLIAM B. MERSHON, JOHN J. WHEELER.