

.

.

•

.

.

•

•

.

•

ô

•

•

.

.

.

WITNESSES: And Beyon OMblark W Ъ

.

•

۶.

-

Y GO Oryd Munn HC BΥ ATTORNEYS.

.

٠ N. PETERS, Photo-Lithographer, Washington, D. C.

a

с. -.

	·
•	• • • • • • • • • • • • • • • • • • •

· · · ·

· · · · · · ·

· .

UNITED STATES PATENT OFFICE.

GEORGE H. BOYD, OF MARYSVILLE, CALIFORNIA.

## SUSPENDERS.

SPECIFICATION forming part of Letters Patent No. 332,479, dated December 15, 1885.

Application filed September 22, 1885. Serial No. 177,914. (No model.)

To all whom it may concern: Be it known that I, GEORGE H. BOYD, of Marysville, in the county of Yuba and State of California, have invented new and Im-5 proved Suspenders, of which the following is a full, clear, and exact description.

The object of my invention is to provide new and improved suspenders which fit well, are convenient, do not draw the pants nor tear 10 off buttons, and rest well.

The invention consists in suspenders constructed as will fully be described and set forth hereinafter, and pointed out in the claims.

The bands or straps may be made of webbing, 35 leather, &c.

The suspenders are attached to the waistband of the pants at the front and sides only, and thus the suspenders rest very easily, do not interfere with stooping or bending, and 40 the suspenders and the buttons are not subjected to any undue strains, especially in stooping and bending.

Having thus described my invention, I claim as new and desire to secure by Letters Patent-- 45 1. A pair of suspenders having the front ends of the shoulder bands or straps passed through buckles on buckle-straps having but-Reference is to be had to the accompanying | ton-holes in the front end, and having their rear ends secured to the shoulder-bands, sub- 50 stantially as herein shown and described. 2. In a pair of suspenders, the combination, with the crossed bands A, having their front ends united to the buckles C and their rear ends provided with button-holes, of buckle- 55 straps B, passed through the buckles C, having button holes at their front ends, and having their rear ends connected with the straps A a short distance above the button-holes at the rear ends of said straps, substantially as here- 60 in shown and described.

15 drawings, forming a part of this specification, in which similar letters of reference indicate corresponding parts in both the figures.

Figure 1 is a perspective view of my im-20 proved suspenders on the body. Fig. 2 is a perspective view of the same detached.

The suspenders consist of the two shoulder straps or bands, A, and the two buckle straps, B, and the buckles C, held on the straps B.

- 25 The buckle-straps B are each provided at the front end with a button-hole, b, for receiving the front button, D, on the pants, and the rear ends of the buckle-straps B are secured to the shoulder-bands A a short distance above the
- 30 back ends of the same, which back ends have button-holes a for receiving the side buttons, E. The buckle-straps B pass freely through the buckles C. The shoulder-straps A are crossed on the back in the usual manner.

## GEORGE H. BOYD.

Witnesses:

ORTIS F. LEE, WM. ENGLAND.

. .

•

· · 

. 

. . -

.

·			
		:	
	· · ·		