



J. S. RAWORTH.

ELECTRIC METER.

No. 332,832.

Patented Dec. 22, 1885.



Witnesses:
O. Fred. Keller
J. B. Langer

Inventor,
John S. Raworth
By C. S. Whitman
Att'y

J. S. RAWORTH.

ELECTRIC METER.

No. 332,832.

Patented Dec. 22, 1885.

FIG. 6.





FIG. 3.



Witnesses:
Wm. H. Keller.
J. B. Lanyon

Inventor:
John S. Raworth
By C. S. Whitman
Atty.

(No Model.)



3 Sheets—Sheet 3.

J. S. RAWORTH.

ELECTRIC METER.

No. 332,832.

Patented Dec. 22, 1885.



Witnesses:
L. Fred Keller
J. B. Langen

Inventor:
John S. Raworth
By C. S. Whitman
Atty.

UNITED STATES PATENT OFFICE

JOHN SMITH RAWORTH, OF MANCHESTER, COUNTY OF LANCASTER, ASSIGNOR
TO SIEMENS BROTHERS & COMPANY, (LIMITED,) OF 12 QUEEN ANNE'S
GATE, WESTMINSTER, COUNTY OF MIDDLESEX, ENGLAND.

ELECTRIC METER.

SPECIFICATION forming part of Letters Patent No. 322,392, dated December 22, 1885.

Application filed September 12, 1885. Serial No. 175,931. (No model.) Patented in England May 13, 1884, No. 7,539.

To all whom it may concern:

Be it known that I, JOHN SMITH RAWORTH, a citizen of England, residing at Manchester, in the county of Lancaster, England, have invented a new and useful Electric Meter, (for which I have obtained a patent in Great Britain, No. 7,563, dated May 18, 1884,) of which the following is a specification.

My invention relates to an electric meter—that is to say, an instrument for measuring the electric current in a circuit, in which case it may be termed an "electro-dynamometer," or with suitable modifications, for measuring the electro-motive force, in which case it may be called a "volt-meter." For both purposes the principles of action are the same, but the construction is so far modified as to suit two different conditions, the chief modification being in the character of the coils employed. In the one case, for the electro-dynamometer, a coil-conductor of large sectional area and very low resistance is used; in the other case, for the volt-meter, coils of fine wire and very high resistance are used.

I will describe both forms, referring to the accompanying drawings, in the several figures of which the same reference-letters are as much as possible employed to indicate corresponding parts.

Figure 1 is a vertical section, and Fig. 2 is a sectional plan, of an electro-dynamometer according to my invention, Fig. 3 being a front view showing the parts immediately behind the dial, which is supposed to be removed.

Fig. 4 is a vertical section, and Fig. 5 a sectional plan, of the modified form of the instrument constituting a volt-meter, Fig. 6 being a transverse section.

A is an iron spindle delicately pivoted at its ends, where there are two iron arms, *a a*, projecting from it in opposite directions. Around the spindle A there are conducting-coils B, consisting, for the electro-dynamometer, as shown in Figs. 1 and 2, of a few convolutions of copper bar of rectangular section helically wound without contact with each other; but in the volt-meter, as shown in Figs. 4 and 5, consisting of numerous convolutions of fine insulated wire. In either case, when

these coils are acted on by electricity, the spindle A becomes polarized, its arms *a a* constituting polar extensions of the magnet into which it is converted.

As shown in Fig. 1, the electric current entering, by the post C passes along a metallic framing, *C' O' C'*, through the coil B and out by the post D, or in the reverse direction. In passing along the parts of its circuit *C'* and *O'*, which are parallel to the arms *a a*, it tends to deflect them, and so to turn the spindle A partly round with more or less force, according as the current is greater or less.

As shown in Figs. 4, 5, and 6, the electric current entering by the post C passes through a number of convolutions of fine insulated wire, *C' O' C' O'*, wound round a rectangular casing, E, outside the spindle A and its coil B. In this case also the current in the parts *C'* and *O'* of the rectangular coil is parallel to the arms *a a* and tends to deflect them the more the greater the electro-motive force.

At the front end of the spindle A is fixed a light index-wire, F, which may be of aluminium. It is counterbalanced by an adjustable weight, F', and is bent forward so as to project through a hole in a dial, G. Through this dial passes a central spindle, H, which can be turned by hand, and which has fixed to its inner end the innermost convolution of a volute spring, K, the outermost convolution of which is connected by an arm, *k*, to the index-wire F.

On the spindle H, outside the dial G, and protected by a glass, L, there is fixed an index, M, pointing to graduations on the dial.

When the instrument is put in circuit, the spindle H is turned by hand until the force of the volute spring K is made to balance the force tending to turn the spindle A by deflecting the arms *a a*, as can be seen by observing the point of the wire F, just vibrating within the hole of the dial through which it passes. The index M will then point to a graduation on the dial G, by which can be ascertained the number of amperes in the current acting on the electro-dynamometer, or the number of volts in that acting on the volt-meter.

As shown in Figs. 4 and 5, a key, N, pressed

upward by a spring can be used to put the volt-meter in circuit by pressing down this key by the finger, and thereby bringing into contact two metallic springs, *n n*, by which the circuit of the instrument is closed.

No claim is made to features disclosed in this application which are claimed in the application No. 157,077, filed February 25, 1885.

Having thus described the nature of my invention and the best means I know for carrying it out in practice, I claim—

The combination of the spindle A, having two small arms, *a a*, projecting from it in opposite directions, conducting-coils B, consisting of numerous convolutions of fine insulated wire arranged around the spindle, the rectangular casing E, having a number of convolu-

tions of insulated wire, *C' C' C' C'*, wound around it, the index-wire F, counterbalanced by an adjustable weight, *F'*, and projecting through the dial G, the central spindle, H, passing through the dial, and the volute spring K, connected by the arm *k* to the index-wire, as and for the purpose described.

In testimony whereof I have signed my name to this specification, in the presence of two subscribing witnesses, this 13th day of August, A. D. 1885.

JOHN SMITH RAWORTH.

Witnesses:

CHAS. M. DORMAN,
31 *Ackers St., Manchester.*

JOHN WM. MACLEAN,
50 *Bishop St., Manchester.*