

(No Model.)

G. A. TAYLOR.

STOVE.

No. 335,974.

Patented Feb. 9, 1886.

Fig. 1.




Fig. 2.





Fig. 3.



WITNESSES

Philemasi.
Ben Gungitt.

INVENTOR

Geo. A. Taylor,
by Anderson Smith
his Attorneys

UNITED STATES PATENT OFFICE.

GEORGE A. TAYLOR, OF NEW HAMPTON, IOWA.

STOVE.

SPECIFICATION forming part of Letters Patent No. 335,974, dated February 9, 1886.

Application filed June 27, 1885. Serial No. 169,994. (No model.)

To all whom it may concern:

Be it known that I, GEORGE A. TAYLOR, a citizen of the United States, residing at New Hampton, in the county of Chickasaw and State of Iowa, have invented certain new and useful Improvements in Stoves; and I do declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the art to which it appertains to make and use the same, reference being had to the accompanying drawings, and to letters or figures of reference marked thereon, which form a part of this specification.

Figure 1 of the drawings is a representation of a vertical sectional view. Fig. 2 is a horizontal section on line *x x*, Fig. 1. Fig. 3 is a detail view.

My invention relates to heating-stoves; and it consists in the construction and novel combination of parts, as will be hereinafter fully described, and particularly pointed out in the claim.

Referring by letter to the accompanying drawings, A designates the base of the stove, which is of cast-iron, and comprises the base-plate B, the inclosing sides B', and the top plate B², said top plate being provided with a central opening, B³, for the grate B⁴, said opening B³ communicating with the ash-pan receptacle B⁵. The grate B⁴ is dished inwardly and downwardly, and is provided with a central dumping plate or section, D, which is rigidly secured to a dumping-rod, E, which also serves as a shaking-rod for the grate.

G designates the fire-pot, which is provided with an outwardly-flaring flanged rim, G', the rear portion of which is provided with a grated or barred portion, G², which permits a down-draft to the exit-flue H.

A cold-air flue, I, leads from the bottom of the stove up through a hot-air chamber, I', in rear of the fire-pot, up to and connects with a hot-air chamber, J, which is provided with a deflecting-plate, J', supported therein by arms J², connected to the sides of the chamber J. From this chamber J three hot-air flues, K K' K², lead out through the top of the stove into the room and conduct the heated air into the room.

The smoke-flue L connects with the base-chamber or ash-pan receptacle and leads up outside of the stove-casing, and is connected by a short pipe or flue, M, with the stove-casing near its upper end. That portion of the stove-casing which surrounds the fire-pot is constructed of lattice-work N, so that the heat from the fire-pot may be radiated directly into the room through said lattice-work.

A cast-iron transverse plate, B², surmounts the base-section of the stove and supports the upper portion of the stove. The draft is up through the fire-pot from below, down through the top grating to the ash-pan receptacle, and out through the smoke-flue.

By the central dumping-grate the exhausted coals may be dumped into the ash-pan without permitting the sound coal to escape, and the grate may be shaken to cause the descent of the ashes in the same manner as in grates of the ordinary construction.

The cold air enters at the bottom of the stove, becomes highly heated before passing to the heater, near the top of the stove, and in this condition is discharged into the room through the hot-air pipes near the top of the stove-casing.

The front of the ash-pan section is provided with the usual sliding damper for regulating the draft.

Having thus fully described my invention, what I claim as new, and desire to secure by Letters Patent of the United States, is—

The combination, with a stove, of the chamber J, arranged therein above the fire-box, and having a deflector, J', the cold-air pipe leading from beneath the stove through the fire-box to the chamber J, and the hot-air pipes leading from the top of the said chamber through the stove-body, substantially as specified.

In testimony whereof I affix my signature in presence of two witnesses.

GEORGE A. TAYLOR.

Witnesses:

W. J. DARROW,
C. A. HARRIS.