
W. F. MAURER.

SHOE.

No. 343,047.

Patented June 1, 1886.



United States Patent Office.

WILLIAM F. MAURER, OF HARMONY, INDIANA.

SHOE.

SPECIFICATION forming part of Letters Patent No. 343,047, dated June 1, 1886.

Application filed March 9, 1886. Serial No. 194,524. (No model.)

To all whom it may concern:
Be it known that I, WILLIAM F. MAURER, a citizen of the United States, and a resident of Harmony, in the county of Clay and State of 5 Indiana, have invented certain new and useful Improvements in Shoes; and I do hereby declare that the following is a full, clear, and exact description of the invention, which will enable others skilled in the art to which it ap-10 pertains to make and use the same, reference being had to the accompanying drawings, which form a part of this specification, and in which—

Figure 1 is a perspective view of my im-15 proved shoe. Fig. 2 is a longitudinal sectional view of the same, and Fig. 3 is a perspective view of the sole-leather portion of the shoe.

Similar letters of reference indicate corre-

20 sponding parts in all the figures.

My invention has relation to shoes adapted for rough usage; and it consists in the improved construction and combination of parts of a shoe or boot having a lower sole-leather 25 portion attached to the sole, to which portion again the upper is secured, as hereinafter more fully described and claimed.

In the accompanying drawings, the letter A indicates the sole, which may be of any de-30 sired thickness and provided with a heel, B, or made without a heel, and which may be either double or single, as occasion and the usage to which the shoe is to be subjected may require. The portion C of sole-leather is se-35 cured between the sole and the inner sole, D, at its lower edges in the same manner as the vamp is secured in a common shoe or boot, and this portion, which is shaped into its desired shape while the sole-leather is wet, ex-40 tends around the entire lower portion of the shoe or boot, and is formed with a seam, E, at one side, the entire portion being made in one piece. The portion F may be shaped as a gaiter, as shown, and is stitched at its lower 45 edge to the inner side of the upper edge of the sole-leather vamp.

It will thus be seen that the entire lower portion of the shoe will be made of sole-leather, and consequently be capable of withstanding rough 50 usage, while the upper portion of the shoe or boot may be made of leather of any degree of softness, so that the shoe will be comfortable for the foot and at the same time hard and strong.

When the upper is made in the shape of a 55 gaiter, the entire upper is made out of one piece of leather, which is connected by means of a seam, G, at one side, preferably at the side opposite to the side at which the seam of the sole-leather vamp is, and it will be seen that 60 neither in the vamp nor in the upper will be found a seam at the back of the shoe, which, in a shoe of the stiffness which the sole-leather vamp causes would be uncomfortable, and would hurt the heel and back part of the foot 65 of the wearer.

This shoe or boot will be useful for miners, persons walking upon rough or stony surfaces, and for persons working with strong acids or alkalies, the sole-leather forming the entire 70 lower portion of the boot being of a sufficient thickness and strength to prevent its being cut through by stones or ragged rocks, or to be penetrated by any acid or alkali which might be dropped upon the shoe, or which 75 otherwise might come in temporary contact with the shoe.

If desired, only the vamp proper may be made of the sole-leather, and the back portion may be made in the usual manner of leather 80 where the forward part of the shoe is subjected to the worst usage, and numerous minor changes may be made in the construction of the shoe or boot without departing from the spirit of my invention.

Having thus described my invention, I claim and desire to secure by Letters Patent of the

United States—

The combination of the soles of a shoe, a vamp made in one piece of sole-leather se- 90 cured between said soles, and having its ends joined in a seam at one side of the shoe, and an upper made in one piece having a slit in the instep, and having its ends joined in a seam at the opposite side of the shoe to that 95 upon which is the seam in the vamp, the said upper being secured by its lower edge to the upper edge of the vamp.

In testimony that I claim the foregoing as my own I have hereunto affixed my signature 100

in presence of two witnesses.

WILLIAM F. MAURER.

Witnesses:

SUTTON STRONG, FRANKLIN D. STEWART.