
(No Model.)

J. T. GRAMER.

SCRUBBING BRUSH HOLDER.

No. 345,893.

Patented July 20, 1886.



United States Patent Office.

JOHN T. GRAMER, OF BOWMANSVILLE, PENNSYLVANIA.

SCRUBBING-BRUSH HOLDER.

SPECIFICATION forming part of Letters Patent No. 345,893, dated July 20, 1886.

Application filed March 17, 1886. Serial No. 195,533. (No model.)

To all whom it may concern:

Be it known that I, John T. Gramer, of Bowmansville, in the county of Lancaster and State of Pennsylvania, have invented a new and useful Improvement in Scrubbing-Brush Holders, of which the following is a specification, reference being had to the annexed drawings, forming a part thereof, in which—

Figure 1 is a plan view. Fig. 2 is a trans10 verse section taken on line xx in Fig. 1. Fig. 3 is an inverted plan view of the brush-clamp. Fig. 4 is a transverse section taken on line yy in Fig. 3.

Similar letters of reference indicate corresponding parts in the different figures of the drawings.

The object of my invention is to provide a holder for scrubbing-brushes, in which the brushes may be readily clamped in position for use, and from which they may be easily removed.

My invention consists in a yoke having downwardly-projecting arms provided with spurs extending inward toward the center of the yoke and adapted to engage the edges of the scrubbing-brushes, and a cam journaled in the yoke and adapted to press the scrubbing-brushes in opposite directions against the spurs of the yoke, as hereinafter more fully described.

The yoke A is formed of a central cross-bar, a, and two parallel side bars, b, cast integrally with the cross-bar a, and provided with downwardly-projecting arms c, on the inner faces of which spurs d project toward the center of the yoke. Upon the back of the yoke are formed two ears, e, for receiving a bail, D, the bail being provided with a tang, which is inserted in the handle B, by which the brush-40 holder is held.

In the center of the cross-bar a is journaled a short shaft, f, carrying on its lower end a cam, g, and upon its upper end, above the cross-bar, a ratchet-wheel, h, which is engaged by a pawl, i, pivoted to the back of the cross-

bar a. The ratchet-wheel h is provided with a cross-bar, j, by which it is turned, and the shaft f is held in place in the cross-bar a by a pin, k, which is received in a recess in the under side of the cross-bar a.

The cam g is oblong in form, and it is provided with beveled edges, which are adapted to bite into the edges of the scrubbing brushes C, which are placed between the arms c and the cam g.

When the brushes are placed in the position indicated, and the shaft f is turned, the cam g is brought into engagement with the edges of the brushes C, pushing them laterally against the spurs d, and at the same time 60 forming indentations for itself in the edges of the brushes, which gives the cam a secure hold on the brushes. When the cam is brought in this manner into engagement with the edges of the brushes, the pawl i is received in one of 65 the notches of the ratchet-wheel h, thus holding the cam in the position in which it is placed. By shifting the handle B or turning it on its bail the holder may be reversed.

Having thus described my invention, what 75 I claim as new, and desire to secure by Letters Patent, is—

1. A scrubbing brush holder formed of the yoke A, having the cross-bar a and longitudinal bars b, terminating in arms c, provided with spurs d, and the central cam, substantially as described, for clamping the scrubbing-brushes between the arms c.

2. The combination of the yoke A, provided with side bars, b, arms c, and inwardly-pro-80 jecting spurs d, the shaft f, carrying the cam g and ratchet-wheel h, and the pawl i, pivoted to the cross-bar of the yoke and arranged to engage the ratchet-wheel h, substantially as herein shown and described.

JOHN T. GRAMER.

Witnesses:

ELIAS ZIEGLER, F. S. STOVER.