
H. P. KOCHSMEIER & G. M. WALDORF.

SPRING HINGE.

No. 345,905.

Patented July 20, 1886.



United States Patent Office.

HENRY P. KOCHSMEIER AND GEORGE M. WALDORF, OF FREEPORT, ILL.

SPRING-HINGE.

SPECIFICATION forming part of Letters Patent No. 345,905, dated July 20, 1886.

Application filed February 26, 1886. Serial No. 193,288. (Model.)

To all whom it may concern:

Be it known that we, Henry P. Kochsmeier and George M. Waldorf, both residents of Freeport, in the county of Stephenson and State of Illinois, have invented certain new and useful Improvements in Spring-Hinges; and we do hereby declare that the following is a full, clear, and exact description of the invention, which will enable others skilled in the art to which it appertains to make and use the same, reference being had to the accompanying drawings, which form a part of this specification, and in which—

Figure 1 is a perspective view of our improved spring-hinge. Fig. 2 is a vertical sectional view of the same. Fig. 3 is a perspective detail view of the sleeves removed from the hinge. Fig. 4 is a similar view of the sleeves, the spring, and the buttons separated; and Fig. 5 is a view of the sleeves, showing a slight modification in the means for securing

the spring and the buttons.

Similar letters of reference indicate corre-

sponding parts in all the figures.

Our invention has relation to that class of spring-hinges in which the two leaves of the hinge are formed with obliquely-projecting ears at the upper and lower ends of their inner edges, which ears are pivoted together, and in 30 which springs arranged axial to the pintles of the hinge are secured to the inner edges of the leaves, drawing them together; and it consists in the improved construction and combination of parts of such a hinge in which the spring is se-35 cured at its ends to two sleeves which surround the spring, and which turn upon each other, each sleeve having a hook projecting from it, which engages an ear upon the inner edge of a leaf, as hereinafter more fully described and 40 claimed.

In the accompanying drawings, the letters A A indicate the leaves of the hinge, which are provided at the ends of their inner edges with obliquely-projecting ears or lips B, which are pivoted together upon pintles C, concentric to each other. The middles of the inner edges of the leaves are provided with wide slightly outwardly bent perforated ears or bails D, while otherwise the leaves are conbails D, while otherwise the leaves of springhinges of this class. Two sleeves, E and F, inclose the spring G, one sleeve, E, having a

reduced inner portion, H, upon which the other sleeve turns, and the sleeves are provided at the inner meeting edges with out- 55 wardly-projecting wide hooks I, the ends of which project beyond the edge of the other sleeve, and which hooks engage the wide bails upon the inner edges of the leaves of the hinge. The outer edges of the sleeves are provided 60 with diametrically opposite notches J, and caps K, or buttons, fit with their inner reduced ends into the ends of the sleeves, having lips or projections L from the inner faces of their flanged outer portions, M, which fit 65 into the notches and prevent the caps from turning within the ends of the sleeves. The reduced inner portions of the caps are formed each with a perforation, N, which extends into a transverse recess, O, in the outer face of 70 the cap, and the inwardly-bent ends Q of the spring fit into these perforations and recesses, and are retained in the same, keeping the caps in their positions in the ends of the sleeves. It will thus be seen that the spring and the 75 caps will keep the sleeves together; and the caps fitting with their lips in the notches in the ends of the sleeves, the spring will be twisted when the sleeves are revolved upon each other, thus serving by its tension to draw 80 the sleeves back in their original position, forcing the wide hooks toward each other. As these hooks are hooked into the ears at the middles of the inner edges of the hinge-leaves, the said inner edges will be drawn together in 85 the same manner as in spring-hinges of a similar construction. After the leaves in opening have passed over the position in which they stand at right angles to each other, the spindle with the springs will be forced out from 90 a line with the pintles of the hinge-ears, and the tension of the spring drawing upon the bails or ears of the leaves will tend to draw the leaves to stand in a position parallel with each other, so that after the door has been 95 opened beyond a certain distance it will be drawn open by springs and held open by the springs.

If desired, the buttons or caps may be formed with a transverse groove forming notches in 100 the edges of the cap, into which groove the end of the spring may be placed; or the caps may be held together by means of an axial rivet, R, as shown in Fig. 5, while the ends of

the spring are secured in notches S in the outer edges of the sleeves. It will thus be seen that the sleeves will serve as a casing for the spring, preventing any dust or dirt from 5 entering into the spring and interfering with its operativeness, and at the same time the sleeves will serve as means for conveying the power of the twisted spring to the hingeleaves, as well as for holding the spring straight, to and the spring will hold all the parts of the spring mechanism of the hinge together, holding the caps together, which in their turn hold the sleeves together.

Having thus described our invention, we 15 claim and desire to secure by Letters Patent of

the United States—

1. In a spring-hinge, the combination of hinge-leaves having lugs upon their inner edges, two sleeves turning with their inner edges, two sleeves turning with their inner ends upon each other, and having hooks projecting from their sides andengaging with said lugs, with a spring inclosed within the sleeves and secured to the outer ends of the sleeves, as and for the purpose shown and set forth.

25 2. In a spring-hinge, the combination of hinge-leaves having lugs upon their inner edges, a sleeve having a reduced inner end and having an outwardly-projecting hook at the shoulder, formed by the reduction, a sleeve 30 turning with its inner end upon the reduced portion of the other sleeve, and having a hook projecting outwardly from its inner end, said hooks engaging with said lugs, and a spring inclosed within the sleeves and secured to their outer ends with its ends, as and for the purpose shown and set forth.

3. In a spring-hinge, the combination of hinge-leaves having lugs upon their inner

edges, two sleeves turning with their inner ends upon each other, and having hooks pro-40 jecting from their sides and engaging with said lugs, removable and adjustable caps secured to the outer ends of said sleeves, and a spring inclosed by said sleeves, and having its ends secured to said caps, substantially as and 45 for the purpose set forth.

4. The combination of hinge-leaves having lugs upon their inner edges, two sleeves turning with their inner ends upon each other, and having hooks projecting from their sides and 50 engaging with said lugs, and having notches in their outer ends, caps formed with recesses and perforations, fitting into the outer ends of the sleeves, and having lips to engage with said notches, and a spring inclosed within the 55 sleeves and having its ends inserted into the

perforations in said caps.

5. In a spring-hinge, the combination of two hinge-leaves having oblique ears at the ends of their inner edges pivoted together, and 6 formed with wide perforated lugs or bails upon the middles of the inner edges, sleeves turning upon each other with their inner ends, and having wide hooks at their inner ends engaging said perforated lugs or bails, and a 6 spring inclosed by the sleeves and having the ends thereof attached to said sleeves, as and for the purpose shown and set forth.

In testimony that we claim the foregoing as our own we have hereunto affixed our signa- 70

tures in presence of two witnesses.

HENRY P. KOCHSMEIER. GEORGE M. WALDORF.

Witnesses:

GEORGE SHOVER, CALVIN KISTNER.