




(No Model.)

W. O. FREYTAG.

FOOT WIPER OR BOOT AND SHOE CLEANER.

No. 350,879.

Patented Oct. 12, 1886.



WITNESSES:
A. P. Grant
W. F. Fischer

INVENTOR:
W. O. Freytag
John A. Dederheim
ATTORNEY.

UNITED STATES PATENT OFFICE.

WILLIAM O. FREYTAG, OF PHILADELPHIA, PENNSYLVANIA.

FOOT-WIPER OR BOOT AND SHOE CLEANER.

SPECIFICATION forming part of Letters Patent No. 350,879, dated October 12, 1886.

Application filed January 7, 1886. Serial No. 187,832. (No model.)

To all whom it may concern:

Be it known that I, WILLIAM O. FREYTAG, a citizen of the United States, residing in the city and county of Philadelphia, State of Pennsylvania, have invented a new and useful Improvement in Boot and Shoe Cleaners, which improvement is fully set forth in the following specification and accompanying drawings, in which—

Figure 1 represents a top or plan view, partly in section, of a cleaner embodying my invention. Fig. 2 represents a longitudinal section thereof. Fig. 3 represents an end view thereof.

Similar letters of reference indicate corresponding parts in the several figures.

My invention relates to devices for cleaning boots and shoes by means of brushes and scrapers; and it consists of the novel features hereinafter described, whereby I obtain a structure adapted to simultaneously clean the top, bottom, and opposite sides of a boot or shoe, to collect and afford convenient removal of collecting dirt, and to permit effective clearance of the cleaning devices.

Referring to the drawings, A designates two side pieces or walls of the frame of the cleaner, between which are located the cleaning devices, consisting of a transverse top brush, B, a series of transverse bottom brushes, C, alternating with scrapers D, and of longitudinal side brushes, E, the several brushes being in proper relation to each other to act on the top, the sole, and opposite sides of the boot or shoe that may be presented thereto. The top brush, B, is arched in longitudinal direction to correspond with the general contour of the top of a boot or shoe, the bottom and side brushes being substantially flat, and the back of said top brush is fastened to the side pieces, A, so that it is not only held in position thereby, but in turn serves to unite the side pieces. The position of the top brush, B, is at or near one end of the side brushes, E, and of the series of bottom brushes, C, and consequently the greater portion of the side and bottom brushes is left exposed, to be used independently of the top brush, as when the top of the boot or shoe does not require cleaning. Spaces are left between the bottom brushes, C, as shown, to receive the scrapers D, and to permit the dirt removed from the boot or shoe, especially by

said brushes or the scrapers, to escape downward into an accumulating box or drawer, F, which is located beneath the brushes on cleats G of the side pieces, and adapted to slide in and out thereon, and which is provided with a recess, H, for the engagement of a spring-catch, J, on the side pieces, thus holding the drawer in closed position. The area of the drawer F is such that it underlies the entire series of bottom brushes, C, which insures the reception therein of all the dirt falling through the spaces between the brushes, and it will be seen that by means of the drawer the accumulating dirt can be removed with great facility. The backs of the bottom brushes, C, together with the scrapers D, are fastened to bars or sills K, which are fitted in guideways on the inner surfaces of the side pieces, A, to slide inward and outward, a catch, L, being connected with the side pieces and engaging with the sills for retaining the same in position; and it will be seen that when the sills are slid outward from the side pieces the bottom brushes and scrapers may be readily cleaned of dirt, while the top and side brushes are rendered convenient of access for cleaning purposes. The side brushes, E, are preferably formed by inserting tufts of proper material into the side pieces, A, so that the latter constitute the backs of said brushes.

Having thus described my invention, what I claim as new, and desire to secure by Letters Patent, is—

1. A boot and shoe cleaner comprising a top brush, side brushes, and a series of bottom brushes, with intermediate scrapers, having open spaces or passages between said scrapers and brushes, all substantially as and for the purpose set forth.

2. A boot and shoe cleaner consisting of an arched top brush, B, secured to the side pieces, A, the side brushes, E, the series of bottom brushes, C, and scrapers D, secured at their ends to the sill K, and having open spaces between the said brushes and scrapers, the drawer F below said brushes, scrapers, and open spaces, all combined and arranged substantially as described.

W. O. FREYTAG.

Witnesses:

JOHN A. WIEDERSHEIM,
A. P. GRANT.