

(No Model.)


2 Sheets—Sheet 1.

J. ALLEN.

COMBINED BAG AND TWINE HOLDER.

No. 353,435.

Patented Nov. 30, 1886.



WITNESSES

Jas. E. Hutchinson.
S. J. Nottingham

INVENTOR

Joseph Allen
By *H. A. Seymour*
Attorney

(No Model.)

2 Sheets—Sheet 2.

J. ALLEN.

COMBINED BAG AND TWINE HOLDER.

No. 353,435.

Patented Nov. 30, 1886.




Fig. 2.



Fig. 7.




Fig. 5.




Fig. 6.




Fig. 8.

WITNESSES
Jas. E. Hutchinson.
S. G. Nottingham

Joseph Allen INVENTOR
By H. A. Seymour
By Attorney

UNITED STATES PATENT OFFICE.

JOSEPH ALLEN, OF PALMYRA, NEW YORK.

COMBINED BAG AND TWINE HOLDER.

SPECIFICATION forming part of Letters Patent No. 353,435, dated November 30, 1886.

Application filed August 31, 1885. Serial No. 175,828. (No model.)

To all whom it may concern:

Be it known that I, JOSEPH ALLEN, of Palmyra, in the county of Wayne and State of New York, have invented certain new and useful
5 Improvements in a Combined Bag and Twine Holder; and I do hereby declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the art to which it appertains to make and
10 use the same.

My invention relates to an improvement in combined bag and twine holder, the object of the same being to provide a neat and stiff device adapted to be suspended above the counter, that shall combine simplicity and economy in construction with durability and efficiency in use. A further object is to provide a device of this character that can be easily
15 taken apart for packing and put together by an unskilled person without the aid of any tools; and with these ends in view my invention consists in the parts and combinations of of parts as will be more fully described, and pointed out in the claims.

25 In the accompanying drawings, Figure 1 is a view in perspective of the complete device. Fig. 2 is a view in longitudinal section of the same. Fig. 3 is a view of one of the bag-supporting arms. Fig. 4 is a detached view of
30 the plates between which the bag-supporting arms are clamped. Fig. 5 is a view of one of the braces and the plate to which the braces are attached. Fig. 6 is a view of the brush or other holder. Fig. 7 is a view of the bag-holder, and Fig. 8 is a view of one of the pins
35 with the handle attached.

A represents a stiff rod or hanger, consisting, essentially, of the sections a , a' , and a^2 . The section a is screw-threaded at its opposite
40 ends, and is attached at its lower end to the screw-threaded boss b of the plate B. This plate B rests on the plate B', which former can be angular, as shown in the drawings, or of any other shape, and is provided on its
45 lower face with a series of V-shaped grooves, b' , arranged substantially as shown in Fig. 4, which register with corresponding grooves formed on the upper face of the plate B'. This plate B' corresponds in size and shape to
50 the plate B, and is provided centrally with an opening, which registers with a similarly-shaped opening in the plate B and with the

screw-threaded opening in the boss b of the plate B. The plates B and B' are secured together by the bolt B³, which latter passes
55 through the plates B and B', and into the screw-threaded boss b of the plate B.

Between the plates B and B' are clamped the bag-supporting arms C. These supports radiate from the plates B and B', and are made
60 of wire strips bent centrally to resemble the letter V. The two arms or members of the bent strip are bent around to form the rings c , and the free ends of said arms, which are of spring-metal wire, are then bent downwardly
65 at right angles to the main body of the wire, and then upwardly, forming V-shaped clasps or hooks. The extreme ends of the clasps or hooks thus formed rest in close contact with
70 rings c , which latter form guards and prevent the bag-holding pins which are supported by the clasps or hooks from being displaced. A series of these bent supporting arms are
75 clamped at the central portion between the plates B B', and are prevented from displacement by the grooves b' , formed on the adjacent faces of said plates.

The bag-holding pins D are adapted to reach from one end of the bent supporting-arm to the other end, or from one end of one sup-
80 porting-arm to the adjacent end of the next arm, and each is provided at one end with a loop adapted to be slipped over the upper end of one clasp or hook, while the opposite end of the pin is provided with a pointed end
85 triangular in cross-section, and is adapted to rest on an adjacent hook. These pins are removable, and hence when it is desired to fill the same with bags it is simply necessary to remove the pins and apply a handle, J, or a
90 handle of any construction to the pins, which converts the same into a gimlet and permits it to penetrate a great number of bags without exertion and without injuring the hands.

The arms C are provided with the rings c' ,
95 formed integral therewith, into which are secured the braces E', which prevent the arms from lateral displacement, and the braces E, which prevent the arms from bending downward. The braces E are formed in pairs, as
100 shown, and each consists of a strip of wire having two rings, d , formed at or near its central portion, the two arms of each brace being bent downwardly and connected at their free

ends to the rings c' of arm C, as before described. The rings d , formed on the braces E, are slipped over the lugs d' , formed on the upper surfaces of the plate F, the latter being
 5 secured to the screw-threaded upper end of the section a of the stem. After the parts are thus secured together, by turning the stem-section a , which is provided on one end with right-hand screw-threads and on the other
 10 end with left-hand screw-threads, the plates F and B are moved farther apart and the braces E tightened.

The plate F is provided on its upper face with a boss, f , having a screw-thread opening
 15 therein, into which is screwed the lower end of the stem-section a' . To the upper screw-threaded end of this section a' is screwed the plate G, having a series of openings, g , therein, through which are passed the holders g' . These
 20 holders are preferably U-shaped with outwardly or hook-shaped ends, and are removably secured in position by passing the hook-shaped ends through the holes in the plate from the upper side thereof; but it is evident
 25 that instead of making the holders double—or, that is, providing each holder with two hooks—they can be made single, as shown in Fig. 6, and answer all necessary purposes. These holders are adapted to hold brushes and
 30 other small articles of trade. The plate G is also provided with a screw-threaded boss, into which is screwed the lower end of the stem-section a^2 . The upper end of this section is provided with a hook, by which the device is
 35 suspended.

To the lower face of plate B', near opposite sides thereof, are secured rings or loops h for the attachment of the twine-holder I, which latter consists of a wire frame having loops i
 40 for its attachment to the plate B', loops i' for the pin i^2 , which latter passes through the ball of twine, and the loop i^3 , through which the twine passes.

It is evident that numerous slight changes
 45 in the construction and relative arrangement of the several parts might be resorted to without departing from the spirit of my invention, and hence I would have it understood that I do not confine myself to the exact construction shown and described, but consider myself
 50 at liberty to make such changes and alterations as fairly fall within the spirit and scope of my invention.

Having fully described my invention, what I
 55 claim as new, and desire to secure by Letters Patent, is—

1. In a combined bag and twine holder, the combination, with a rigid stem and plates attached thereto, of a series of arms clamped between the plates and provided at their outer
 60 ends with spring-hooks and pins removably attached to said spring-hooks.

2. In a combined bag and twine holder, the combination, with a stem and plates attached
 65 thereto, of a series of arms clamped between the plates, pins secured to the outer end of

said arms, and a twine-holder suspended below the plates.

3. The combination, with a stem and plates rigidly secured thereto, the latter being pro-
 70 vided with grooves, as described, of the arms clamped between the plates and pins secured to the arms.

4. The pins, each having a ring at one end and triangular point at the other end, and a
 75 removable handle adapted to engage the ring, substantially as set forth.

5. The combination, with a stem, supporting-arms rigidly secured thereto, and pins secured to the outer ends of the supporting-
 80 arms, of a plate secured to the stem above the supporting-arms, and braces connecting said plate and supporting-arms, substantially as set forth.

6. In a combined bag and twine holder, the
 85 combination, with the stem, arms, and pins, of the plate located above the arms, the braces, substantially as described, connecting the plate and arms, and a twine-holder.

7. The combination, with the sectional stem,
 90 the plates B and B', the arms secured between said plates, and the pins, of the plate located above the arms, braces connecting said latter plate and the arms, and the lateral braces, all of the above parts combined substantially as
 95 set forth.

8. The combination, with a rigid stem, plates secured thereto, and bag-supporting arms secured between the plates, of the plates G, secured to the stem, a series of hooks removably
 100 secured to said plate G, and a twine-holder located below the bag-supporting arms.

9. The combination, with the sectional stem and the plates F and G, connecting the sections of said stem, of bag-supporting arms secured to the lower end of the stem, braces connecting the plate F and bag-supporting arms,
 105 and hooks secured to the plate G, substantially as set forth.

10. In a combined bag and twine holder, the
 110 combination, with the sectional stem having a hook-shaped upper end, of bag-supporting arms rigidly secured to the lower end of the stem, and a twine-holder located below the bag-supporting arms, substantially as set forth.
 115

11. In a combined bag and twine holder, the combination, with a stem, plates secured to the stem, and bag-supporting arms clamped between said plates, of a twine-holder hinged to the lower face of one of said plates.
 120

12. In a combined bag and twine holder, the combination, with a stem, plates secured thereto, and arms clamped between said plates, of the wire twine-holding frame hinged to the lower face of one of said plates, substantially
 125 as set forth.

In testimony whereof I have signed this specification in the presence of two subscribing witnesses.

Witnesses: JOSEPH ALLEN.
 S. G. NOTTINGHAM,
 J. E. JONES.