
(No Model.)


S. R. MOORE.

EXTENSION TABLE.

No. 353,574.

Patented Nov. 30, 1886.





Witnesses Howler Deruhard

Inventor S.R. Moore By his attorneys. Chambles

United States Patent Office.

SANFORD R. MOORE, OF EGAN, DAKOTA TERRITORY.

EXTENSION-TABLE.

SPECIFICATION forming part of Letters Patent No. 353,574, dated November 30, 1886.

Application filed March 5, 1886. Serial No. 194,162. (No model.)

To all whom it may concern:

Be it known that I, SANFORD R. MOORE, a citizen of the United States, residing at Egan, in the county of Moody and Territory of Da-5 kota, have invented a new and useful Improvement in Extension-Tables, of which the following is a specification, reference being had to the accompanying drawings.

My invention relates to improvements in ex-10 tension-tables; and it consists of the peculiar and novel construction and combination of parts, substantially as hereinafter fully set forth, and particularly pointed out in the claim.

The primary object of my invention is to 15 provide an improved extension-table which when folded occupies a very small space, to provide hinged sections of the side rails that lie flat against one another when folded, and to provide stop-blocks for the hinged sections 20 to abut against and to relieve the strain on the hinges, and fastening devices for securing the end sections of the table together.

The table is very simple and strong in its construction and thoroughly effective in oper-

25 ation and easy of adjustment.

In the accompanying drawings, Figure 1 is a side elevation showing the table extended and having the removable leaves therein. Fig. 2 is a bottom plan view of the table with the 30 leaves removed and the end sections and side rails folded together.

Referring to the drawings, in which like letters of reference indicate corresponding parts in both the figures, A B designate the end sec-35 tions of the table, each of which comprises the legs a, having the cross-bar a', connecting the legs, a rigid top section, b, and a section, b', of the side rails, C. The legs are arranged in pairs, and the top-section b has a foldable 40 leaf, b^2 , hinged thereto and held in its extended position by means of a pivoted block, b^3 , or other suitable fastening device. The sections b' of the side rails, C, are provided with dowelpins and sockets c c', and with blocks C', rig-45 idly secured on the inner faces thereof at a distance from the free edge.

D designates the sections of the side rails, which are of equal number and size at or near each side edge of the table top, and these sec-50 tions of each side rail are hinged together on opposite side faces of their ends, as at d', so

that they can fold flat against one another, as shown in Fig. 2, the end section of each rail being hinged to the blocks C', so that when the table is folded together the edges of the 55 sections b' will abut together, whereby the dowel-pins therein will enter the sockets to connect the end sections A B of the table together.

E designates stop-blocks, which are rigidly 60 secured to the under surface of the top-section b, near their opposing edges, and when the table is folded together the sections D thereof fold together within the edges of the table-top and abut against said blocks to relieve the 65 strain on the hinges and hold the sections D

securely and rigidly in place.

F designates the removable top-sections, which are adapted to rest on and be supported by the sections D of the side rails when the 70 latter are unfolded, and each leaf or top-section F is provided on opposite edges with dowel-pins and sockets therefor to fit into and receive dowel-pins and sockets on the adjacent leaves of the table top, as will be very readily 75 understood.

G designates a hook, which is pivoted at one end to one of the top-sections b, and confined or held in place by stop-pins g, located on each side of the shank thereof, and the free end of 80 the hook engages a staple or pin, G', on the other section b of the opposite end section Aor B of the table. The side-rail sections b' of the end section A of the table have pivoted hooks I on their inner faces between the latter 85 and the end sections D of the foldable side rails, and the similar sections, b', of the end section B of the table have pins I' secured on their inner faces, whereby the end sections A B of the table are securely locked and held 90 together when the leaves F are removed and the hinged side-rail sections D are folded together.

The operation of my invention will be readily understood from the foregoing description, 95 taken in connection with the accompanying drawings.

I do not desire to limit myself to the particular form of fastening device comprising the pivoted hooks and eyes; nor to the pre- 100 cise details of construction and form and proportions herein shown as an embodiment of

353,574

my invention, as I am aware that changes therein can be made.

I am aware that it is not broadly new to provide an extension-table with foldable side 5 rails which comprise a series of hinged sections that are adapted to fold together; but in my improved table I provide the end sections A B with stop-blocks E, which are arranged near the free edges of the top-section b and 10 with suitable fastening devices. When the table is folded to its most compact form, the hinged blocks or sections D of the side rails thereof lie or abut together within the edges of the top, and the end blocks D bear against 15 the stop-blocks E, which serve to hold and brace the blocks D in their folded position and relieve the strain on the hinges thereof, the table-sections A B being secured or connected together by the fastenings I I' G G', as 20 heretofore described, and more clearly shown in Fig. 2 of the drawings.

Having thus fully described my invention,

what I claim as new, and desire to secure by Letters Patent, is—

In an extension-table, the combination of 25 the end sections A B, carrying the side blocks, b', and the shorter blocks, C', arranged in rear of the blocks b', the blocks D, hinged together and to the blocks C', and forming the side rails of the table when the latter is extended, 30 the blocks E, secured and arranged at an angle to the end sections A B, and having the blocks D bearing against the same when the table is folded, and the fastening devices carried by the end sections A B, and the side 35 blocks, b', thereof, for securing the end sections together when folded, as set forth.

In testimony that I claim the foregoing as my own I have hereto affixed my signature in presence of two witnesses.

SANFORD R. MOORE.

Witnesses:

GEO. M. DE GROFF, K. W. SHELDEN.