




(No Model.)

F. TAYLOR.
BRACKET FOR SINKS.

No. 353,991.

Patented Dec. 7, 1886.



Witnesses:
Harry Avery
John E. Parker

Inventor:
Fitch Taylor
by his Attorneys
Howson & Sons

UNITED STATES PATENT OFFICE.

FITCH TAYLOR, OF PHILADELPHIA, PENNSYLVANIA, ASSIGNOR TO HIMSELF,
THOMAS R. BROWN, AND R. PITT OWEN, ALL OF SAME PLACE.

BRACKET FOR SINKS.

SPECIFICATION forming part of Letters Patent No. 353,991, dated December 7, 1886.

Application filed April 19, 1886. Serial No. 199,336. (No model.)

To all whom it may concern:

Be it known that I, FITCH TAYLOR, a citizen of the United States, residing in Philadelphia, Pennsylvania, have invented certain
5 Improvements in Brackets for Sinks, of which the following is a specification.

The object of my invention is to provide a simple, cheap, and efficient means of securing the end flanges at the top of a sink to the top
10 bars of the supporting-brackets, and this object I attain in the manner which I will now proceed to describe, reference being had to the accompanying drawings, in which—

Figure 1 is a side view showing my improved device for confining the flange of the sink to the bracket; Fig. 2, a transverse section showing the sink and both of the brackets; Fig. 3, a perspective view, on a larger
15 scale, of the confining device detached from the bracket and sink; and Figs. 4 and 5, views showing a modified form of bracket and confining device.

A represents an ordinary kitchen-sink having top flanges, *a a*, at each end; and B B are the opposite supporting-brackets, on the top
25 bars, *b*, of which the end flanges, *a a*, of the sink rest, as shown in Fig. 2. In order to confine the flanges vertically to said top bars of the supporting-bracket I use clamps D,
30 which embrace the lower edges of the bars *b*

of the brackets, and are secured to the flanges *a* of the sink by means of screws or bolts *d*. These confining-clamps thus provide a simple and efficient means of confining the sink to the brackets and simplify and cheapen the
35 construction of said brackets, inasmuch as they render unnecessary the formation of a double or slotted top bar on the bracket, as in devices of this class formerly manufactured.

The clamp D may have at the top a flange
40 projecting outwardly, as shown in Fig. 3, or the flange may project inwardly, as shown in Figs. 4 and 5, the top bar of the bracket in this case being recessed, as shown, for the reception of said flange.
45

I claim as my invention—

The combination of the sink having end flanges and the opposite supporting-brackets, with clamps D, bolted to said end flanges of the sink and embracing the top bars of the
50 supporting-brackets, all substantially as specified.

In testimony whereof I have signed my name to this specification in the presence of two subscribing witnesses.

FITCH TAYLOR.

Witnesses:

J. R. MASSEY,
WM. V. MASSEY.