




(No Model.)

L. MOORE.
FENCE.

No. 356,006.

Patented Jan. 11, 1887.



WITNESSES

Jos. A. Ryan
W. H. Patterson

INVENTOR

Lewis Moore
Per A. H. Evans & Co.

Attorneys

UNITED STATES PATENT OFFICE.

LEWIS MOORE, OF BETHALTO, ILLINOIS.

FENCE.

SPECIFICATION forming part of Letters Patent No. 356,006, dated January 11, 1887.

Application filed October 14, 1886. Serial No. 216,222. (No model.)

To all whom it may concern:

Be it known that I, LEWIS MOORE, a citizen of the United States, residing at Bethalto, in the county of Madison and State of Illinois, have invented a new and useful Improvement in Portable Fences, of which the following is a clear, full, and exact description, reference being had to the accompanying drawings, making a part of this specification, in which—
10 Figure 1 is a perspective view of a panel of fencing with my improvement attached. Fig. 2 is an end view of the same. Fig. 3 is a section through *x x* of Fig. 1.

My invention relates to portable fences; and it consists in the combination and arrangement of devices hereinafter explained and claimed.

To enable others skilled in the art to make and use my invention, I will proceed to describe the exact manner in which I have carried it out.

In the drawings, A represents the post supporting the panels B. This post consists of two inclined braces, *a*, clamping at their upper points a short block, *a'*, perforated, as shown in Fig. 3, to permit the passage of the chain *b*, by which the panel is locked to the upper part of the post. The lower parts of the braces *a* are secured together by the cross-plates C, between which, and near their longitudinal center, is pivoted the standard D, through the upper end of which is a perforation to permit the passage of the chain *b'*, which

locks the lower portion of the panel to the pivoted standard. By means of this pivoted standard, and when the chain *b* is removed, it is evident the panels will be allowed to assume a vertical position regardless of any incline or irregularity of the ground over which the fence is run. After the panels have been adjusted with relation to the ground the chains *b* are inserted and properly secured.

The short chains *b b'* are quickly secured in position by pins *c* passed through the links, or by other well-known means; after the parts have been properly drawn together; and by simply knocking out these pins the fence is ready for removing.

Having thus described my invention, what I claim as new, and desire to secure by Letters Patent, is—

1. In a portable fence, the post A, formed of the inclined braces *a*, and the perforated short block *a'*, in combination with the lower cross-plates, C, and the pivoted and perforated standard D, all constructed to operate substantially as and for the purpose set forth.

2. The post A, formed of the inclined braces *a* and the perforated short block *a'*, in combination with the panels B, chains *b b'*, and pins *c*, all constructed and arranged substantially as and for the purpose set forth.

LEWIS MOORE.

Witnesses:

LUCAS PFUFFENBERGER,
L. H. SENBERT.