

(No Model.)

2 Sheets—Sheet 1.

G. WESTINGHOUSE, Jr.

FLUID PRESSURE MOTOR.

No. 359,303.

Patented Mar. 15, 1887.




Fig. 1.


WITNESSES
C. M. Clarke
R. H. Whittlesey

INVENTOR
Geo. Westinghouse Jr.
by J. Thomson Bell atty.

2 Sheets—Sheet 2.

FLUID PRESSURE MOTOR.

Patented Mar. 15, 1887.



WITNESSES

L.M. Clarke
R.H. Whittsey

INVENTOR

Geo. Westinghouse Jr
By J. Snowden Bell
att'y.

UNITED STATES PATENT OFFICE.

GEORGE WESTINGHOUSE, JR., OF PITTSBURG, PENNSYLVANIA.

FLUID-PRESSURE MOTOR.

SPECIFICATION forming part of Letters Patent No. 359,303, dated March 15, 1887.

Application filed August 30, 1886. Serial No. 212,177. (No model.)

To all whom it may concern:

Be it known that I, GEORGE WESTINGHOUSE, Jr., residing at Pittsburg, in the county of Allegheny and State of Pennsylvania, a citizen of the United States, have invented or discovered a certain new and useful Improvement in Fluid-Pressure Motors, of which improvement the following is a specification.

In the accompanying drawings, which make part of this specification, Figure 1, Sheet 1, is a vertical sectional view of my improved fluid-pressure motor, showing the valve mechanism shifted to admit fluid-pressure to one side of the piston, also showing the valve mechanism by which impulse or movement is imparted from a distant station to operate the motor-valves, the pipe connecting the two being broken away, except at its ends. Fig. 2, Sheet 2, is a vertical sectional view, to an enlarged scale, of the operator's or distant station valve mechanism; and Fig. 3 is a view in sectional elevation of the upper portion of a pair of such valves connected as in use for operating the motor in opposite directions, the plane of section in this figure being at right angles to that shown in Fig. 2.

My present invention relates to certain improvements in the valve-actuating mechanism of fluid-pressure engines or motors.

In an application for patent filed by me August 30, 1886, Serial No. 212,180, I have described and claimed a fluid-pressure engine or motor having a power-piston, a distributing-valve, two small pistons inclosed within the valve-chamber, connected with and operating the distributing-valve, valve-governed escape-ports for moving the valve-controlling pistons by difference of fluid-pressure thereon, and electrically-controlled mechanism for opening the escape-valves at the pleasure of the operator.

My present invention consists of certain combinations of an engine or motor having pistons, valves, and ports, substantially as shown and described in said prior application, with mechanism for operating the escape-valves by force applied through a fluid, preferably a liquid column inclosed within pipe-connections, as hereinafter more fully described and claimed.

In the drawings, A represents a cylinder inclosing a packed piston, A'. A stem, A², ex-

tends from this piston through a suitable stuffing-box, A³, and may make connection, directly or indirectly, with the apparatus or mechanism to be actuated thereby.

Fluid-pressure is admitted to either side of the piston from valve-chamber C by passages *a a*, and is exhausted to the outer air by intermediate passage, *a'*. A slide-valve, *a*², moving on the seat *a*³, controls supply and exhaust of fluid-pressure. Movement is given to the valve by two pistons, *c c*, fixed upon a common tubular stem, *c'*, such stem having a one-sided enlargement at or near its center, with recess or socket *c*² therein to receive the upper part of the valves. The valve-governing pistons *c c* may either fit loosely within the cylindrical valve-chamber C; or by preference small channels or passages *c*³ are made along the chamber-wall in the path of the pistons, or through the body of the pistons, thereby providing for passage of fluid in small quantities from the inner to the outer sides of the pistons. Fluid, by preference air under pressure, is supplied to the valve-chamber between its inclosed pistons by any suitable pipe-connections leading from a reservoir, compressing apparatus, or other source of supply. If fluid be permitted to escape from either end of the valve-chamber outside one of the valve-pistons *c*, an excess of fluid-pressure will be exerted on the pistons in the direction of such escape, thereby moving them and the distributing-valve *a*² in that direction. When such escape is closed, the leakage or limited flow past the piston will soon restore equilibrium of pressure.

In order to make provision for such escape and to control opening and closing the same, ports *e'* are made in the chamber ends or heads, leading by passages *e*² to the exterior air. These ports are opened and closed by valves *e*, which abut or rest against stems *e*³, extending inward within the tubular passage *c*⁴ of stem *c'*. Springs *e*⁴ hold the valves to their seats with a definite degree of pressure, assisted somewhat by fluid-pressure upon the inner ends of stems *e*³, admitted within the stem *c'* through central port, *c*⁵.

In order to unseat the valves and permit escape, rods or stems *e*³ are extended from the valve outward through the ports *e'* and through an axial passage, *d*, into a piston-chamber, *d'*,

100

formed in the cases or shells D, which latter—
one at either end—screw into the ends of and,
in effect, form heads for the piston-chamber C.

Pistons I are fitted to move in the chambers
5 d' , such pistons having stems i , extending in-
ward to or nearly to the ends of valve-rods e^5 .
The pistons are packed to prevent leakage
past them, and yet afford freedom of move-
ment, by means of diaphragms I', bound at
10 their peripheries between the abutting shoul-
ders d^2 of the shells D and plugs D', which lat-
ter screw into and close the ends of the piston
or diaphragm chambers, except in the central
pipe-like passages, d^3 , leading to such cham-
15 bers through the plugs.

The pistons I are held against the dia-
phragms I' by springs i' , having some prede-
termined degree of tension or resistance to
20 compression—say twenty-five pounds, (more or
less.) If fluid, by preference liquid, filling the
passages d^3 and the space on the outer sides of
the diaphragms be subjected to a compressing
force greater than the resisting power of the
springs, the diaphragms I' will be bent or de-
25 flected inward, as represented on the left,
Fig. 1, thereby pressing the piston I and stem
 i inward against valve-rod e^5 , and forcing the
valve from its seat. Such unseating of the
valve permits escape of fluid-pressure through
30 port e' , and causes the pistons c and valve a^2
to move to the left, as shown, in position to
admit fluid-pressure to the right of the main
piston and open the passage on the left to the
exhaust.

35 In Fig. 1 the valve a^2 is shown shifted to the
left, as above described; but the piston is on
the right, not having yet moved in response to
fluid-pressure, which might enter through
right-hand port a . When fluid or liquid pres-
40 sure in passage d^3 is released or falls below the
power of spring i' , the latter forces the piston
outward, thereby permitting the compressed
spring e^4 , assisted by fluid-pressure on stem e^3 ,
to seat valve e and close the escape. This be-
45 ing done, the leakage or limited passage of
fluid-pressure past the piston c will soon re-
store equilibrium of fluid-pressure on the
valve-pistons.

Provision is also made in this motor for
50 making and breaking electric circuits, both by
movements of the valve-operating mechanism
and by the piston at the ends of its stroke.
This feature of construction is not claimed
herein, however, but is included in the sub-
55 ject-matter of a separate application filed by
me of even date herewith.

Make and break by the valve mechanism is
secured by connecting the metal parts of the
engine in circuit, and also binding-posts M M,
60 which latter are secured to but electrically in-
sulated from the plugs or shells D D by hard-
rubber or equivalent sleeves m' . The inner
ends, m , of these posts are in position to make
contact with the inner ends of piston-stems i ,
65 when the latter are moved inward to open the
escape-valves. Consequently the circuits con-
nected to the posts and the pistons will be

made and broken by making and breaking
contact between the parts m and i .

The piston make and break is secured by 70
means of a stem, b , carrying a button, b' , which
makes contact at the two ends of piston-stroke
with springs $b^2 b^3$, secured to posts $b^4 b^5$, which
latter are secured to but electrically insulated
from the shell B, cast on the head of the main 75
cylinder. Circuits connected to the posts b^4
 b^4 or $b^5 b^5$ will be made and broken by the move-
ment of the piston. The circuits thus made
dependent upon the movements of the engine
may be employed for various purposes, as de- 80
scribed in the separate application referred to,
and among others they may, if desired, be made
to actuate some signal by which it may be
known whether some desired movement of the
engine has been effected. 85

In apparatus of this class employed to op-
erate switches, signals, locks, and other parts
or appliances connected with a railway-track,
it is ordinarily required to control the opera-
tion of the same from some central or common 90
station more or less distant. To this end a
pipe or tube, H, is connected to each plug D'
by coupling h . These pipes are extended in
length from each end of the valve mechanism
of the motor to the cabin or stand of the oper- 95
ator, where each makes connection by suitable
coupling with the pipe end r of an operator's
valve mechanism R. As before stated, I pre-
fer to use liquid in this pipe-connection H,
and of the various liquids which may be used 100
therein to communicate pressure or impulse I
prefer one like alcohol, or petroleum, or other
equivalent liquid not liable to congeal or be
frozen. Such liquid or other fluid medium is
forced into the connecting-pipe under such 105
pressure as practically to exclude air or other
compressible gas or vapor and to secure a col-
umn or body of uniform density. In practice
the liquid composing such column may be con-
fined wholly within pipe H, or it may enter 110
and partially fill the chamber in shell R of the
valve mechanism, which may be made of suffi-
cient length for this purpose, as hereinafter
described. If the liquid is contained wholly
within pipe H, open communication is af- 115
forded to it from chamber R', by passage r .
Pressure to be communicated through the
column or pipe is imparted by fluid, by pref-
erence air, under pressure of sufficient degree.
This is done as follows: 120

To the upper end of shell R is screwed an
elbow-shaped upper shell or case, r' , closed at
its upper end by screw-plug or other equiva-
lent stopper, r^2 , having therein an annular
port, r^3 , for admission of air under pressure. 125
Air thus supplied passes downward between
the wings of upper valve-stem, n^3 , filling the
chamber r^4 below. At the angle of the elbow,
and extending downward therefrom, is a
valve plug or bushing, S, having therein ports 130
 $s s'$, leading from supply-chamber r^4 down-
ward and laterally to the tubular or pipe-like
passage r^5 , through the elbow-piece r' ; also, a
port, s^2 , in line with and below port s , opens

into a valve-chamber, s^3 , and thence by port s^4 to open air. The bushing s^5 , in the lower end of this valve-chamber, affords a guide for valve-stem N, on the upper end of which is formed the escape-valve n , seating upward against and closing the port s^2 . This valve has a pin-extension, n^5 , thereon, adapted to enter and fill or practically close the passage s^2 , like a piston, and thus prevent escape in case the conical portion n of the valve is not properly seated by reason of insufficient lift on the stem N. A reduced stem, n' , extends from pin n^5 upward through ports s^2 and s , and abuts against or enters a socket-passage, n^6 , in the supply-valve n^2 , which latter is formed on the lower end of winged stem n^3 , and seating downward closes port s from above. A light spring, r^6 , seated between the collar n^4 on stem n^3 and the inner end of plug r^2 above, presses valve n^2 upon an escape-valve, n , away from the respective seats or ports. Upward lift of sufficient force upon the stem N will seat escape-valve n and open supply-valve n^2 , thereby permitting air-supply under pressure to pass through ports s s' to passage r^5 , and thence to the upper side of collar or valve-ring m . This ring or collar moves loosely on the upper winged end, p , of stem P, and it is held in place thereon between a nut, p' , secured on the upper end of the stem, and a spring, p^2 , below, seated upon a collar, p^3 , on the stem.

Pressure of inflowing fluid upon the upper face of valve or ring m , if in excess of the resistance of spring p^2 , will depress such valve, permitting the fluid supply to pass downward through the wing-passages p to the chamber R' below. This pressure will be operative upon the liquid or other equivalent medium, whether the same is contained within pipe H or whether it enters and partially fills chamber R' , and being communicated through such medium will be effective in moving the diaphragm L' and opening the escape-valve e of the engine, as before described. When upward lift on stem N is released, the spring r^6 will seat valve n^2 , closing the supply and opening the escape-valve n . The escape thus afforded will reduce fluid-pressure in passage r^5 , so that fluid-pressure below the ring-valve m , plus the pressure of spring p^2 , will lift the valve and seat it upon the under face of nut p' , thereby preventing fluid escape past the same. As the passage r^5 is open to the external air by ports s^2 s^4 there will be practically atmospheric pressure only to oppose the pressure confined below the ring-valve m . Consequently the stem P will be raised toward or against the stop r^7 by such pressure, assisted somewhat by spring p^4 below, thereby unseating the valve u , formed on the lower end of the stem, and opening an escape-port, u' , formed in the bottom plug, R^2 , of the shell or case. If the liquid column is confined to pipe H, this escape may open directly to the exterior air, either by side port, u^3 , or by an open port in the end made by removing the screw-plug u^4 ,

such escape taking place when valve u is raised. If, on the other hand, the liquid column terminates in chamber R' , I prefer to make pipe-connection u^2 from port u^3 to a small tank or reservoir, U, fixed at sufficient height above the pipe H to insure sufficient liquid in the case R at all times to fill pipe H. As the valve u is raised the pressure upon the liquid will be relieved by forcing a portion of the liquid, in case liquid is contained in chamber R' , into the tank, thereby in either case providing for quick release or cessation of the force or impulse exerted upon the liquid column. Slow leakage past the valve m —such as is incident to valve-piston mechanism of this character—will permit the liquid in tank U and chamber R' to return to a common level. The valve u may be seated or returned to normal position either by the weight of the stem P and valve m or by pressure of inflowing fluid thereon, so as to impart to the liquid the desired impulse. The operation of valve m , stem P, and valve u , both in admitting fluid-supply, imparting impulse to the liquid column, and in relieving pressure below the valve m , is automatic, prompt, and efficient, and is substantially the same, whether liquid is present in the chamber R' or not; but if present the tank U performs an important function, not only in affording convenient means for maintaining liquid-supply without introducing air into the pipes, but also in providing relief from pressure or impulse without waste of liquid; also, to this same end the shell R may be made of considerable length—say six inches, more or less—in order that valve m may be clearly above the level of liquid, and thereby prevent discharge of liquid upward.

The stems N for supply and exhaust fluid may be lifted in any convenient and suitable manner, either by hand or by means of suitable mechanical contrivance. In Fig. 3 two of the valve mechanisms are shown connected together, each being connected by separate pipes H to its appropriate end D' of the mechanism, for shifting the distributing-valve a^2 of the engine, as before described.

Fluid-supply is by a passage, w , in upper connecting-bar, W, and the relief or escape may be either directly to the exterior air or by separate pipe-connections to tank U. The two valves are secured by flanges k to any suitable support, K, and their stems N are lifted by a rocking bar, T, upon the ends of which the stems rest, and the stems are raised alternately by rocking the pivot t , which carries the bar. This may be done either by hand or by mechanical contrivance, and I reserve for a separate application suitable interlocking apparatus for effecting these movements in predetermined order with reference to other operations to be performed on or about a track. Either fluid-supply valve n^2 will be opened, as desired, according to the movement of the rocking bar T in one or the other direction, and when said bar is moved into its middle or horizontal position both the fluid-supply valves will be

automatically seated and both fluid-exhaust valves opened by the springs r^6 .

Pressure communicated to the liquid column, as above described, will be transmitted almost instantaneously to and be effective on the diaphragm I' , and while I prefer to use air as a medium of communicating such pressure to the liquid, yet other fluid medium, or even a liquid medium, may be employed; also, instead of subjecting the liquid column to direct contact with the air or equivalent fluid, the two may be separated by a diaphragm or by movable piston or other equivalent yielding device by which pressure may be communicated from one to the other. Such partitions are not essential, but are referred to as modifications, which may, if desired, be made in details of construction, which I consider as coming within my invention; also, for the purpose of imparting impulse to the liquid column other means than fluid-pressure may be employed—for example, a mechanically-actuated plunger; or fluid-pressure may be admitted to and turned from the liquid column by a three-way cock or other equivalent device. I prefer, however, to employ for this purpose the valve mechanism herein shown and described, because best adapted to fill all the requirements of use.

I claim herein as my invention—

1. The method herein described of imparting movement from a distant station to the valve-shifting mechanism of a fluid-pressure engine or motor, consisting in connecting such mechanism with the distant station by a continuous inclosed column or body of liquid and giving movement or impulse to such column by subjecting the same to pressure at the distant station, substantially as set forth.

2. A fluid-pressure engine or motor having a main piston, a distributing-valve, pistons for moving the distributing-valve, and escape-valves for reducing fluid-pressure on one side of the valve-pistons, in combination with suitable mechanisms for unseating the escape-valves, and a fluid column for communicating impulse or movement to the valve mechanism from a distance, substantially as set forth.

3. The combination of distributing-valve a^2 , pistons c , escape-valves e , pistons I , and fluid-pressure diaphragms I' , substantially as set forth.

4. In a fluid-pressure motor, the combination of a distributing-valve, pistons for shifting the valve, escape-valves for reducing fluid pressure on one side of the piston, flexible diaphragms exposed on one side to a fluid column, pistons abutting against the diaphragms and the escape-valves, and springs for holding such latter pistons against the diaphragms, substantially as set forth.

5. In combination with the valve-shifting mechanism of a fluid-pressure motor, an inclosed fluid column for transmitting impulse without expenditure of fluid, and a movable or flexible partition between the valve mechanism and the fluid column for transmitting the impulse of the fluid column to the valve mechanism, substantially as set forth.

6. In combination with the valve-shifting mechanism of a fluid-pressure motor, a column of liquid for communicating movement to the valve mechanism from a distance, and valve mechanism for directing fluid under pressure upon the liquid column at the distant station, substantially as set forth.

7. A valve mechanism having, in combination, a valve-governed supply and exhaust ports at its upper end, and a valve-governed exit at its lower end, the valve for the latter exit having an upwardly-extending stem with a valve movable thereon opening downward to permit fluid passage and seating upward against and lifting the stem by fluid-pressure on the under side, substantially as and for the purposes set forth.

8. In mechanism for subjecting a liquid column to fluid-pressure, the combination of a case receiving a portion of the liquid at its lower end, valve-governed ports in the case above the liquid for supply and exhaust of fluid-pressure, a valve within the case above the level of the liquid, such valve opening downward to admit fluid-pressure to the liquid and seating upward to close the passage, and a valve-governed exit below the level of liquid, the valve to such exit being opened by upward pressure upon the valve above the liquid, substantially as set forth.

9. In mechanism for subjecting a column of liquid to fluid-pressure, the combination of a case having open communication with the liquid, valve-governed ports above the level of liquid for supply and exhaust of fluid-pressure, a valve-governed exit below the level of liquid, and a liquid reservoir or receptacle communicating with the exit, substantially as set forth.

10. The combination of rock-shaft t , bar T , valve-stems N , resting upon the bar on either side of the shaft and lifted alternately by rocking movements thereof, fluid-supply valves n^2 , and springs r^6 , acting to automatically seat said valves when the rock-shaft is moved to central position, substantially as set forth.

In testimony whereof I have hereunto set my hand.

GEO. WESTINGHOUSE, JR.

Witnesses:

R. H. WHITTLESEY,
J. SNOWDEN BELL.