



## M. B. McCASTLINE. CARPET FASTENER.






































Inventor —

DW C. Braymond.

Minne Dathone.

## United States Patent Office.

MINNIE B. McCASTLINE, OF SYRACUSE, NEW YORK.

## CARPET-FASTENER.

SPECIFICATION forming part of Letters Patent No. 362,171, dated May 3, 1887.

Application filed March 16, 1887. Serial No. 231,076. (No model.)

To all whom it may concern:

Be it known that I, MINNIE B. McCastline, of Syracuse, county of Onondaga, in the State of New York, a citizen of the United States, 5 have invented certain new and useful Improvements in Carpet-Fasteners, of which the following is a specification, reference being had to the accompanying drawings, in which—

Figure 1 is a sectional elevation on the line to of the tack. Fig. 2 is a like view on the line of the retaining-rod; Fig. 3, a like view of the base and fastening; Fig. 4, a view like Fig. 1, showing different base; Fig. 5, a view like Fig. 2, showing base of Fig. 4; Fig. 6, a view like 15 Fig. 1, showing another base; Fig. 7, a like view of Fig. 6 on the line of the retainingrod; Fig. 8, a view of the base and its fastening shown in Fig. 7; Fig. 9, a sectional elevation showing another base; Fig. 10, a sec-20 tional elevation showing another base; Fig. 11, a sectional elevation showing another base and follower.

My invention relates to that class of carpetfasteners in which the carpet is secured by per-25 manent tacks projecting above a base which is secured to the floor adjacent to the base-board; and it consists in the several novel features of construction and operation hereinafter described, and specifically set forth in the claims 30 hereunto annexed.

It is constructed as follows:

A represents the base in all of the figures of the drawings, consisting of a strip of wood or metal of one of the several forms shown, and 35 which is secured to the floor by a nail or screw, 1, so that at least one face will lie against the base-board. In this base I secure the tacks or spurs 2, the points of which project outwardly from the base. At the proper points I also 40 secure in the base the threaded rods 3, each of which is provided with a set or thumb screw of any desired form.

B is my follower, consisting of a strip of | hand this 25th day of February, 1886. wood or metal of one of the forms shown, per-45 forated to receive the outer ends of the tacks, as shown, at any angle desired, and also to receive the rods 3 at any desired angle. These

rods 3 are slotted or cross-bored to receive a key, 4.

C is an ornamental cap-molding, of wood or 50 metal, (metal is shown in the drawings,) perforated at intervals in its length to permit the rods 3 to pass through it. This cap consists of a front face, 5, a downward flange, 6, upon its back side, and an inward flange, 7, upon its 55 front side. The flange 6 rests against the base-board, and the flange 7 rests upon the carpet.

In the several figures the dotted line 8 rep-

resents the carpet.

It operates as follows: Having provided the base with the tacks 2 and rods 3, I secure it to the floor. I then draw up the edge of the carpet and press it down upon the tacks. I then put on the follower over the rods 3 and press 55 it down thereon until the points of the tacks enter or pass through it, and when down tight I insert the keys 5 through the rods 3, thus holding the follower in place. I then put on the cap C and screw down the thumb screws. 70

It will be observed that I can use a perforated washer upon the rods 3 in place of the follower, or a follower in such case composed of short pieces.

What I claim as my invention, and desire 75 to secure by Letters Patent, is—

1. A carpet-fastener consisting of a base provided with projecting tacks, a follower fitting upon said tacks, a cap piece, and retaining-rods passing through the base, the follower, so and the cap, substantially as shown and described.

2. A carpet-fastener consisting of a base provided with projecting tacks and rods 3, a follower fitting over said tacks and rods and 85 held in place by keys through said rods, and a cap-covering secured upon the rods 3, substantially as shown and described.

In witness whereof I have hereunto set my

MINNIE B. McCASTLINE.

In presence of— C. W. SMITH, F. L. STEVENS.