


(No Model.)

W. SEXAUER.  
CARPET STRETCHER.

No. 362,791.

Patented May 10, 1887.



Witnesses:

A. S. Dobson  
Benj. P. Coulson

Inventor:

Wm. Sexauer



# UNITED STATES PATENT OFFICE.

WILLIAM SEXAUER, OF OMAHA, NEBRASKA.

## CARPET-STRETCHER.

SPECIFICATION forming part of Letters Patent No. 362,791, dated May 10, 1887.

Application filed October 12, 1886. Serial No. 216,065. (No model.)

*To all whom it may concern:*

Be it known that I, WILLIAM SEXAUER, a citizen of the United States, residing at Omaha, in the county of Douglas and State of Nebraska, have invented certain new and useful Improvements in Carpet-Stretchers; and I do hereby declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the art to which it ap-  
10 pertains to make and use the same.

This invention relates to improvements in carpet-stretchers; and it consists of a combined carpet stretcher, holder, knee-rest, and tack-hammer, as will hereinafter be fully described.

15 In the accompanying drawings, Figure 1 represents a perspective view of the combined implement, and Fig. 2 an underside plan view of a portion thereof.

A represents a knee-rest and carpet stretcher and holder, comprising a strip, frame, or block of wood or other suitable material, and of any desired shape and length, such as oblong, as represented in the drawings. This block or strip is upholstered on its upper portion, as  
20 shown at B, to form a cushioned rest for the knees of the user. At suitable intervals on the under side of this frame or knee-rest A are removably attached transverse strips of woven-wire cloth C, or some suitable fabric,  
25 having short fine wires D projecting outwardly therefrom, which grip the carpet with sufficient tenacity to hold it firmly and yet avoid the abrasion, puncturing, or tearing of the carpet, as will be presently explained.

35 E represents a combined tack-hammer and carpet-stretching lever having a head, F, grooved and perforated side faces, G, to facilitate the implement being grasped and firmly held by the user, and curved, pointed, or hooked lower end, H, to take into the floor, and an in-  
40 curved hook or lug, I.

J represents a rod or wire connecting the upholstered carpet stretcher and holder and knee-rest A and the combined lever and ham-  
45 mer E, said rod or wire connecting at one end with the frame A by a hook and eye, as shown, and at its opposite end, by means of a loop, K, with the lever E.

50 In use the upholstered frame A is placed upon the carpet a suitable distance from the edge to be secured, with the upholstered top portion uppermost, and with the woven or

outwardly-projecting wires D resting upon the carpet. The user then rests one knee upon the upholstered top of the frame A with sufficient  
55 pressure to cause the wire-cloth or wires on its under side to grip the carpet. The user then grasps the combined tack-hammer and lever E, sticks the point H in the floor beyond the edge of the carpet and raises the lever E upward to any  
60 suitable angle, say of about forty-five degrees, (more or less,) when the combined device will assume the position represented in Fig. 1 of the drawings. As the lever is thus raised, it neces-  
65 sarily follows that, owing to the pointed lower end, H, thereof being inserted in the floor, said lever will, through its connecting rod or wire J, operate as a fulcrum to draw the frame A toward it, and as the fine teeth D on the un-  
70 der side of the frame A are in gripping contact with the carpet, by reason of the superposed weight of the user's knee, it also follows that the carpet will be drawn forward and tightly stretched throughout the area thereof behind  
75 the frame A. The desired stretching of the carpet being thus attained, the user then rests both knees upon the upholstered top face of the frame, so as to hold it and the carpet there-  
80 under securely in position. The combined lever and tack-hammer E is then released from the connecting-rod J by slipping said rod off the hook I, and the hammer is then brought into play to tack the carpet down. By reason of  
85 the under carpet-gripping surface being composed of fine wires, upon the user pressing upon the frame in the manner before mentioned said wires will simply grip the carpet and will not  
90 penetrate the same to a degree to form holes therein, or so as to tear it under the forward strain exerted upon the frame by the operation of the lever E; but at the same time said wires  
95 will grip the carpet with sufficient tenacity to insure its being properly stretched as the lever is raised and pushed forward.

I am aware that it is not new to construct a  
knee-rest with an upholstered top face; that it  
95 is not new to apply card-clothing or teeth to the under face of a knee-rest, and that it is also not new to connect to a knee-rest, by means of  
100 a rod, a fulcrum-lever having pointed lower end, and such I do not broadly claim.

Having thus described my invention, what I claim is—

The combined carpet stretcher and holder

herein described, comprising a knee-rest having an upholstered top surface, a series of strips of woven-wire cloth removably attached to the under side of said knee-rest, a combined lever and tack-hammer, said lever having grooved side faces, a curved and pointed lower end, and an incurved hook, and a rod or wire having at one end a loop to engage the hook on the lever, and at its opposite end connecting with the knee-rest by a hook and eye, as shown and described. 10

WILLIAM SEXAUER.

Witnesses:

NELSON HILL,  
W. W. WRIGHT,  
W. P. WELCH.