

(No Model.)

A. BRENOWITZ.
SAFETY POCKET FOR GARMENTS.

No. 363,586.

Patented May 24, 1887.

Fig. 1.




Fig. 2.




Fig. 3.




Fig. 4.



WITNESSES:

Alfred du Faurg
William Miller

INVENTOR

Abraham Brenowitz

BY *Van Santvoord & Hauck*

ATTORNEYS

UNITED STATES PATENT OFFICE.

ABRAHAM BRENOWITZ, OF NEW YORK, N. Y.

SAFETY-POCKET FOR GARMENTS.

SPECIFICATION forming part of Letters Patent No. 363,586, dated May 24, 1887.

Application filed March 31, 1887. Serial No. 233,170. (No model.)

To all whom it may concern:

Be it known that I, ABRAHAM BRENOWITZ, a citizen of the United States, residing at New York, in the county and State of New York, have invented new and useful Improvements in Safety-Pockets, of which the following is a specification.

This invention relates to improvements in safety-pockets, as set forth in the following specification and claim, and illustrated in the accompanying drawings, in which—

Figure 1 shows a safety-pocket applied to an apparel. Fig. 2 is a detail perspective view of a pair of jaws. Fig. 3 is a transverse central section of a safety-pocket applied to an apparel. Fig. 4 is a section of a jaw in the plane $x x$, Fig. 2.

Similar letters indicate corresponding parts.

In the drawings, the letter A designates the substance of the apparel, such as cloth.

In Fig. 3 a portion of the substance A is cut and the lips of the cut are respectively clamped or secured to the jaws B C of a frame. The jaws B C swing about a pivot or joint, D. A back, F, of cloth or other material, suitably sewed or secured to the substance A, completes the pocket.

The jaw C is provided on its under side, at a suitable point between its ends, with a depending loop, E, through which may be passed a watch-chain, and such insertion of the watch-chain through said downwardly-projecting loop will prevent the watch from being surreptitiously removed from the pocket without

the wearer's notice. By making the depending or downwardly-projecting loop E of metal the watch-chain is prevented from chafing the apparel. The entire jaw C is preferably made of one piece of metal, said piece being so formed as to provide an eye for the jaw.

For the purpose of securing the lips or edges of the material A to the jaws the latter are channeled along their undersides, so that when the lips or edges of the material comprising the pouch or pocket are inserted thereinto such lips or edges may be clamped in place. The depending loop E is also channeled to receive the lip or edge of the fabric comprising the pocket, as shown in Fig. 2.

What I claim as new, and desire to secure by Letters Patent, is—

A garment the pocket of which is provided with a frame consisting of the two jointed jaws, each having a channel along its under side, in which are clamped the edges of the material comprising the pouch or pocket, and one of said jaws provided at its inner edge with the depending loop E, in which one edge of the material is also secured, substantially as and for the purposes described.

In testimony whereof I have hereunto set my hand and seal in the presence of two subscribing witnesses.

ABRAHAM BRENOWITZ. [L. S.]

Witnesses:

W. C. HAUFF,

E. F. KASTENHUBER.