

(No Model.)




2 Sheets—Sheet 1.

C. C. HUDSON.

CASE FOR DISPLAYING TUBES AND VIALS.

No. 372,222.

Patented Oct. 25, 1887.



Witnesses:

Edwin K. Roper
Royal Doane

Inventor.

C. Columbus Hudson
per Alex. C. Estess
Attorney.

(No Model.)



2 Sheets—Sheet 2.

C. C. HUDSON.

CASE FOR DISPLAYING TUBES AND VIALS.

No. 372,222.

Patented Oct. 25, 1887.



Witnesses:

Joseph P. Eustace.

Edwin K. Roper

Inventor.

C. Columbus Hudson
per A. C. Eustace
Attorney

UNITED STATES PATENT OFFICE.

C. COLUMBUS HUDSON, OF ELMIRA, NEW YORK.

CASE FOR DISPLAYING TUBES AND VIALS.

SPECIFICATION forming part of Letters Patent No. 372,222, dated October 25, 1887.

Application filed March 7, 1887. Serial No. 230,049. (No model.)

To all whom it may concern:

Be it known that I, C. COLUMBUS HUDSON, residing at the city of Elmira, in the county of Chemung and State of New York, have invented certain new and useful Improvements in Cases for the Carriage and Display of Tubes and Vials, of which the following is a specification.

My invention is a new and useful improvement relating to cases for the carriage and display of vials and tubes, by means of which is afforded an ornamental receptacle for the display of goods contained in tubes and vials, and a secure and convenient means of packing the same for storage or transportation.

The invention consists in the particular construction, combination, and arrangement of parts, as hereinafter more fully set forth.

In the accompanying drawings, forming part of this specification, and in which similar letters refer to similar parts throughout the various views, Figure 1 is an oblique projection of my improved display-case. Fig. 2 is a plan of the inner face of top piece, B. Fig. 3 is an end elevation of base C, showing jaws and springs. Fig. 4 is a plan of base C without jaws attached; and Fig. 5 is a plan of the under face of base C, showing metal spring *g*. Fig. 6 is an oblique projection, showing construction of top piece, which may be substituted for the top piece, B, as described hereinafter; and Fig. 7 is a section of said top piece on the line O N of Fig. 6.

Referring to the drawings, A represents a rectangular frame having on the inner face of its base C the rabbet *a*, along one side of the central longitudinal flange, *b*, the opposite side of said flange being provided with notches *c c*.

Hinged, or removably secured to the sides of the base C, are jaws *d d*, the ends of which are connected to and held firmly against the body of the frame A by means of elastic strips *e e*. In the top piece, B, above and in a line with the rabbet *a* and the notches *c c*, are the sockets *f f*, adapted to receive the corks or caps of vials or tubes. The bottoms of the tubes and vials rest in the rabbet *a* and the notches *c c*, and are held firmly in place by the jaws *d d*, which are drawn tightly against the vials and tubes by the elastic strips *e e*. The tubes or vials are readily removed from the frame by pressing the jaws *d d* outward far enough to

allow the bottoms of the tubes or vials to pass outward over the tops of said jaws. It is also intended to use, when desired, either separately or in connection with the elastic strips *e e*, and for the purpose of springing said jaws firmly against the sides of the tubes and vials, the metal strip *g*, secured to the central part of the under face of the base C, and extending crosswise under the edges of the jaws *d d*.

If preferable, the construction here shown for the base C, including rabbet, notched flange, jaws, and springs, may be substituted for the construction of top piece, B, shown, in which case the top and bottom of frame A would be same as the bottom shown in drawings. It will be observed that the rabbeted side of flange shown is especially adapted to hold the bottoms of what are known as "collapsible tubes" and the notched side of flange for ordinary vials and tubes. The elastic strips *e e* may be placed at one or both ends of jaws, as preferred, and the metal spring *g* may be multiplied, if desirable. The case may be covered with satin or plush or otherwise ornamented.

The central longitudinal flange, *b*, referred to may be constructed with the notches *c c* on one or both sides of it, or without such notches on either side, at pleasure.

I claim in behalf of this case that its use will, besides affording an ornamental exhibition of those lines of goods sold in small tubes and vials, prevent the serious loss which retail dealers experience, through petty thievery, of such goods when loosely shown on store counters and cases.

Having thus described my invention, what I claim as new, and desire to secure by Letters Patent, is—

1. A case for the carriage and display of vials and tubes, consisting of rectangular frame A, whose base is provided with the rabbet *a*, the flange *b*, the jaws *d*, and the elastic strips *e*, and the inner face of whose top piece, B, is provided with the sockets *f f*, substantially as shown and described.

2. A case for the carriage and display of tubes and vials, consisting of a rectangular frame, A, the inner faces of any two opposite sides of which are provided with rabbets *a*, longitudinal flanges *b*, hinged longitudinal jaws *d*, extending along the sides of said flanges,

and elastic strips *e*, connecting the jaws *d* with the frame *A*, substantially as shown and described.

3. In a display-case for tubes and vials, the
5 combination, with a rectangular frame, *A*, the inner surface of one of whose sides is provided with a central longitudinal flange, *b*, and rabbet *a*, of hinged longitudinal jaws *d*, extending along the sides of said flange *b* and rabbet *a*,
10 and elastic strips *e*, connecting said jaws *d* with said frame *A*, substantially as and for the purposes described.

4. In a display-case for tubes and vials, the

combination, with a rectangular frame, *A*, the inner surface of one of whose sides is provided 15 with a central longitudinal flange, *b*, and rabbet *a*, of hinged longitudinal jaws *d*, extending along the sides of said flange *b* and rabbet *a*, and metal strip *g*, secured to the outer surface of such side of frame *A*, and extending later- 20 ally across the edges of jaws *d*, substantially as and for the purposes shown and described.

C. COLUMBUS HUDSON.

Witnesses:

THEODORE M. McKNIGHT,
CHARLEY F. BROMLEY.