


(No Model.)

H. D. & C. H. HARD & J. CRAWFORD.

FOLDING COT.

No. 373,363.

Patented Nov. 15, 1887.





# UNITED STATES PATENT OFFICE.

HENRY D. HARD, CHARLES H. HARD, AND JOHN CRAWFORD, OF ONEIDA,  
NEW YORK.

## FOLDING COT.

SPECIFICATION forming part of Letters Patent No. 373,363, dated November 15, 1887.

Application filed February 28, 1887. Serial No. 222,209. (No model.)

*To all whom it may concern:*

Be it known that we, HENRY D. HARD, CHARLES H. HARD, and JOHN CRAWFORD, of Oneida, in the county of Madison and State of New York, have invented certain new and useful Improvements in Folding Cots; and we do hereby declare that the following is a full, clear, and exact description thereof, reference being had to the accompanying drawings, and to the letters of reference marked thereon, which form part of this specification, in which—

Figure 1 is a perspective view of our improved folding cot ready for use. Fig. 2 is a rear elevation of the same. Fig. 3 is a vertical central section. Fig. 4 is a plan view of cot, showing same folded. Figs. 5, 6, and 7 represent details showing the construction of the head-rest. Fig. 8 is a detail section through the joint of the legs.

This invention relates to improvements in folding cots, and has especial reference to the devices for bracing the legs of the cot when opened, and to an improved head-rest for the same.

The invention consists in the novel construction and arrangement of parts, as will be hereinafter fully described, and particularly specified in the claim.

Referring to the accompanying drawings, A A' designate the respective side rails of the cot, to which the side edges of the web or ticking X are secured in the usual well-known manner.

B B' are the legs, pivoted to the said rails near the head of the cot. The said legs each has preferably secured to its upper end a plate, b, which is pivoted at b' upon the inner surface of the corresponding side rail in such manner that the leg can be turned up against the inner surface of the side rail when the cot is folded.

The legs B B' are pivoted together at c at about their central points, and leg B is provided on its outer side and above its pivotal point with a longitudinal recess, C, and the leg B' is provided on its inner face, but below its pivotal point, with a similar recess, C'.

c' c' are slotted guard-plates, which are secured upon the legs B B' over said recesses, the edges of the slots in each plate extending inward over the edges of the recess, for a purpose hereinafter explained.

D D' are legs similar to the legs B B', and similarly pivoted together at e. Their upper ends have secured to them plates d, similar to the plates b, and similarly pivoted at d' d' to the side rails, A A'. The pivot-joints d' d' are at equal distances from the rear ends of the side rails as the pivot-points b' b' are from the front or head ends of the same. The leg D has above its pivot-point e a longitudinal recess, E, and the leg D' has below its pivot-point a recess, E', similar to the recesses C C', and similarly overlaid by slotted guard-plates e' e'.

F is a bar or rod, having its upper end bent outwardly horizontally and journaled in the side rail, A', near the head end thereof, so as to turn thereon. The lower end of the rod F is bent horizontally, so as to enter the recess C in the leg B, and is provided with a head, f, which is retained in the recess by the edges of the slotted guard-plate c'. G is a similar rod, having its bent upper end journaled in the side of the rail A, near the foot end of the same, and provided with a head, g, on its bent lower end, which travels in the recess E' of leg D', and is retained therein by the edges of the slotted guard-plate e'.

F' and G' designate rods similar to rods F and G. Rod F' has its upper end journaled in the rail A inward of the legs B B', and has its headed lower end engaging the recess C' in leg B' by means of plate c', as shown. The rod G' is similarly engaged with rail A and leg D, and is secured on the cot to the inner side of the legs.

H H' are the head-rest bars, each attached to the corresponding side rail, A A', near the head end thereof, by means of the short rods h h'. There are two of these rods for each bar. The inner ends of the rods are bent at right angles upward and journaled in the lower surface of the bars H, and the outer ends of the rods are bent similarly downward and journaled in the upper edge of the corresponding head-rail, as shown. The rods h h' being equal in length, the bars H can be turned upward and inward in relation to the side rails, or outward against the latter for transportation.

X' is the web or cloth for the head-rest. When the bars H are turned upward and inward, this web is raised and tightened and forms a suitable support for the head.



In folding the cot for transportation the two siderails are brought together, folding the legs of each set upon the other. The legs are then folded upward and inward against the side rails, the heads *f g* of the rods *F G* slipping upward in the recesses *C E*, respectively, and the heads *f' g'* of rods *F' G'* slipping downward, or toward the feet of their respective legs *B' D'* in the recesses *C' E'* thereof. The bars *H* are folded down against the side rails and the web *X* wound around the front end of the latter. This folds the device in very small compass.

It will be observed from the foregoing that when the cot is opened, as described, the rods *F F'*, standing from the opposite side rails of the cot and on opposite sides of legs *B B'*, strongly brace the latter and prevent their shifting out of proper supporting position when the cot is opened, and the rods *G G'* perform a similar office for legs *D D'*. It will be further observed that the rods form additional supports for the side bars by transferring strain from their points of connection with said bars directly to the legs of the cot. By the de-

scribed construction it is obvious that the cot when opened is held rigidly, and the legs cannot be knocked down or turn under while the cot is occupied.

Having described our invention, we claim— 30

A folding cot comprising parallel side rails, pairs of crossed pivoted legs pivoted to said rails, and two diagonal bracing and supporting rods slidably attached on opposite sides of each pair of legs above and below the pivot of said legs and to the side rails, whereby when the cot is extended the lower end of one rod of each pair will lie above the crotch of the legs and the lower end of the other rod will be below said crotch, substantially as described. 35 40

In testimony that we claim the foregoing as our own we affix our signatures in presence of two witnesses.

HENRY D. HARD.  
CHAS. H. HARD.  
JOHN CRAWFORD.

Witnesses:

JULIUS W. SPERRY,  
L. ELISHA GALLUP.