

(No Model.)


4 Sheets—Sheet 1.

A. JOHNSTON.

CUTLERY GRINDING MACHINE.

No. 377,201.

Patented Jan. 31, 1888.



Witnesses:

Sew. C. Curtis.
Jos. L. Rippey Jr

Inventor:

Allen Johnston.

By Munday Everts & Adcock
his Attorneys:


(No Model.)

4 Sheets—Sheet 2.

A. JOHNSTON.
CUTLERY GRINDING MACHINE.

No. 377,201.

Patented Jan. 31, 1888.



Witnesses:
Geo. C. Curtis
Geo. L. Rippert

Inventor:
Allen Johnston.
By Munday Evans & Deock
his Attorneys:

(No Model.)




4 Sheets—Sheet 3.

A. JOHNSTON.

CUTLERY GRINDING MACHINE.

No. 377,201.

Patented Jan. 31, 1888.



Witnesses:

Levi C. Curtis.
Jas. L. Rippey.

Inventor:

Allen Johnston.

By Munday Evans & Alcock.

His Attorneys:


A. JOHNSTON.

CUTLERY GRINDING MACHINE.

No. 377,201.

Patented Jan. 31, 1888.

Fig. 5.



Figs 11+12.




Fig. 13.




Fig. 6.




Fig. 7.





Fig. 8.



Witnesses:

Geo. C. Curtis
Jas. L. Ruppel

Inventor:

Allen Johnston

By Munday Evans Tadeock
His Attorneys:

UNITED STATES PATENT OFFICE.

ALLEN JOHNSTON, OF OTTUMWA, IOWA.

CUTLERY-GRINDING MACHINE.

SPECIFICATION forming part of Letters Patent No. 377,201, dated January 31, 1888.

Application filed July 28, 1887. Serial No. 245,473. (No model.)

To all whom it may concern:

Be it known that I, ALLEN JOHNSTON, a citizen of the United States, residing in Ottumwa, in the county of Wapello and State of Iowa, have invented a new and useful Improvement in Cutlery-Grinding Machines, of which the following is a specification.

My invention relates to improvements in machines for grinding cutlery or other articles which require to have a convex surface.

The blades of table-knives are usually and preferably ground with convex curved instead of flat or plane surfaced sides. Heretofore these knives have usually been ground upon the outside cylindrical surface of a grindstone or emery-wheel the thickness or width of which is equal or about equal to the length of the knife-blade, the knife being held by the workman about parallel to the axis of the stone, and the convexity being given to the side of the knife by the workman continually rocking the same on the stone as it is being ground. In this method of grinding the knife is and can be given little if any reciprocating movement across the face of the stone, and as a consequence, owing to inequalities in the hardness, &c., of the stone at different parts, and the varying amount of grinding required at different points along the length of the knife, the stone or emery will soon wear uneven and its periphery become more or less wavy or made up of a series of high and low bands. In practice, therefore, the workman is required to stop grinding every hour or two and dress his stone by chopping or hacking its peripheral surface all over with a suitable instrument, and thus filling it with a series of transverse grooves, cavities, or hackles, the hackles being made closer and deeper in the high parts of the stone and fewer and lighter in the low parts, so that the stone may again receive an approximately true cylindrical surface. This method of grinding is not only comparatively slow, laborious, and expensive, requiring skilled labor, but it also results in quite a proportion of the stone being wasted, hacked, or chopped away instead of utilized.

The object of my improvement is to provide improved machines for grinding knives or other articles with a convex surface.

In my improved machine knives or other articles are ground with a convex surface by

automatically feeding the knife or article across the inside conical surface of a revolving annular or ring grinder. The degree of convexity given to the surface of the article may be varied or regulated by varying the inclination at which the knife is held to the axis of the annular stone. If the article is held parallel to the axis of the stone, it will have the full convexity of the inside curved surface of the annular stone. If it is held at right angles to the axis of the stone it will of course be ground on a plane or flat surface, and at intermediate inclinations the degree of convexity will be inversely proportioned to the angle.

My invention consists, in a grinding machine, of the combination, with a revolving hollow or cup-shaped grinder, of a work-holder reciprocating across the inside surface of said grinder in an inclined position to the axis thereof.

It also consists, in connection with such grinder and work-holder, of the particular mechanism I have devised for operating the same, whereby I am enabled to keep the grit from the working parts.

It also consists, in connection with such grinder, of an inclosing-case provided with an upper and lower water-receptacle, whereby the centrifugal action of the revolving stone is made to supply the water or other liquid continuously to the grinding-surface and directly at the point where the work is being done. Where the grinding is done upon the end face or upon the outside periphery of the grinder, as heretofore, and the grinder is revolving at great speed, as is usually the case, the centrifugal action tends to quickly throw the water from the grinding-surface of the stone. However close to the work, if the speed is very high, the water may be poured upon the stone the centrifugal force will throw it from the stone and leave its surface comparatively dry. By my invention, however, the water is raised from the lower receptacle to the upper receptacle by the centrifugal action of the outer periphery of the stone, and is delivered upon the interior peripheral surface of the stone by a spout or conductor leading from the upper water receptacle or trough, and the water being thus delivered upon the inside of the wheel, the centrifugal action tends to spread it out in a thin annular sheet over the whole

inside surface of the stone and to flow it over the grinding edge or surface of the stone all around and at the very place where the work is being done.

- 5 In the accompanying drawings, which form a part of this specification, and in which similar letters of reference indicate like parts, Figure 1 is a side elevation of a machine for practicing my invention and embodying the same. 10 Fig. 2 is a central vertical longitudinal section. Fig. 3 is a horizontal section on line 3 3 of Fig. 2. Fig. 4 is a vertical cross-section on line 4 4 of Fig. 3. Fig. 5 is a detail perspective view of the hollow stone and inclined reciprocating work-holder. Fig. 6 is a detail 15 horizontal sectional view showing the work-holder and the means for reciprocating the same. Figs. 7 and 8 are detail views illustrating the operation of the work-holder-reciprocating mechanism. Fig. 9 is a detail perspective view of the hollow grinder and the knife being ground thereon, and Fig. 10 is a cross-section of the reciprocating work-holder and its guideway. Figs. 11 and 12 are cross-sections of the knife, the former showing one side 20 ground and the latter both. The degree of convexity is exaggerated. Fig. 13 is a detail plan view of the segment and gear for operating the knife-feed slide.
- 30 In said drawings, A represents the frame of the machine, which may be of any suitable construction.

B is a hollow ring, rim, or cup-shaped grinder. This grinder may be made of stone, emery, or other suitable material. The hollow 35 grinder may, if desired, have one end or head, in which case the grinder will be cup-shaped; but I preferably make the grinder in the form of an annulus or ring.

- 40 B' is a revolving holder in which the hollow grinder B fits, and is secured by the set-screws b . The stone or emery holder B' is preferably made cup-shaped, or with a closed end, and is secured, by screw-threads or otherwise, upon a hollow revolving shaft, B^2 , which is journaled 45 in a sleeve, B^3 , mounted upon the frame of the machine. The annular grinder B is adjusted or pushed out of its holder B', as it wears away, by means of a follower-disk, b' , which fits against the back end or edge of the 50 grinder, and is secured upon the adjustable rod b^2 , which fits in the hollow shaft B^2 , and is adjusted by means of the set-screw b^3 , which works in the hollow threaded end of said rod.
- 55 The sleeve B^3 also has a slight sliding movement in its bearing on the frame of the machine, for the purpose of adjusting the pressure of the grinder against the work or article being ground. This adjustment is effected by 60 means of the threaded hand-wheel b^4 , the threads of which work in threads b^5 cut upon the sleeve B^3 . The sleeve B^3 is kept from revolving by a key, b^6 , or other suitable means. The emery-holder B' is furnished with a hub, 65 b^7 , of the same exterior diameter as the sleeve B^3 , and fits snugly against the end of said sleeve. The interior of this hub is threaded

70 closely upon the hollow shaft B^2 , so that the grit or grindings worn from the stone cannot get into the bearing or journal of the shaft B^2 . The follower b' and its rods b^2 close the end of the hollow shaft B^2 , and prevent the 75 grit to any appreciable extent working its way through the same, and, moreover, the centrifugal action tends to throw such particles away from the axis.

C represents the hollow case which incloses the grinder B and its holder B', and also constitutes the upper and lower water receptacles or troughs, C C^2 . The water in the lower receptacle, C^2 , is maintained at such depth 80 that the outer periphery of the grinder B or its holder B' will turn in the water, and by its centrifugal action throw or carry the water up so that it will strike upon the inside of the case C and fill the upper water receptacle or 85 trough, C' . A spout or conductor, C^3 , leads from this upper trough, C' , and delivers the water upon the interior peripheral surface of the hollow or cup-shaped wheel B. As the water 90 is thus delivered upon the inside of the grinder, the centrifugal force of the revolving grinder tends to spread it in a thin film over the inside surface of the wheel, and to cause it to flow out in an annular sheet over the grinding 95 edge or rim of the annular stone, and thus supply the water continuously and evenly to the stone at the very point where the work is being done. By this means I am enabled to effectually prevent the heating of the article being ground, however rapidly the stone 100 may revolve, and also to facilitate the work.

It is obvious that if the knife or article, c , being ground were to be held against the inside surface of the revolving stone, and about 105 parallel to the axis of the stone, the convexity given to the ground surface of the knife would be the same as the curve of the stone. In grinding cutlery I in practice usually employ a hollow stone about a foot in diameter. 110 Such a stone would give much too great a degree of convexity to the knife if the knife should be held parallel or nearly parallel to the axis of the stone, and if the article were so held the annular stone would wear thinner 115 and thinner, and it would be difficult to utilize all or nearly all of the material of the stone. By holding and reciprocating the knife or article at a greater or less inclination across the rim or edge of the stone any degree of convexity desired may be given to the face of the 120 article ground from the full curve of the stone to a flat or plane surface. By grinding the article upon the inclined or conical surfaced end or edge of the annular stone nearly the whole 125 material of the stone may be utilized.

D represents the inclined reciprocating work-holder upon which the work—knife or other article—being ground is held and supported, and by which it is reciprocated across 130 the conical surface of the annular stone. This work-holder, as shown in the drawings, is specially adapted for holding table cutlery or knives. The holder, however, may readily

be adapted to hold other articles. The holder is provided with a longitudinal ledge, d , against which the back of the knife rests, and with a pin or lug, d' , to enter one of the handle-holes in the handle of the knife. The holder is further provided with a hook or clamp, d^2 , to prevent the knife falling off the ledge when not being pressed against the grinder. The work-holder D is mounted and reciprocates upon a suitable guide, D' . The guide D' is mounted adjustably or pivotally upon the frame of the machine by means of its hollow pivot d^3 and set-screw d^4 , so that the inclination of the guide to the axis of the revolving grinder may be varied or adjusted as desired. The work-holder D is reciprocated upon its guide D' by means of a rack, d^5 , secured to said holder by screws d^6 and a gear, d^7 , on the shaft d^8 , which meshes with said rack. The shaft d^8 is revolved by means of a segment, d^9 , pivoted at d^{10} to the frame of the machine, and which meshes with a gear, d^{11} , on the shaft d^8 . The pivoted segment d^9 is furnished with a pin or friction-roller, d^{12} , and is oscillated back and forth by a grooved cam, E, on the shaft E' . The shaft E' is driven by a worm, f , on the shaft F, which meshes with a gear, f' , on the shaft E' . The shaft F is journaled in a sleeve, F' , pivoted at F^2 to the frame of the machine. The shaft F is furnished with a driving-pulley on its end and is driven by a belt. The sleeve F' is furnished with a handle, F^3 , at its outer end, by which the worm may be raised into engagement with the gear f' . The sleeve F' is further provided with a spring pawl or catch, f^2 , which engages a corresponding pawl or notch, f^3 , upon the frame of the machine and serves to hold the worm f and gear f' in engagement until the gear f' has made one complete revolution. At each complete revolution of the gear f' a pin or lug, f^4 , thereon strikes the spring-pawl f^2 and disengages said pawl from the catch f^3 , and thus permits the worm f to drop out of engagement with its gear f' . The pivoted sleeve F' , in which the shaft F revolves, may be prevented from dropping too far when the pawl f^2 is disengaged from the catch f^3 by means of a slotted bracket or other support, as shown at f^5 in Fig. 4, the slot being indicated by dotted lines. At each complete revolution of the gear f' the cam E of course makes one revolution and the knife-holder is reciprocated back and forth across the beveled rim or edge of the hollow or cup shaped grinder B.

If desired, the mechanism may be readily arranged to cause the knife-holder to make two or more or any desired number of reciprocations across the hollow grinder by simply changing the shape of the cam-groove E. In grinding cutlery or table-knives, however, I have found one complete reciprocation of the knife and knife-holder to be ordinarily sufficient for each knife. As soon as the worm f is thus disengaged from the gear f' , the knife-holder ceases to reciprocate, and while it is thus stationary the operator removes the knife,

one side of which has been ground, and places another knife in the holder, and then by lifting on the handle F^3 he raises the worm f into engagement with its worm-gear f' .

It will be observed from the arrows that the stone revolves in the direction to press or force the back of the knife against the longitudinal ledge d on the holder D. If the stone were to revolve in the opposite direction, it would tend to raise or throw the knife out of its holder; and as it is also desirable to grind the knife with its edge forward in respect to direction of motion of the stone, I in practice grind one side of the knife upon one machine and the other or opposite side of the knife upon another machine, the two machines being duplicates of each other, excepting that the knife-holders are arranged at the opposite ends of the annular stone.

For the purpose of protecting the guide or slide way D' of the reciprocating work-holder D and its rack d^5 and gear d^7 , I make the guide groove or way d^{13} in the under face of said holder and of a dovetail shape, as indicated clearly in Fig. 10, thus giving the holder D an inverted-box shape, the ends of which also are closed by plates D^3 D^3 . The rack d^5 and gear d^7 are thus also protected and covered by the box form of the sliding holder D, the gear d^7 being inclosed between the slide and its guide D' .

An angle-arm, d^2 , is secured to the frame of the machine and serves in a measure to hold the knife or work in place on its holder D. The ledge d , upon which the knife rests, should be made of hardened steel and separate from the knife-holder slide, being secured thereto by screws, as indicated in the drawings.

In practice I usually employ hollow cylindrical emery-grinders, the same being cast or made in the form of hollow cylinders with square ends. The end of the same upon which the grinding is done will soon assume a bevel or conical surface corresponding to the inclination at which the knife-holder and knife thereon are held and reciprocated in respect to the axis of the grinder. It is not necessary, however, that the grinder be made in the form of a hollow cylinder. It may be in the form of a hollow cone or dish shape. In such case, however, it is obvious that as the grinder wears away and the diameter of its bevel grinding-surface becomes less and less the inclination at which the work is held to the axis of the grinder will need to be varied if it is desired to give the same degree of convexity to the ground surface. If the grinder is made in the form of a hollow cup, the annular rim or ring-holder B' will not be required, as in such case the stone may be secured in the ordinary manner upon the revolving shaft. If the disk or follower b' (indicated in Fig. 2) were made integral with the stone B, it would represent the head or bottom of a cup-shaped grinder.

I do not herein claim the process or method of grinding knives or cutlery with a convex surface, consisting in feeding the article across the internal edge of a cylindrical revolving grinder, nor the method of regulating the de-

gree of convexity of the ground surface by adjusting the inclination of the line of feed of the article relative to the axis of the grinder, as the same constitutes the subject-matter of a divisional application, Serial No. 259,387, filed December 30, 1887.

I claim—

1. The combination of a hollow cylinder or cup-shaped ring-grinder having an internal cone-shaped end surface with a work-holder and a guide for said work-holder inclined to the axis of said work-holder, whereby the side or surface of the article to be ground may be fed across and parallel to the conical end surface of said grinder, substantially as specified.

2. The combination, with a revolving hollow or cup shaped grinder, of a trough or receptacle in which the outer periphery of said grinder revolves, a second trough or compartment into which the liquid is elevated or thrown by the centrifugal action of the grinder, and having a spout or connection leading to the interior of the hollow grinder, and by which it is thus automatically delivered upon the inner surface of the hollow or cup-shaped grinder, so that the centrifugal action thereof will flow or spread the liquid entirely and constantly over and to the grinding-surface at the very point and time the work or grinding is being done, substantially as specified.

3. The combination, with a hollow or cup-shaped grinder, of a water spout or conductor directed into the hollow grinder for delivering a supply of water upon its interior periphery, so that the centrifugal action will flow or distribute the water constantly to the grinding-surface, substantially as specified.

4. The combination of a hollow or cup-shaped grinder with a water trough or receptacle, an inclosing-case, an elevated water trough or receptacle, and a spout or conductor to deliver the water from said elevated trough to the interior of the wheel, so that the centrifugal action may serve to automatically supply the water to the grinding-surface, substantially as specified.

5. The combination, with a hollow emery cylinder or ring, a hollow cylindrical holder for said ring, and reciprocating knife-holder slide mounted upon an adjustably-inclined guideway, said guideway being inclined toward the axis of said grinder and adapted to reciprocate said work-holder and the article held thereon to be ground in and out of said hollow grinder and over and parallel to its inside conical end surface, substantially as specified.

6. The combination, with a hollow emery-cylinder, of a holder for said emery-cylinder and an inclosing-case provided with a lower and an upper water trough or receptacle, substantially as specified.

7. The combination, with a hollow revolving grinder, of a reciprocating work-holder and threaded sleeve B³, and hand-nut b⁴, for adjusting the pressure of the grinder against the ar-

ticle being ground in the work-holder, substantially as specified.

8. The combination of hollow grinder B, with its revolving holder B', secured to hollow shaft B², follower b', abutting against the end of said grinder, and adjustable follower-rod b², mounted in said hollow shaft, substantially as specified.

9. The combination of hollow grinder B, with its revolving holder B', secured to hollow shaft B², follower b', abutting against the end of said grinder, and adjustable follower-rod b², mounted in said hollow shaft, and an adjusting-screw, b³, substantially as specified.

10. The combination of hollow grinder B, its revolving holder B', to which it is secured, having interiorly-threaded hub b⁷, hollow shaft B², secured to said hub, journal-sleeve B³, follower b', abutting against the end of said grinder, follower-rod b², adjusting-screw b³, and wheel or nut b⁴, for adjusting said sleeve B³, substantially as set forth.

11. The combination, with hollow revolving grinder B, of reciprocating inverted-box-form work-holder D, mounted upon a guide, D', in and covered by said sliding box-form work-holder, a rack secured to said work-holder upon the under side thereof, and a shaft journaled in said guide and having a gear meshing with said rack and inclosed between said slide and guide D', oscillating segment d⁹, gear d¹¹, and cam E, substantially as specified.

12. The combination, with hollow revolving grinder B, of reciprocating inverted-box-form work-holder D, mounted upon a guide, D', in and covered by said sliding box-form work-holder, a rack secured to said work-holder upon the under side thereof, and a shaft journaled in said guide and having a gear meshing with said rack and inclosed between said slide and guide D', oscillating segment d⁹, gear d¹¹, cam E, worm-gear f', and worm f, mounted upon a pivoted or movable shaft, substantially as specified.

13. The combination with the hollow grinder B, reciprocating work-holder D, guide D', rack d⁵, pinion d⁷, shaft d⁸, gear d¹¹, segment d⁹, cam E, worm f, worm-gear f', mounted upon a pivoted or movable shaft, spring-pawl f², catch f³, and a lug or pin, f⁴, on said worm-gear, substantially as specified.

14. The combination, with a hollow or cup-shaped emery-grinder having an inside conical end grinding-surface, of a reciprocating knife-holder, an adjustable inclined guide upon which said knife-holder reciprocates, said guide being inclined inwardly toward the axis of said grinder and parallel to the inside conical end grinding-surface of the grinder, and means for reciprocating the knife-holder, substantially as specified.

ALLEN JOHNSTON.

Witnesses:

J. T. HACKWORTH,
A. G. HARROW.