


(No Model.)

L. P. PELL.
LAMP BRACKET.

No. 377,907.

Patented Feb. 14, 1888.



Witnesses
Thos. Houghton.
Robt. P. Harris.

Inventor.
Lyman P. Pell.
By his Attorneys
Singletown & Piper.

UNITED STATES PATENT OFFICE.

LYMAN P. PELL, OF WOBURN, MASSACHUSETTS.

LAMP-BRACKET.

SPECIFICATION forming part of Letters Patent No. 377,907, dated February 14, 1888.

Application filed February 23, 1886. Serial No. 192,813. (No model.)

To all whom it may concern:

Be it known that I, LYMAN P. PELL, of Woburn, in the county of Middlesex and Commonwealth of Massachusetts, have invented a new and useful Improvement in Lamp-Brackets; and I do hereby declare the same to be described in the following specification, and represented in the accompanying drawings, of which—

10 Figure 1 is a perspective view of the device; Fig. 2, a side view with part B down; Fig. 3, a side view with part B down; Fig. 4, a top view.

15 In carrying out my invention I make the bracket in two separate parts or portions, A B, the part A, which is to be placed or hung against the wall, having in it a tapering opening, *a*, and it is also provided with two hooks or catches, *b b*, projecting from its front face, 20 as shown. The part B is formed with two ears or prongs, *c c*, which project in opposite directions from each other and at right angles, or thereabout, to the sides of the arm *d*, said arm sustaining and forming a part of the C-shaped supporter *e*, which is to receive the 25 body of the lamp.

In using the parts above described I first in-

sert in the wall or surface against which the bracket is to be supported a headed screw, *f*, the inner surface of whose head projects at 30 right angles to the surface of the shank, as represented. I then hang the part A on the screw, and as the sides of the slot or opening *a* are tapered to a point they will take firm hold of the shank of the screw. The prongs *c c* can 35 next be inserted in the hooks *b b*, as represented, the end *o* of the arm *d* resting against the face of the part A, and the bracket is then ready for use.

The supporter *e* being C-shaped, a standard 40 lamp can be readily placed therein and supported to advantage.

Having described my invention, what I claim is—

In a lamp-bracket, the part A, provided 45 with the hooks or catches *b b* and the tapering slot or opening *a*, in combination with the part B, composed of the C-shaped supporter *e*, the arm *d*, and prongs *c c*, all being arranged and for use substantially as shown and described. 50

LYMAN P. PELL.

Witnesses:

HENRY L. ANDREWS,
CHARLES D. ADAMS.