





(No Model.)

J. WOLF.  
LOCK HINGE.

No. 379,921.

Patented Mar. 20, 1888.



WITNESSES:

*W. H. Rosenbaum*  
*Martin Petry*

INVENTOR.

*Josef Wolf*  
BY *Loepke & Paegener*  
ATTORNEYS.



# UNITED STATES PATENT OFFICE.

JOSEF WOLF, OF HOBOKEN, NEW JERSEY, ASSIGNOR TO THE UNIVERSAL  
LOCK-HINGE COMPANY, OF SAME PLACE.

## LOCK-HINGE.

SPECIFICATION forming part of Letters Patent No. 379,921, dated March 20, 1888.

Application filed August 2, 1887. Serial No. 245,920. (No model.)

*To all whom it may concern:*

Be it known that I, JOSEF WOLF, of Hoboken, in the county of Hudson and State of New Jersey, have invented certain new and useful  
5 Improvements in Lock-Hinges, of which the following is a specification.

This invention has reference to an improved lock-hinge of that class by which the door is  
10 and prevented from being closed by drafts or otherwise, the hinge being specially adapted for the outer doors of buildings, car-doors, &c.; and the invention consists of the combination, with the leaves of the hinge, of a knuckle that  
15 is rigidly secured to or cast integral with one leaf of the hinge, said knuckle being provided with an inclined flange having depressions at opposite ends equidistant from the pintle, and  
20 of a spring-bolt arranged in a socket located outside of the axis of the pintle and made integral with the other leaf, the rounded-off upper end of the bolt passing along the inclined flange of the knuckle and engaging the depressions or sockets at the ends of the same,  
25 so as to hold the door in position.

In the accompanying drawings, Figure 1 represents a side elevation of my improved lock-hinge for doors in open position. Fig. 2  
30 is a vertical transverse section of the same on line *x x*, Fig. 3. Fig. 3 is a top view of Fig. 2, and Fig. 4 is a horizontal section on line *y y*, Fig. 1.

Similar letters of reference indicate corresponding parts.

35 Referring to the drawings, A and B represent the leaves of my improved hinge, which are connected in the usual manner by a pintle, A'. The leaf A is provided with a knuckle, C, that is cast integral therewith, or attached  
40 rigidly thereto, said knuckle being provided with an inclined flange, C'. At the under side of the flange C', and preferably at or near both ends of the same, are arranged depressions or sockets *a*, which are engaged by the rounded-  
45 off end of a spring-bolt, D, that is guided in a socket, D', of the leaf B, which latter is provided with a recess, *b*, of sufficient height and

width to provide for the inclined flange C' of the knuckle C. The socket D' of the spring-bolt D is located sidewise of the axis of the  
50 pintle A' and cast integral with the leaf, the axis of the socket being at the same distance from the center of the pintle as the centers of the depressions or sockets *a a* at the under side of the inclined flange C'. The upper end of  
55 the spring-bolt D is provided with an anti-friction roller, *d*, by which it moves easily along the under side of the flange C'. The spring-bolt D is forced in upward direction by a strong spiral spring which is interposed between  
60 the lower end of the same and the bottom of the socket D', as shown in Fig. 2. When the door is in open position, the spring-bolt D engages the depression *a* at the upper end of the flange C', as shown in Fig. 2, while when the  
65 door is placed in closed position it engages the depression at the lower end of the same, as shown in Fig. 4. The pressure of the spring-bolt on the flanged knuckle retains the door in  
70 open position, so that it forms thereby an effective and easily-operated lock-hinge for doors of all kinds. The depression at the upper end may be dispensed with, as the locking action  
75 is mainly required when the door is in open position, in which position the spring-bolt engages the depressions at the lower end of the inclined flange.

Having thus described my invention, I claim as new and desire to secure by Letters Patent—

The combination, with the leaves of a hinge,  
80 of a knuckle attached to one leaf and having an inclined flange, said flange having depressions at diametrically-opposite points of said flange, and a spring-bolt attached to the other  
85 leaf sidewise of the connecting-pintle, substantially as set forth.

In testimony that I claim the foregoing as my invention I have signed my name in presence of two subscribing witnesses.

JOSEF WOLF.

Witnesses:

JOHN A. STRALEY,  
MARTIN PETRY.