


(No Model.)

J. BERRY.
GRAIN CRADLE.

No. 382,024.

Patented May 1, 1888.



Witnesses.

M. H. Rumphrey.
C. C. Doyle.

Inventor,
Joshua Berry.
By his Attorneys,
C. A. Howland.

UNITED STATES PATENT OFFICE.

JOSHUA BERRY, OF JONESBOROUGH, GEORGIA, ASSIGNOR OF ONE-HALF TO
F. C. BETTS, OF SAME PLACE.

GRAIN-CRADLE.

SPECIFICATION forming part of Letters Patent No. 382,024, dated May 1, 1888.

Application filed September 29, 1887. Serial No. 251,060. (No model.)

To all whom it may concern:

Be it known that I, JOSHUA BERRY, a citizen of the United States, residing at Jonesborough, in the county of Clayton and State of Georgia, have invented new and useful Improvements in Grain-Cradles, of which the following is a specification.

My invention relates to improvements in grain-cradles; and it consists in a certain novel construction and arrangement of parts for service, fully set forth hereinafter, and specifically pointed out in the claims.

In the drawings, Figure 1 is a perspective view of the cradle. Fig. 2 is a detail section of the lower end of the snath to show the attachment of the scythe-blade thereto. Fig. 3 is a detail view of the back end of the scythe. Fig. 4 is a detail view.

Referring by letter to the drawings, A designates the snath, of the ordinary shape, provided on the under side, at the lower end, with a groove, *a*, the upper end of the said groove terminating in a depression or socket, *a'*.

B represents a nib attached to the snath.

C represents the scythe-blade, of the ordinary shape, having the tang D on the rear end, adapted to be placed in the groove in the snath. The extremity of the said tang D is bent over to form a hook to fit in the socket *a'* at the upper end of the said groove *a*.

E represents a band secured to the snath near the lower end and passing around the tang D of the blade, and F represents a wedge adapted to be driven between the said band and the outer side of the tang D, to firmly secure the latter in the groove.

G designates an upright or post secured at the lower end to the blade near its outer end or point, and H designates a similar post bolted to the blade near its inner end. The upper end of the post G is inserted in the lower arm of the socket-piece I, and a finger or top bar, K, is attached to the upper ends of the uprights G and H and inserted at the outer end in the horizontal arm of the said socket-piece. The inner end of the finger K extends beyond the upright H, and is secured at the extremity to a third upright or post, L, which is secured at its lower end to the lower end of the snath.

M designates a brace-bar extending from the

post L near the upper end to the snath near the nib, and N N designate similar braces extending from different points along the upright H to the snath, these latter being also designed to prevent the grain from slipping off the cradle at the inner end.

O O designate the fingers, extending from the post L through the post H and secured at their outer ends in the post G.

It will be seen that the construction of this cradle is very simple and strong. The lower ends of the uprights G and H are secured to the scythe by bolts or screws passed up through the latter. The advantage of the third post, L, is to strengthen the cradle and prevent the same from twisting when a heavy weight of grain falls against the point of the same. This accident is liable to happen when only two posts are used, for the reason that there is not substantial attachment to the snath of the inner ends of the fingers.

The construction herein shown and described allows of a very secure bracing of the parts, and as the same may be accomplished without materially adding to the weight, the result is an improvement.

The manner herein described of attaching the scythe to the snath is very simple, the connection is easily made, and there is little liability of the parts becoming detached. The band being secured around the lower end of the snath prevents the same from splitting, and when the wedge is driven in between the band and the outer side of the tang on the scythe the said scythe is very securely attached to the snath.

The socket-piece, I, herein described is in the form of an angle, having a horizontal and a vertical arm, each of which forms a socket, in which the end of one of the bars of the frame may be inserted. The said socket-piece is placed at the upper outer corner of the said frame, and the ends of the upright G and the top finger, K, are inserted therein, and thus they are bound securely together. The said joint between the upright and the finger is much more secure than it could be if simply bolts were used. The bars are prevented from splitting at the same time that they are bound together.

The cradle as herein described is composed of wood, preferably, and therefore, although

there are a few more parts comprising it than in other frames, (which are constructed without the additional or third standard or upright,) the weight is in reality less. Being
 5 constructed of wood and in the manner described, the frame is given a rebounding flexible action which iron or metallic cradles lack. This is an advantage, from the fact that a sudden strain on any part of the cradle does not
 10 strain the same, but it yields and then returns to its first shape immediately.

It will be seen that the ends of the braces N are inserted at their upper ends in apertures in the upright H and at their lower ends in
 15 apertures in the snath. The brace M is similarly attached to the upright L and the snath. This construction obviates the necessity of using any supplemental means of attachment. The lower ends of the braces might be at-
 20 tached to a separate bar which is secured to the snath; but this is objectionable, as it adds weight and renders the cradle clumsy to handle. It also adds to the cost of manufacture. It will be seen, therefore, that it is far prefer-
 25 able to attach the ends of the said braces directly to the parts which they are intended to brace, as shown and described herein.

The fingers O pass through the upright H, and there is much less danger of their being
 30 broken when this method of construction is followed.

Having thus described the construction and arrangement of my invention, I claim—

1. The combination, with the snath and the
 35 scythe attached thereto, of the uprights G and H, secured at their lower ends to the scythe respectively near its outer and inner ends, the socket-piece I, having its vertical arm ar-
 40 ranged on the upper end of the upright G, the top finger, K, secured to the upper end of the

upright H and inserted at its outer end in the horizontal arm of the socket-piece, the said finger being extended inward beyond the up-
 right H, the upright L, secured to the lower end of the snath and attached at its upper end
 45 to the inner end of the finger K, the fingers O, secured at their inner ends in the upright L and at their outer ends in the upright G, and passing at their intermediate points through
 50 the upright H, the brace M, extending from the upper end of the upright L to the snath, and the braces N, extending from intermediate points of the upright H to the snath, substan-
 tially as specified.

2. In a grain cradle, the combination of the
 55 snath and the scythe secured thereto, the outer and inner uprights, G and H, secured at their lower ends to the scythe, the top finger, K, connecting the upper ends of the said uprights
 60 and extending inward beyond the inner upright, the upright L, attached at its lower end to the snath, and having an aperture in its up-
 per end to receive the inner end of the finger K, the fingers O, passing through the upright
 65 H at intermediate points of its length and secured at their ends, respectively, to the uprights G and L, the brace M, inserted at its ends in apertures in the upright L and the snath, and
 the braces N, inserted at their ends in aper-
 70 tures at intermediate points of the upright H and the snath, substantially as and for the pur-
 pose hereinbefore specified.

In testimony that I claim the foregoing as my own I have hereto affixed my signature in pres-
 ence of two witnesses.

JOSHUA BERRY.

Witnesses:

J. J. HANES,

GEO. S. HANES.