



(No Model.)

A. PETERSON.
LOCK FOR BAGS OR SATCHELS.

No. 382,728.

Patented May 15, 1888.



Witnesses.
J. Paul Mayer.
Wm. H. Ranney

Inventor
Albert Peterson.
by Adolph Barthel.
Attorney

UNITED STATES PATENT OFFICE.

ALBERT PETERSON, OF DETROIT, MICHIGAN.

LOCK FOR BAGS OR SATCHELS.

SPECIFICATION forming part of Letters Patent No. 382,728, dated May 15, 1888.

Application filed May 13, 1887. Renewed February 27, 1888. Serial No. 265,433. (No model.)

To all whom it may concern:

Be it known that I, ALBERT PETERSON, a resident of Detroit, in the county of Wayne and State of Michigan, have invented new and useful Improvements in Locks for Bags or Satchels; and I hereby declare that the following is a full, clear, and exact description thereof, reference being had to the accompanying drawings, which form a part of this specification.

This invention relates to new and useful improvements in locks for traveling-bags or satchels; and the invention consists in the peculiar construction, arrangement, and combination of parts.

Figure 1 is a section through one corner of a traveling-bag or satchel to which my improved lock is applied. Fig. 2 is a detached perspective view of the lock with the co-operating parts of the satchel.

In the drawings, A and B are the metallic bows of a satchel, and C are two like corner-locks arranged to prevent the satchel from spreading open at the corners.

The construction of these locks is as follows: To the face of the outer bow is secured the corner metal plate, *a*, of any desired plain or ornamental form. Within a slot of this plate is pivotally secured a locking-lever, *b*, the arm *c* of which lever rests on the top of the plate, while the other arm projects below and forms the hook *d*. The arm *c* preferably forms a complementary part of the plate *a*, so as to deceive the eye of the uninitiated about the nature of the device, the whole appearing to be merely a corner-plate when closed. To the inner bow of the satchel is secured a suitable catch, *e*, to engage with the hook *d*. A spring, *f*, is suitably arranged to keep the locking-lever either in its open or closed position.

In practice the raising of the arms *c* of the locking-levers disengages the hooks *d* from the

catches *e* and permits the satchel to be opened, while the reverse movement locks the satchel at the corners.

While I have described and shown my lock as a corner-lock for bags or satchels, I want it distinctly understood that I do not intend to limit myself to such use alone, but as a lock for satchels, bags, purses, &c., in the place of the ordinary locks or clasps as well, in which case the plate *a* assumes the form of the bows at the place to which it is applied.

I do not claim, broadly, a lock for bags, satchels, and the like, consisting of a plate and a spring-actuated lever pivoted thereto, for I am aware that such is not new with me. I deem it important that the outer arm of the lever be formed complementary to the plate, thus making a neat appearance and disguising the presence of a lock or fastening.

What I claim as my invention is—

1. In a lock for bags, satchels, or purses, the combination of a plate secured to the outer bow and a locking-lever pivotally secured between its ends in a slot therein, and having an outer arm formed complementary to the said plate and an inner arm constructed to engage a catch, substantially as and for the purpose described.

2. In a corner-lock for traveling-bags or satchels, a curved corner-plate secured to the face of the outer bow, a locking-lever pivotally secured between its ends in a slot therein and provided with an outer arm formed complementary to said plate and an inner arm forming a hook, and a catch formed on the inner bow, all arranged to operate substantially as described.

ALBERT PETERSON.

Witnesses:

J. PAUL MAYER,
WM. H. RANNEY.