




(No Model.)

2 Sheets—Sheet 1.

J. J. REICHENBACH.  
DISPLAY FRAME.

No. 384,334.

Patented June 12, 1888.



Witnesses.

*G. P. Hoyer*

*C. E. Doyle*

Inventor,

*Jacob J. Reichenbach.*

By *J. J. Reichenbach*'s Attorneys.

*C. H. Snow & Co.*

(No Model.)

2 Sheets—Sheet 2.


J. J. REICHENBACH.

DISPLAY FRAME.


No. 384,334.

Patented June 12, 1888.


Page 5.



9674



784



Witnesses.

Geo. J. Pope,  
C. E. Doyle.

Inventor,

*Jacob J. Reichenbach.*

By *K* & Attorneys.

C. A. Howes



# UNITED STATES PATENT OFFICE.

JACOB J. REICHENBACH, OF CENTRALIA, ILLINOIS.

## DISPLAY-FRAME.

SPECIFICATION forming part of Letters Patent No. 384,334, dated June 12, 1888.

Application filed April 14, 1888. Serial No. 270,603. (No model.)

*To all whom it may concern:*

Be it known that I, JACOB J. REICHENBACH, a citizen of the United States, residing at Centralia, in the county of Marion and State of Illinois, have invented a new and useful Improvement in Display-Frames, of which the following is a specification.

My invention relates to improvements in display-frames, such as are employed in stores to support articles of wearing-apparel, &c., which are offered for sale, and it has special reference to frames which are adapted to display shoes and like articles of foot-wear.

The object of the invention is to provide a rest which is simple, strong, and cheap, and will hold the shoe firmly in a position to display its merits.

The invention consists in a certain novel construction and arrangement of devices, fully set forth hereinafter in connection with the accompanying drawings, wherein—

Figure 1 is a plan view of the improved rest. Fig. 2 is a side view of the same. Fig. 3 is a front view of the display-frame. Fig. 4 is a side view of the same. Fig. 5 is a plan view of the rest and devices for attaching it to the frame. Fig. 6 is a detail view of the collar.

Referring by letter to the drawings, the shoe-rest *a* is provided with a flat bearing-surface for the sole and heel, and it is preferably made of wire bent approximately to the shape of the shoe. One length of wire composes the outer frame, *b*, the rear ends of which terminate in spring-arms *c c*, which are provided with up-turned jaws *d d*. The rear ends of these arms are separated a short distance and the jaws are bent inward slightly to enable them to engage the heel of the shoe firmly. The inner frame, *e*, is arranged between the sides of the outer frame, and it consists of the heel-loop *f*, the slot or socket *g*, which is located at the narrowest portion of the rest, and the forward-extending spring-arms *h h*, which consist of the converging portions *i* and the lateral extensions *k*. The ends of the spring-arms are provided with inwardly-bent jaws *l l*, which engage the soles of the shoe. The sides of the loop at its front end and the rear ends of the spring-arms *h* are secured rigidly to the sides of the outside frame at the points *m* and *n*, re-

spectively, by means of metal clips, fine wire wrapping, or solder, and the portions of the inner frame in front of the fastenings *n* constitute the spring-arms *h*, and the portions of the outer frame in rear of the fastenings *m* constitute the spring-arms *c c*. The portions of the sides of the inner frame between the fastenings *m* and *n* are drawn together and secured by the fastenings *o o*, and the portions of the sides between the fastenings *o o* are separated slightly to form the slot or socket *g*, above referred to.

It will be seen that the rest consists of two pieces of wire, the outer frame comprising, essentially, a sole-loop and heel-springs, and the inner frame comprising, essentially, a heel-loop, which is located between the heel-springs, and the toe or sole springs, which extend outside of the sole-loop.

The display-frame *A* consists of the vertical standard *B*, having a horizontal sleeve, *C*, at its upper end, provided with a set-screw, *D*, and the movable or adjustable frame *E*, comprising the vertical and horizontal rods *F* and *G*, respectively. One of the horizontal rods is mounted in the sleeve *C*, and the frame is clamped at any desired inclination by the set-screw *D*, above mentioned.

The horizontal rods are secured to the vertical rods by means of the brackets *M*, which consist of the tubes *N*, embracing the vertical rods and having set screws in their sides to impinge against the rods and hold at the desired point, and the hooks *P* on the sides of the said tubes and having set-screws mounted therein. The horizontal rods are arranged in the hooks, and the set-screws clamp them therein.

It will be seen that the horizontal rods may be arranged at any desired points of the vertical rods to suit the character of the stock to be displayed, it being at times desirable to have the rods arranged at a considerable distance apart, while at other times it is of advantage to arrange them close together.

*H* represents a collar, which is adapted to be mounted on one of the rods of the frame, (either vertical or horizontal,) and it is provided with a set-screw, *I*; and *K* represents a thumb-screw, which passes through the slot or socket *g* in the shoe-rest and engages a tapped aperture in a boss, *L*, which is formed on the side



of the said collar. The rest is capable of rotary adjustment around the thumb-screw K, in order to enable the shoe to be arranged in any desired position to display its merits.

5 Having thus described my invention, I claim—

1. In a shoe-rest, the combination of the outer frame, *b*, open at its rear end and terminating in spring-arms *c*, and the inner frame, 10 *e*, open at its front end and terminating in the spring-arms *h*, substantially as and for the purpose specified.

2. The within-described shoe-rest, comprising the outer frame, *b*, forming the sole-rest, 15 and the heel-springs *c c*, provided with the jaws *d d*, and the inner frame, *e*, secured to the outer frame and comprising the heel-loop *f*, the forward-extending spring-arms *h h*, having the jaws *l l*, and the intermediate loop or 20 socket to enable the rest to be attached to a frame, substantially as and for the purpose specified.

3. The combination, with the display-frame having the standard B, provided on its upper 25 end with a horizontal sleeve, C, and the frame having horizontal rods G, one of which is mounted in the said sleeve and locked firmly

in position by a set-screw, of the collars adjustably mounted on the horizontal bars and having tapped apertures in their sides, the 30 shoe-rests comprising the outer frames, *b*, having spring-arms at their rear ends, and the inner frames having heel-loops, forward-extending spring-arms, and loops or sockets between the same, and the set-screws mounted in the 35 tapped apertures in the collars and engaging the slots or sockets in the shoe-rests, substantially as and for the purpose specified.

4. The herein-described shoe-rest, comprising the two frames *b e*, one arranged within 40 the other, each frame having a closed and an open end and each having spring arms or jaws at the open ends, the spring arms or jaws of one frame engaging and sliding upon the other frame, as set forth. 45

In testimony that I claim the foregoing as my own I have hereto affixed my signature in presence of witnesses.

JACOB J. REICHENBACH.

Witnesses:

L. F. CASEY,  
S. L. DWIGHT,  
F. SCHINDLER, Jr.