


(No Model.)

A. S. MANN.
CORSET LACING.

No. 386,642.

Patented July 24, 1888.



Attest.
P. H. Henshaw
A. S. Smith.

Inventor.
Abram S. Mann,
per R. J. Osgood,
Atty.

UNITED STATES PATENT OFFICE.

ABRAM S. MANN, OF ROCHESTER, NEW YORK.

CORSET-LACING.

SPECIFICATION forming part of Letters Patent No. 386,642, dated July 24, 1888.

Application filed July 19, 1886. Serial No. 208,506. (No model.)

To all whom it may concern:

Be it known that I, ABRAM S. MANN, of Rochester, in the county of Monroe and State of New York, have invented a new and useful
5 Improvement in Lacings; and I do hereby declare that the following is a full, clear, and exact description of the same, reference being had to the accompanying drawings.

My invention relates to lacings for corsets
10 or other articles of wearing apparel, and it is of that kind where the lacing-cord passes alternately from side to side around bearings or holders, the ends being drawn up by the wearer to close the sides of the garment. I use a single
15 or continuous lacing-cord, and form and arrange the parts in such manner as to allow the two ends of the cord to come out together at one side of the garment, to be taken hold of for the purpose of tightening.

20 Referring to the drawings, Figure 1 is a side elevation of the two meeting edges of a garment—for instance, a corset—showing my improved form and manner of lacing; and Fig. 2, an enlarged cross-section on line *xx* of Fig. 1.

25 Referring to the parts shown in the drawings, *A A* indicate the opposing edges of the corset to be drawn together by the lacing-cord *B*.

C C are the bearings for the cord, secured to
30 the edges of the corset. I form one side of the corset with a marginal longitudinal channel, *b*, and the other side with a similar marginal channel, *c*, in each of which channels I place rollers *d*, to receive and hold the cord.
35 These rollers constitute spacers for the respective walls of the channels *b c*, to hold said walls asunder, and they are formed with peripheral grooves, and are mounted upon axial pins *e*, which pierce the walls *f* of the channels, and
40 external plates, *g*, to which latter said pins are secured by being riveted or otherwise. The rollers in the two sides of the corsets are alternated, so that the cord, when carried around them, follows a zigzag course.

45 In addition to the channel *c*, the right-hand side of the corset is formed with a narrow inner channel, *a*, adjacent to and parallel with the channel *c*, formed for the purpose of re-

turning the end of the string to the place of starting after it has been carried around the 50 rollers, as shown.

The cord is in one continuous piece, and after being carried upward, for instance, by being threaded around the rollers in succession the upper end is returned through the 55 channel *a* to the lower end of the corset to join the lower end of the cord. The loose part of the cord occupying the channel *a* is confined and protected, and being thus covered it is not liable to be caught and pulled to one side or out 60 of place by other parts of the clothing or by other means.

The rollers are covered from view by the walls of the channels, and the cord when passed around them, as stated, is carried fully into the 65 respective channels *b* and *c*, the bends being out of sight on account of said walls.

The portion of the corset appearing at the right in Fig. 1 is provided near its upper end with a roller or sheave, *h*, placed out of line 70 with the rollers in the channel *c*, it being so placed as to overhang the space within said channel or sheath, so that the string or cord will be carried substantially centrally down the channel. 75

It is known that single cords have been used in lacings—for shoes, for instance—but the advantages possessed by my invention I am not aware have heretofore been obtained.

What I claim as my invention, and desire to 80 secure by Letters Patent, is—

The herein-described device for lacing, comprising a garment having rollers *d* on its meeting edges, and a side channel, *a*, a separate roller, *h*, in a different vertical line from that 85 of said rollers *d*, and in line with said side channel, and a cord passing over said rollers *d* and said separate roller *h* and down said channel, substantially as shown.

In witness whereof I have hereunto signed 90 my name in the presence of two subscribing witnesses.

ABRAM S. MANN.

Witnesses:

R. F. OSGOOD,
P. A. COSTICH.