

(No Model.)

C. F. PERRY.
CUFF HOLDER.

No. 389,973.

Patented Sept. 25, 1888.

Fig. 1.




Fig. 2.





Fig. 3.



WITNESSES:
John H. Deamer
C. Sedgwick

INVENTOR:
C. F. Perry
BY *Mum & Co*
ATTORNEYS.

UNITED STATES PATENT OFFICE.

CHARLES F. PERRY, OF AUGUSTA, MAINE.

CUFF-HOLDER.

SPECIFICATION forming part of Letters Patent No. 389,973, dated September 25, 1888.

Application filed July 12, 1888. Serial No. 279,724. (No model.)

To all whom it may concern:

Be it known that I, CHARLES F. PERRY, of Augusta, in the county of Kennebec and State of Maine, have invented a new and Improved Cuff-Holder, of which the following is a full, clear, and exact description.

The object of my invention is to provide a cheap and practical cuff holder, designed more particularly for ladies' use, the main outer member of this device being adapted to be passed through a loop fastened upon the interior of the sleeve.

The invention consists of the special construction of the holder, all as hereinafter described and claimed.

Reference is to be had to the accompanying drawings, forming a part of this specification, in which similar letters of reference indicate corresponding parts in all the figures.

Figure 1 is a perspective view showing the application of my new and improved cuff-holder. Fig. 2 is an enlarged perspective view of the holder, and Fig. 3 is an enlarged perspective view of the loop to be attached to the sleeve.

The cuff holder A is made of a single strip of sheet metal bent upon itself to form the inner member, *a*, outer member, *b*, intermediate loop, *c*, and the two outer loops, *d e*. The member *b* projects beyond the member *a*, and it is curved near the loop *e* to form the spring *f*, which, together with the adjacent surface of the intermediate loop, *c*, forms a clasp to retain the loop B, as illustrated in Fig. 1. The

loop B is made of wire or any suitable material, and is secured to the interior of the sleeve C in proper position so that the member *b* may be passed through it, and when so passed through will hold the cuff D at proper position.

The holder is applied to the cuff by passing the inner member, *a*, through the button-holes of the cuff, the holes being held with more or less spring action at the fold of the intermediate loop, *c*. The member *b*, having been passed through the loop B until the latter passes spring *f* into the loop *e*, will retain the cuff firmly in place without inconvenience and without materially soiling the cuff.

Having thus fully described my invention, I claim as new and desire to secure by Letters Patent—

1. The holder formed with the inner member, *a*, outer member, *b*, and intermediate fold, *c*, in combination with the loop B, secured to the sleeve of the garment, substantially as described.

2. The cuff-holder formed with the inner member, *a*, outer member, *b*, and intermediate fold, *c*, forming the loops *d e*, the outer member, *b*, being bent to form the spring *f*, in combination with loop B, secured to the sleeve of the garment, substantially as described.

CHARLES F. PERRY.

Witnesses:

J. H. COGAN,
H. L. COCHRANE.