




(No Model.)

E. P. HASBROUCK.
MATCH SAFE.

No. 410,588.

Patented Sept. 10, 1889.



Witnesses

N. P. Denison,

J. P. Denison.

Eli Perry Hasbrouck Inventor

By his Attorneys

Smith & Denison

UNITED STATES PATENT OFFICE.

ELI PERRY HASBROUCK, OF SYRACUSE, NEW YORK.

MATCH-SAFE.

SPECIFICATION forming part of Letters Patent No. 410,588, dated September 10, 1889.

Application filed April 11, 1889. Serial No. 306,762. (No model.)

To all whom it may concern:

Be it known that I, ELI PERRY HASBROUCK, of Syracuse, county of Onondaga, in the State of New York, a citizen of the United States, have invented certain new and useful Improvements in Match-Safes, of which the following is a specification, reference being had to the accompanying drawings.

My invention relates to the construction of match-safes which comprise the combination, with a match-holder, of a receptacle for burned matches, which receptacle is adapted to extinguish the burning match dropped or placed into it.

The object of my invention is to produce such a match-safe consisting of a match-holder and means for extinguishing burning matches and holding the burned and extinguished match-stick.

My invention consists in the combination, with a match-holder, of a receiver for burning matches adapted to extinguish the flame and spark almost instantaneously after it is placed in the receptacle, the body of the receptacle being integral with the match-holder or detached therefrom.

Figure 1 is a side elevation. Fig. 2 is a top plan view. Fig. 3 is a side elevation of the cap detached.

It is constructed as follows: When the match-holder and extinguishing-receiver are in one piece integral with each other, A is the body, comprising a metallic box divided into two compartments by the partition 1, of which B is the match-holder, and C constitutes the lower part of the burned-match receiver or re-

ceptacle. The compartment B is provided with a hinged cover to close the top. Upon the top of the compartment C, I place the raised or arching cover, (shown in the drawings as provided with an opening 4 upon the top thereof,) and this cover and the compartment C comprise the receptacle for the burning and burned matches.

Any ordinary means for suspending this article may be employed.

It will be observed that when a burning match is placed or dropped or inserted through the opening 4 into the cap or cover the confinement will at once cause the flame to go out, and the spark or a hot coal upon a match-stick will at once be extinguished. The safety as well as the convenience of the extinguisher will be perfectly apparent.

To empty the receptacle, I simply remove the cap or cover and turn out the matches or what may remain, holding the cover of the match-holder closed.

What I claim is—

A match-safe and burning-match extinguisher comprising a body, a central partition across the body, a hinged cover upon the match-receiver, and a detachable cover upon the extinguisher, provided with an opening to receive the burning match.

In witness whereof I have hereunto set my hand this 6th day of April, 1889.

ELI PERRY HASBROUCK.

In presence of—

C. W. SMITH,
H. P. DENISON.