



(No Model.)

M. SHAEFFER.
CAKE GRIDDLE.

No. 411,619.

Patented Sept. 24, 1889.



Witnesses

Ed. S. Law
Ed. S. Smith

Inventor
William Shaeffer
By *Bond & Wise*

Attorneys

UNITED STATES PATENT OFFICE.

MILTON SHAEFFER, OF CANTON, OHIO, ASSIGNOR TO BARBARA SHAEFFER,
OF SAME PLACE.

CAKE-GRIDDLE.

SPECIFICATION forming part of Letters Patent No. 411,619, dated September 24, 1889.

Application filed June 5, 1889. Serial No. 313,236. (No model.)

To all whom it may concern:

Be it known that I, MILTON SHAEFFER, a citizen of the United States, residing at Canton, in the county of Stark and State of Ohio, have
5 invented certain new and useful Improvements in Cake-Griddles; and I do hereby declare that the following is a full, clear, and exact description of the same, reference being
10 had to the annexed drawings, making a part of this specification, and to the letters and figures of reference marked thereon, in which—

Figure 1 is an isometrical view showing the griddle open. Fig. 2 is a detached view of the handle, showing the manner of attaching the same.
15

The present invention has relation to cake-griddles; and it consists in the different parts and combination of parts hereinafter described, and particularly pointed out in the
20 claim.

Similar letters of reference indicate corresponding parts in each figure of the drawings.

In the accompanying drawings, A and B represent the griddle-sections, which are
25 hinged together by means of the hinges *a*. The griddle-section A is formed flat and smooth upon its top or upper side, and, as shown, is provided at its ends with the handles *b* and the studs *c*, which handles and studs
30 are formed integral. The section B is provided with cake-cups *d*. In the drawings three cups are shown; but it will be understood that a greater or less number may be used, if desired.

35 For the purpose of providing a means to prevent the grease from dripping the flanges *d'* are provided, which flanges are located substantially as shown in the drawings, and, as shown, are located upon the hinged side

of the section B. For the purpose of preventing the flanges *d'* from striking the cakes when the section B is turned over on top of the section A, said flanges are set a short distance away from the peripheries of the cake-cups *d*.
40

For the purpose of supporting the section B at the required height, the studs *c* are provided, and are so located that the section B will strike the top or upper ends of the studs *c* when the section B is turned over section
45 A. It will also be seen that the flanges *d'* will act as guides for the cakes, thereby preventing the cakes from lapping one over the other as they are conveyed from the section B to the section A.
50

For the purpose of providing a means of operating the section B the handle C is provided, which handle is attached to the section B by means of the arms *a'* and the spring-arms *a''*.
55

The spring-arms are provided with the right-angled portions *b''*, which enter apertures in the arms *a'*, as illustrated in Fig. 2.
60

Having fully described my invention, what I claim as new, and desire to secure by Letters
65 Patent, is—

The combination of the hinged sections A and B, the section A provided with the handles *b* and the studs *c*, the section B provided with the cake-cups *d* and the guide-flanges *d'*, substantially as and for the purpose specified.
70

In testimony that I claim the above I have hereunto subscribed my name in the presence of two witnesses.

MILTON SHAEFFER.

Witnesses:

E. A. C. SMITH,
F. W. BOND.