


(No Model.)

L. D. BALFOUR.  
HAMMER.

No. 411,633.

Patented Sept. 24, 1889.



Witnesses

H. C. Newman,  
Louis B. Fulkner

Inventor

L. D. Balfour,

By his Attorneys

Baldwin, Davidson & Wright.



# UNITED STATES PATENT OFFICE.

LORENZO D. BALFOUR, OF CARTHAGE, MISSOURI.

## HAMMER.

SPECIFICATION forming part of Letters Patent No. 411,633, dated September 24, 1889.

Application filed February 23, 1889. Serial No. 300,890. (No model.)

*To all whom it may concern:*

Be it known that I, LORENZO D. BALFOUR, a citizen of the United States, residing at Carthage, in the county of Jasper and State of Missouri, have invented certain new and useful Improvements in Hammers, of which the following is a specification.

The object of my invention is to provide a hammer adapted to carry a tack, nail, or other similar attaching device, and to place it in position ready to be driven into any desired object.

My invention is especially designed for attaching advertisements to a wall, fence, or board and for attaching canvas, paper, cloth, or other material to ceilings.

In the accompanying drawings, Figure 1 is a view showing my improved hammer and its handle with the tacks in position in their seats, and showing also the manner of attaching an advertisement by the use of my improved hammer. Fig. 2 is a perspective view of one form of my improved hammer in which the head is cylindrical. Fig. 3 is a perspective view of a hammer having a square head with my improvements applied.

As shown in Fig. 2, the hammer-head A is made cylindrical and mounted on the end of a handle B. In the upper end of the hammer-head are formed one or more—preferably several, as shown—T-shaped recesses *a* for holding tacks or nails.

As shown in Fig. 2, several recesses are formed in the hammer-head at equal distances apart and at equal distances from the handle of the hammer. On the upper face of the hammer-head the recesses are made of sufficient length and breadth to accommodate the head of the tack, nail, or similar device. This part of the recess is marked 1 in the drawings. The part 1 of the recess connects with the upper portion 2 in the side of the head. The part 1 of the recess *a* extends below the end of the part 2 of the recess and is of the same width all the way down, so that when the tack or nail is inserted in the recess the head will extend down into the part 1 of the recess, while the shank extends through the part 2. The part 2 of the recess tapers from its upper end downwardly, so that the shank

of the tack or nail will be clamped and held in position when inserted. When a small tack or nail is used, the shank next to the head will rest on the end wall of the recess 2 and the head will lie in the recess 1 and extend into said recess below the end wall of the recess 2, so that the tack is held straight and may be more readily placed in position to be driven home.

I have shown the recesses formed so as to hold the tacks or nails both vertically and horizontally. When the tacks or nails are held vertically, they are in position to be driven into a ceiling. When they are held horizontally, they are in position to be driven into a side wall.

At *b* I have shown the recess 1 for the head of the tack or nail in the side of the hammer-head, the recess 2 extending to the top. At *a* the recess 1 is formed in the top of the hammer-head and the recess 2 extends along the side. Similar recesses are formed in the bottom or end of the hammer-head, as shown.

By means of a long handle, as shown in Fig. 1, the tacks may be elevated to the desired position, may be inserted in place, and then the hammer may be withdrawn from the tack and used to drive it in.

In hanging up advertisements the card may be attached to the tack, and then the tack and advertisement elevated by the hammer to the desired object, and then the tack may be firmly driven in. The card may then be attached more firmly by additional tacks, which may be inserted and driven in afterward.

Having thus described my invention, what I claim as new, and desire to procure by Letters Patent of the United States, is—

1. The combination, substantially as hereinbefore set forth, of the handle and the hammer-head secured to the end of the handle and formed with T-shaped recesses consisting of parts 1 and 2 to hold a tack or nail, the part 1 of said recess being adapted to receive the head of the tack or nail and the part 2 to receive the shank near the head, some of said recesses being formed with the part 1 in the top of the hammer-head and one or more of said recesses being formed with

the part 1 in the side of the hammer-head, whereby tacks or nails may be held for insertion both vertically and horizontally.

2. The combination, substantially as here-  
5 inbefore set forth, of the hammer-handle, and the square hammer-head secured to the end of the handle and having T-shaped recesses formed in the upper edge to hold tacks, nails,

or similar attaching devices both vertically and horizontally. 10

In testimony whereof I have hereunto subscribed my name.

LORENZO D. BALFOUR.

Witnesses:

W. T. GREEN,

J. M. STEVENSON.