


(No Model.)

W. DRISCOLL.  
MEASURING ROD.

No. 413,930.

Patented Oct. 29, 1889.



Witnesses

*Geo. C. French.*

*R. W. Bishop.*

Inventor

*William Driscoll.*

By his Attorneys

*C. A. Snow & Co.*



# UNITED STATES PATENT OFFICE.

WILLIAM DRISCOLL, OF BROCKVILLE, ONTARIO, ASSIGNOR TO JAMES H. CONNOR, OF OTTAWA, CANADA.

## MEASURING-ROD.

SPECIFICATION forming part of Letters Patent No. 413,930, dated October 29, 1889.

Application filed January 30, 1889. Serial No. 298,093. (No model.) Patented in Canada December 17, 1888, No. 30,420.

*To all whom it may concern:*

Be it known that I, WILLIAM DRISCOLL, residing at Brockville, in the county of Leeds and Province of Ontario, Canada, have invented new and useful Improvements in Measuring-Rods, (for which I have been granted Canadian Patent No. 30,420, December 17, 1888,) of which the following is a specification.

10 My invention relates to improvements in measuring-rods; and it consists in certain novel features hereinafter described and claimed.

15 In the accompanying drawings, Figure 1 is an elevation of my complete device extended. Fig. 2 is an edge view of the same. Figs. 3 and 4 are views of the device folded, taken at right angles to each other. Fig. 5 is a detail view of the arm designed for use in measuring horses.

20 Referring to the drawings by letter, A designates the measuring-rod, consisting of the central or main section B and the end sections C D. The central section B is provided with the longitudinal slots E, and has at its center the trammel-point F, which is secured permanently in the said section in any desired manner. The end sections C D are provided with longitudinal slots G, through 25 which pass the bolts H, which are permanently secured in the ends of the central section B, and are provided on their extremities with the thumb-nuts and washers I J, which are adapted to bind against the sides of the end sections, so as to clamp the same to the central section at any desired point.

30 K designates screws or bolts, which are inserted through the slots E of the central section, and are secured permanently in the ends of the end sections. These bolts aid in guiding the end sections in their movements on the main section and holding the sections together.

45 L designates an arm, which is provided at one end with a bracket M, having dowel-pins N engaging the longitudinal slots G of the end section C, so as to guide the said bracket and arm when being adjusted upon the end section in adjusting the device. This bracket 50 also carries a bolt O, which passes through

the slot of the end section and is provided with a thumb-nut P, which is adapted to be turned home against the end section, so as to secure the said arm and bracket at the desired point. The bracket and the arm L can 55 be readily removed when not in use, so that the device will occupy but little room. The bracket is provided on one side with a plummet Q, so as to indicate when the said arm is level. 60

The several sections of the measuring-bar are provided or marked with the scale of lineal measure, so that the length or other dimension of the object being measured can be readily seen. The end section D is also provided in its end with a trammel marker or pencil, so that by reason of the said marker and the trammel-point F the device may be used to describe circles. 65

My device is intended for use in measuring 70 heights of objects or in measuring widths of door and window openings and similar purposes, and the desired measurement is ascertained by adjusting the several sections upon each other until the entire length of the rod is equal to the dimension desired, when the thumb-nuts are tightened, so as to hold the sections together until the measurement can be noted, which is done by reading the scale marked on the sections, as will be readily understood. 75 80

The arm L is intended more especially for use in measuring horses, and in use the end section carrying the said arm is adjusted so as to bring the said arm upon the back of the horse, and when the plummet indicates that the said arm is level the sections are secured together and the height of the horse will be indicated. 85

Having thus described my invention, what I claim, and desire to secure by Letters Patent, is— 90

1. A measuring-rod comprising the sections B C D, the central section B having the longitudinal slots E, and the end sections C D 95 having the longitudinal slots G, the bolts H, secured in the ends of section B and passing through the slots G in the sections C D, the nuts and washers on the ends of said bolts, and the bolts K, inserted through the slots E 100

in the central section B and into the inner ends of the sections C D, as set forth.

2. The combination of the central section B, the end sections C D, secured thereto and  
5 longitudinally adjustable thereon, and the arm L, secured to and projecting laterally from the section C and adjustable along the same, as set forth.

3. The combination of the central section  
10 B, the end sections C D, having the longitudinal slots G and adjustably secured to the central section, and the arm L, adjustably secured to the section C and provided with a bracket M, having pins N, engaging the slot  
15 G, as set forth.

4. The combination of the central section, the end sections adjustably secured thereto, the arm L, having a bracket at one end ad-

justably secured to one of the end sections, and the plummet pivoted to said bracket, as  
20 set forth.

5. The combination of the central section, the end sections adjustably secured thereto, the arm L, having a bracket at one end, the plummet pivoted to said bracket, and the bolt  
25 passing through said bracket and one of the end sections to adjustably secure the arm to said section, as set forth.

In testimony that I claim the foregoing as my own I have hereto affixed my signature  
30 in presence of two witnesses.

WILLIAM DRISCOLL.

Witnesses:

EDMUND F. BURRITT,  
D. J. HURLEAN.