

(No Model.)

L. N. DE LONGE.
ADJUSTABLE DRUM CLAMP.

No. 422,742.

Patented Mar. 4, 1890.

Fig 1.




Fig 2.




Fig 3.





Fig 4.



Witnesses:

R. A. Balderson

A. C. Johnson

Inventor:

Louis N. DeLonge

By His Attorneys,

Nigdon & Nigdon

UNITED STATES PATENT OFFICE.

LOUIS N. DE LONGÉ, OF KANSAS CITY, MISSOURI.

ADJUSTABLE DRUM-CLAMP.

SPECIFICATION forming part of Letters Patent No. 422,742, dated March 4, 1890.

Application filed October 11, 1889. Serial No. 326,688. (No model.)

To all whom it may concern:

Be it known that I, LOUIS N. DE LONGÉ, of Kansas City, Jackson county, Missouri, have invented certain new and useful Improve-
5 ments in Adjustable Drum-Clamps, of which the following is a full, clear, and exact description, reference being had to the accompanying drawings, forming a part hereof.

My invention relates to improvements in
10 adjustable drum-clamps; and it consists in the novel construction, combination, and arrangement of parts, as will be fully hereinafter described, and pointed out in the claims.

In the accompanying drawings, forming a
15 part of this specification, Figure 1 is a perspective view of a drum with my improved clamp in position thereon. Fig. 2 is a side elevation of the clamp detached. Fig. 3 is a detail perspective view of the hook-shaped
20 portion forming the outer end of the clamp; and Fig. 4 is a perspective view of a portion of one of the hoops of a drum, showing the notches for the reception of the clamp.

In the drawings, C represents a rod having
25 at one end a screw-thread *c* and at its other end a thumb-piece E, provided with the usual ears *e*. This thumb-piece is rigidly secured to rod C.

The clamping-section B has an internal
30 screw-thread *d*, extending nearly its entire length and adapted to engage the threaded portion *c* of rod C. A right-angled hook-shaped projection *b* is formed integral with the main part of the clamping-section and at
35 the opposite end to that in which the hole *d* is located. The portion of the clamp which is formed at right angles to the main part is preferably of rectangular shape, in order that it may fit in recesses *a'* in the outer edges of

hoops *a*. These recesses are not necessary to
the use of the clamp; but I prefer to employ
them.

The clamping-section B' is similar to the
one just described, with the exception that
the bore extends its entire length and has no
45 thread, it being designed to fit loosely upon
rod C.

The advantages of my invention will be read-
ily understood. The clamp is placed upon
the drum in such a manner that each of the
50 sections B B' engages one of the clamping-
hoops. The rod C is then tightened by means
of thumb-piece E. The use of this thumb-
piece obviates the necessity of carrying
wrenches, &c., and thereby forms a clamp
55 which is convenient at all times and can be
adjusted as desired.

Having thus described my invention, what I
claim as new, and desire to secure by Letters
Patent, is—

1. The combination, with a drum the clamp-
ing-hoops of which are formed with recesses,
of a clamp the clamping-sections of which are
adapted to engage the said hoop and rest in
the said recesses, and a thumb-screw for op-
65 erating the said clamping-sections.

2. The combination, with a drum the clamp-
ing-hoops of which are formed with recesses,
of a clamp the clamping-sections of which are
adapted to engage said hoops and rest in said
70 recesses, substantially as described.

In testimony whereof I affix my signature
in presence of two witnesses.

LOUIS N. DE LONGÉ.

Witnesses:

C. BUETTNER,
R. A. BALDERSON.