

(No Model.)

A. D. SPENCER.
TOOL FOR TRUING DYNAMO COMMUTATORS.

No. 430,094.

Patented June 10, 1890.




Fig 2.





Fig 3.



-WITNESSES-

David Fisher
Klauson Smith

-INVENTOR-

Allen Duntun Spencer,
by G.H.N. Howard
Atty.

UNITED STATES PATENT OFFICE.

ALLEN DUNTON SPENCER, OF BALTIMORE, MARYLAND, ASSIGNOR OF ONE-THIRD TO RICHARD M. WALLACE, OF SAME PLACE.

TOOL FOR TRUING DYNAMO-COMMUTATORS.

SPECIFICATION forming part of Letters Patent No. 430,094, dated June 10, 1890.

Application filed February 15, 1890. Serial No. 340,524. (No model.)

To all whom it may concern:

Be it known that I, ALLEN DUNTON SPENCER, of the city of Baltimore, and State of Maryland, have invented certain Improvements in Tools for Truing Dynamo-Commutators, of which the following is a specification.

This invention relates to certain improvements in a tool whereby the faces of dynamo-commutators and other rotative cylindrical objects which have become worn may be trued or brought to an accurate cylindrical shape while the same is in motion, as will hereinafter fully appear.

The said invention consists in a segmental toothed block having suitable handles, whereby the same may be held to the surface to be repaired.

In the further description of the said invention which follows reference is made to the accompanying drawings, forming a part hereof, and in which—

Figure 1 is a side view of the improved tool, and Fig. 2 a top view of the same. Fig. 3 is an under side view of the invention.

Similar letters of reference indicate similar parts in all the views.

In the said drawings, A represents a block having a hollow surface, which is a part of or a segment of a circle. This surface, which is denoted by *a*, is serrated or toothed after the manner of a file, and its curvature is made as nearly as possible to correspond with the circumference of the object to be trued. The

back *b* of the block is flat, and to it is secured by means of screws *c* a bar *d*, having the handles *e* at its ends. The length of the block A is preferably the same as that of the face of the commutator or object to be filed.

Commutators, if not properly watched and attended to, become grooved and flattened by the action of the brushes, and they are generally taken from the machine and turned, so as to be again true, in a lathe. This operation of course renders the dynamo of no use for the time, and the truing operation is expensive.

The commutator may be put in complete order by holding with both hands the device described against its cylindrical surface until the irregular projections on the same are removed.

The commutator is shown in dotted lines in Fig. 1 and marked C. One of the handles *e* may be thrown up, as shown in dotted lines in Fig. 1, if desired.

I claim as my invention—

A tool for the purpose described, which consists of a hardened steel block with a segmental toothed face, combined with a bar secured transversely of the back of the block, and a handle at each end of the bar, substantially as and for the purpose specified.

ALLEN DUNTON SPENCER.

Witnesses:

WM. T. HOWARD,
DANL. FISHER.