

(No Model.)

G. W. ARCHER.
BARBER'S CHAIR ATTACHMENT.

No. 436,327.

Patented Sept. 16, 1890.

Fig. 1




Fig. 2





Fig. 3



Witnesses

Johnston Sims
Thomas Hurant

Inventor

George W. Archer
by Churchill
his Atty.

UNITED STATES PATENT OFFICE.

GEORGE W. ARCHER, OF ROCHESTER, NEW YORK, ASSIGNOR TO THE
ARCHER MANUFACTURING COMPANY, OF SAME PLACE.

BARBER'S-CHAIR ATTACHMENT.

SPECIFICATION forming part of Letters Patent No. 436,327, dated September 16, 1890.

Application filed December 24, 1889. Serial No. 334,824. (No model.)

To all whom it may concern:

Be it known that I, GEORGE W. ARCHER, of the city of Rochester, county of Monroe, and State of New York, have invented certain new and useful Improvements in Barber's-Chair Attachments; and I do hereby declare the following to be a full, clear, and exact description of the same, reference being had to the accompanying drawings, forming a part of this specification, and to the letters of reference marked thereon.

My present invention has for its object to provide a child's-seat attachment for barbers', dentists', and similar chairs, whereby a child may be operated upon without requiring a special high chair for the purpose, and also whereby the height of said seat may be readily adjusted as desired; and said invention consists in certain novelties of construction and combinations of parts, all as will be hereinafter fully described, and the novel features pointed out in the claims at the end of this specification.

In the drawings, Figure 1 is a perspective view showing the application of my attachment to a barber's chair; Fig. 2, a longitudinal sectional view through a chair and attachment; Fig. 3, a rear view of the attachment.

Similar letters of reference in the several figures denote similar parts.

The letter A represents a barber's or dentist's chair of ordinary or any preferred construction, having the usual socket or recess B at the back for a head-rest, and a catch or lock C, which co-operates with said head-rest when in position and locks it at any desired height.

D represents a child's seat or chair constructed with a back, seat, arms, and, preferably, a foot-rest, and having attached to the upper portion of its back a standard or bar E, having teeth *e* thereon and adapted to project over and enter the socket B in the main chair when in position, the catch C on the latter co-operating with the teeth *e* on said standard and securing it at any desired height. While this standard could be attached rigidly to the seat, I prefer to permit the latter to rest against the back of the chair A, which will not only serve to assist in its support, but also make it more stable and firm; and to this end I provide upon its rear upper side perforated lugs F, which are entered by the trun-

nions E' on the upper end of standard E, so that there will be a pivotal connection between the standard and seat, and thus, no matter what its vertical movements may be, permit it to rest evenly against the back of chair A, even though the upholstering of the lower portion of the back of the latter may project forward.

Of course the manner of connecting the chair and its supporting-standard may be varied without departing from the spirit of my invention, the essential feature of which is a child's-seat attachment capable of being applied to the backs of the chairs now in use having head-rest sockets, the only operation necessary being the removal of the head-rest and the insertion of the standard of the attachment.

Where the attachment is to be applied to barbers' or similar chairs having head-rests secured in position by other means than a catch C, the standard E could be made to conform to that of the head-rest and fastened in position by the means employed to hold said rest.

I do not claim, broadly, a child's-seat attachment adapted to be suspended from the back of a supporting-chair, as this is not my invention.

I claim as my invention—

1. An attachment for barbers' or similar chairs, consisting of a child's seat having a standard or bar pivotally attached to its upper portion, adapted to enter the head-rest socket in said chair, substantially as described.

2. An attachment for barbers' or similar chairs, consisting of a child's seat having a standard or bar attached to its upper portion with ratchet-teeth thereon and adapted to enter the head-rest socket in said chair, substantially as described.

3. The combination, with a barber's or similar chair having a head-rest socket and a catch located at one side thereof, of an attachment therefor consisting of a child's seat having a standard or bar attached to its upper portion, and provided with ratchet-teeth, with which the catch co-operates, substantially as described.

GEORGE W. ARCHER.

Witnesses:

C. D. KIEHEL,
FRED F. CHURCH.