
(No Model.)

W. R. MAGRAW. HORSE BLANKET FASTENER.

No. 441,249.

Patented Nov. 25, 1890.



United States Patent Office.

WILLIAM REED MAGRAW, OF STRICKERSVILLE, PENNSYLVANIA.

HORSE-BLANKET FASTENER.

SPECIFICATION forming part of Letters Patent No. 441,249, dated November 25, 1890.

Application filed September 16, 1890. Serial No. 365, 155. (No model.)

To all whom it may concern:

Be it known that I, WILLIAM REED MA-GRAW, a citizen of the United States, residing at Strickersville, in the county of Chester and 5 State of Pennsylvania, have invented certain new and useful Improvements in Devices for Holding Horse-Blankets; and I do declare the following to be a full, clear, and exact description of the invention, such as will enable 10 others skilled in the art to which it appertains to make and use the same, reference being had to the accompanying drawings, and to the letters of reference marked thereon, which form a part of this specification.

This invention relates to certain new and useful improvements in horse-blanket retaining devices, and it has more particular reference to that class of retaining devices which are intended for use in securing the blanket

in the stable.

The invention has for its object to simplify and cheapen the construction and to render more serviceable in operation this class of 25 appliances.

To this end the invention consists in the peculiar features of construction, which will be hereinafter more fully described, shown in the accompanying drawings, and then spe-30 cifically defined in the appended claims.

The invention is clearly illustrated in the accompanying drawings, which, with the letters of reference marked thereon, form a part of this specification, like letters of reference 35 indicating like parts throughout the several

views, and in which drawings—

Figure 1 is a perspective view showing the invention applied. Fig. 2 is a side view of a blanket-retainer embodying my improve-40 ments. Fig. 3 is a perspective view, in which the parts are shown as occupying the positions they will assume when in actual use.

The device consists of a body portion A, which is made of a single thickness of heavy 45 leather, cut upon an arc of a circle, as shown in Fig. 1 of the drawings. The leather is split from each end of the body portion A inwardly for a sufficient distance to form the straps a a and b b. Within suitable loops c, 50 formed at the ends of the said straps a and b, are retained the looped ends d of the blanketfasteners D, said fasteners consisting of a single piece of wire bent to form the enlarged l

substantially arrow-head-shaped portion d^8 , body portion d^2 , and loop d, the arrow-head 55 d being adapted to engage an opening e' provided for the purpose in the tag e, secured to the edge of the blanket. In order to permit the fasteners to be adjusted to secure blankets of various sizes, I provide each of the tags 60 e with a series of openings e', as shown in the drawings.

In use the body portion A is placed between the thighs of the animal, the straps a and bbeing passed around the thigh and secured 65 to the tags upon the blanket, said tags being secured to the blanket at the proper places.

The blanket may be fastened at its forward end by a similar securing device placed between the forward legs of the animal.

It will be observed that when in position for use the body portion of the fastener will 20 in place upon the horse when the animal is | be turned upon its edge, thus presenting the flat faces of the strap to the thigh and avoiding injury which would otherwise be caused 75 by frictional contact with the strap.

Having thus described my invention, what I claim to be new, and desire to secure by Let-

ters Patent, is—

1. The herein-described device for securing 80 horse-blankets, the same consisting of the body portion A, made of a single thickness of leather, the ends of which are split to form the straps a and b, and the blanket-fasteners D, each consisting of a single piece of wire 85 bent to form the substantially arrow-head portions d^8 , adapted to engage openings in the blanket, and at their opposite ends having loops to engage the free ends of the straps α and b, substantially as described, and for the 90 purpose specified.

2. The herein-described blanket-holder, the same consisting of the piece of leather A, cut in the form of an arc of a circle, its ends being split to form the straps a and b, each of 95 which is provided at its end with the retaining device D, having an arrow-shaped portion d^8 , adapted to engage openings in straps se-

cured to the blanket.

In testimony whereof I affix my signature 100 in presence of two witnesses.

WILLIAM REED MAGRAW.

Witnesses:

W. DOUGHERTY, H. H. DOUGHERTY.