

(No Model.)

E. BROCKMANN.
SHOW STAND.

No. 444,575.

Patented Jan. 13, 1891.




Fig. 1.

Fig. 3.




Fig. 2.

Fig. 1.

Witnesses:

Glenn H. Hume

Everage H. Hume

Inventor:

Ernst Brockmann

by *Wm. A. R. Hume*
attorneys.

UNITED STATES PATENT OFFICE.

ERNST BROCKMANN, OF ELLRICH, GERMANY.

SHOW-STAND.

SPECIFICATION forming part of Letters Patent No. 444,575, dated January 13, 1891.

Application filed February 4, 1890. Serial No. 339,197. (No model.)

To all whom it may concern:

Be it known that I, ERNST BROCKMANN, a subject of the King of Prussia, German Emperor, and a resident of Ellrich, in the Kingdom of Saxony, Germany, have invented some new and useful Improvements in Show-Stands, of which the following is an exact description.

The object of my invention is to provide a stand for exhibiting objects of sale in show-
10 windows or shops with an especial view to economy of space and facility in reaching the articles.

In order to make my invention more clear, I refer to the accompanying drawings, in
15 which—

Figure 1 is an end view of the show-stand. Fig. 2 is a detail view of one arm of the same, partly in section. Fig. 3 is a front view of Fig. 2. Fig. 4 is a section of line $a\beta$, Fig. 2.

20 The rods $c\ c$, containing hooks $d\ d$ for the suspension of articles, are suspended on the bars b , which in their turn are supported on the cross-bars $a\ a'$ of the frame A. The bar b has its one end resting in the slot-holes b^2 of the back cross-bar a , while its front end is
25 formed into a hook, whereby it is suspended on the front cross-bar a' . The front end of this hook is again formed to a hook b' , in which bar c is suspended.

30 B is a stand having hooks $c^2\ c^2$, so that the bars $c\ c$ may be drawn out and rested on the stand B, for which purpose it is necessary to

detach the front end of bar c (which is formed to a handle) from its hook b' and then draw the same forward, when its back end will slide 35 along bar b . The frame A may be arranged for the reception of any number of such suspension-bars $c\ c$. As it is also desirable to be able to adjust these bars sideward to accommodate articles of various sizes, the back cross-
40 bars $a\ a$, Fig. 4, are provided with a number of slot-holes at any desired distance from each other compatible with the practice.

Having thus fully described my invention, what I desire to secure by Letters Patent of 45 the United States is—

The combination of a frame A, having cross-bars $a\ a'$, the cross-bars provided with slots $b^2\ b^2$, in which one end of a bar b is placed, said bar b being hooked at its other or front 50 end and resting on front cross-bar a' and having end of hook prolonged downward and formed to a second hook, and the bar c , provided with hooks for reception of articles, having its one end sliding on bar b and its other
55 resting in hook b' and adapted to be adjusted sideward in frame A, in the manner described.

In witness whereof I have hereunto set my hand in presence of two witnesses.

ERNST BROCKMANN.

Witnesses:

ADOLF NOMANN,
W. KESSLER.