


(No Model.)

T. A. EDISON.  
ELECTRIC RAILWAY.

No. 448,778.

Patented Mar. 24, 1891.



WITNESSES:

*E. C. Rowland*  
*Witness*

INVENTOR:

*Thomas A. Edison,*  
*By Rich<sup>d</sup>. H. Dyer,*  
*Att<sup>y</sup>.*

# UNITED STATES PATENT OFFICE.

THOMAS A. EDISON, OF MENLO PARK, NEW JERSEY, ASSIGNOR TO THE  
EDISON ELECTRIC LIGHT COMPANY, OF NEW YORK, N. Y.

## ELECTRIC RAILWAY.

SPECIFICATION forming part of Letters Patent No. 448,778, dated March 24, 1891.

Application filed August 7, 1882. Serial No. 68,650. (No model.)

*To all whom it may concern:*

Be it known that I, THOMAS A. EDISON, of Menlo Park, in the county of Middlesex and State of New Jersey, have invented a new and  
5 useful Improvement in Electric Railways; and I do hereby declare that the following is a full and exact description of the same, reference being had to the accompanying drawing and to the letters of reference marked thereon.

10 My invention relates to electric railways in which the current is conveyed from a source of energy by stationary conductors to an electric motor mounted upon and propelling a car or train of cars, and especially to that class  
15 of electric railways in which the rails of the track form the conductors for the current, one line of rails forming one conductor or one side of the circuit and the other line of rails an opposite conductor or side of the circuit,  
20 the rails being sufficiently insulated from each other; and my invention consists in a novel arrangement and construction of switches or sidings for such railways as hereinafter set forth, and specified in the claims.

25 The accompanying drawing represents my invention partly in diagram.

A and B are the stationary rails of the main track, each line of rails forming one conductor of the supplying-circuit.

30 C and D are switch-rails of the main track.

The switch-rails C D are connected together mechanically, but insulated electrically from each other by wooden bars E E, each of such bars being provided at each end with a metal  
35 shoe *e*, in which the rail is held. The switch-lever F for moving the switch is attached to the first of said bars E.

The ends of the switch-rails C D and of the stationary rails A B of the main line rest on  
40 metal plates G H, on which rest also the ends of the rails I and J of the side track. The plates G H thus complete electrically the line of each of the main-track conductors, which would otherwise be broken at the point of con-  
45 nection with the conducting-rails of the branch or side track, and such plates also complete the circuit-connections from the conductors of the main track to those of the branch or side track, the two branch-line or side-track con-  
50 ductors being thus connected to the main-

line conductors in permanent multiple-arc connection.

In the position of the parts shown in the drawing the car-wheels or other current-col-  
lecting devices which travel upon the con- 55 ducting-rails and take current therefrom will pass directly along the main line in either direction, but if the movable rails C D are shifted into the position shown in dotted lines the ends of said rails, moving across the plates 60 G H, are brought into juxtaposition with the ends of the branch or side track rails I J, so that the car-wheels or current-collecting devices may pass from the main track to the branch track, the conductors of the branch 65 track being supplied with current through the switch-plates G H without regard to the position of the movable ends of the conductors C D upon said plates.

At the frog K short sections of rails B and 70 I are cut out electrically by the insulating spaces or sections *a a*. The necessary connections are made around the insulated frog by means of wires *b b* or in any other suitable manner. By this arrangement a short circuit of 75 the main-track circuit by the branch rail I is prevented, and the insulating-sections also prevent a short circuit of the main track when the car-wheel or other current-collector passes between I and B, which would occur if the 80 rails were insulated immediately at the frog.

What I claim is—

1. In an electric railway, two main-line conductors, in combination with a source of electric energy therefor, and two branch-line con- 85 ductors connected to the main-line conductors in permanent multiple-arc connection, substantially as set forth.

2. In an electric railway, two rails of a main track, in combination with a source of elec- 90 tric energy connected therewith, and two rails of a branch or side track electrically connected with the main rails in permanent multiple-arc connection, substantially as set forth.

3. In an electric railway, the combination 95 of a main-line conductor, a branch-line or side-track conductor extending therefrom, and a conducting switch-plate joining the extremities of said conductors, substantially as set forth.

4. In an electric railway, the combination  
of a broken main-line conductor, a conduct-  
ing switch-plate connecting the meeting ex-  
tremities of the separated portions, and a  
5 branch-line or side-track conductor connected  
with and extending from the same switch-  
plate, substantially as set forth.

5. In an electric railway, the combination  
of a broken main-line conductor, a conduct-  
10 ing switch-plate, the meeting ends of the sepa-  
rated portions of said conductor extending  
upon the surface of said switch-plate, and a  
branch-line or side-track conductor also ex-  
tending from the surface of said switch-plate,  
15 substantially as set forth.

6. In an electric railway, the combination  
of a broken main-line conductor, a conduct-  
ing switch-plate, the meeting ends of the sepa-  
20 rated portions of said conductor extending  
upon the surface of said switch-plate, and a

branch-line or side-track conductor also ex-  
tending from the surface of said switch-plate,  
the end of one of said conductors being mov-  
able laterally upon the switch-plate, substan-  
tially as set forth.

7. In an electric railway, the combination  
of a main-line conductor, a conducting switch-  
plate upon the surface of which the said con-  
ductor and a main-line conductor extend and a  
branch-line or side-track conductor extending 30  
from the other end of said switch-plate, the  
end of the first-mentioned main-line conductor  
being movable laterally upon the switch-plate,  
substantially as set forth.

This specification signed and witnessed this 35  
5th day of August, 1882.

T. A. EDISON.

Witnesses:

H. W. SEELY,

EDWARD H. PYATT.