


(No Model.)

3 Sheets—Sheet 1.

J. E. PLATT & W. H. RICHARDSON.  
CARDING ENGINE.

No. 454,986.

Patented June 30, 1891.



Witnesses:

Joseph W. Roe.  
C. Sundgren

Inventors  
James Edward Platt  
William H. Richardson  
By Attorneys  
Brown & Hall

(No Model.)

3 Sheets—Sheet 2.

J. E. PLATT & W. H. RICHARDSON.  
CARDING ENGINE.

No. 454,986.

Patented June 30, 1891.

Fig 12.





Fig 8.



Witnesses:-  
D. H. Haywood  
O. Lundgren

Inventor:-  
James Edward Platt  
William Hall Richardson.  
by their attorneys  
Brown & Greenwood




(No Model.)

3 Sheets—Sheet 3.

J. E. PLATT & W. H. RICHARDSON.  
CARDING ENGINE.

No. 454,986.

Patented June 30, 1891.



*Witnesses:*  
*D. H. Kaywood*  
*C. Sundgren*

*Inventor:*  
*James Edward Platt*  
*William Hall Richardson.*  
*by their attorneys.*  
*Brown & Griswold*



# UNITED STATES PATENT OFFICE.

JAMES EDWARD PLATT AND WILLIAM HALL RICHARDSON, OF OLDHAM,  
ENGLAND.

## CARDING-ENGINE.

SPECIFICATION forming part of Letters Patent No. 454,986, dated June 30, 1891.

Application filed March 12, 1888. Serial No. 266,958. (No model.) Patented in England January 31, 1888, No. 1,432.

*To all whom it may concern:*

Be it known that we, JAMES EDWARD PLATT, engineer, of Hartford Works, Oldham, in the county of Lancaster, England, and  
5 WILLIAM HALL RICHARDSON, engineer, of Bank View, Derker, Oldham, in the county of Lancaster, England, have invented certain new and useful Improvements in Carding-Engines, the same to be used in conjunction  
10 with the casings or casing placed underneath certain parts of carding-engines used for carding cotton and other fibrous materials, of which the following is a specification, and for which we have obtained Letters Patent of  
15 Great Britain, No. 1,432, dated January 31, 1888.

Our invention relates to the casings placed underneath the cylinder and taker-in roller and to the casing placed underneath the cylinder only of carding-engines used for carding cotton and other fibrous materials; and  
20 our invention consists in arrangements by means of which such casings may, in the first case, be adjusted relatively to the cylinder and taker-in roller, and in the second case to the cylinder only, more readily and with greater accuracy than heretofore.

Our invention also consists in arrangements for carrying the taker-in roller-knives, so that  
30 when once adjusted they remain in correct working position in relation to the taker-in roller, although such taker-in roller may be moved in order to be adjusted nearer to or farther from the cylinder.

35 The drawings hereunto annexed show a method of carrying our invention into effect.

Figure 1 is a side view showing so much of a carding-engine as is requisite to illustrate our invention, and Figs. 2 and 3 are views showing portions detached and in a position at  
40 right angles to that in which they are shown in Fig. 1. Fig. 2 shows a section through the line B C. It also shows a side view of the bracket *f*, and how it supports the parts *e'* of the casing A. Fig. 3 shows a section through  
45 the line E E and shows how the plate *q* carries the bracket *r*. Fig. 4 is a plan showing the pedestal *u*, the shroud *t*, and part of the plate or bracket *q*; and Fig. 5 is a section through line C C, showing the pedestal *u*,  
50 shroud *t*, and the plate or bracket *q*. Fig. 6

is a section and side view through the line B C (see Fig. 1) upon a larger scale; and Fig. 7, a front view, also upon a larger scale of the bracket *f* shown in Fig. 1, and which is used  
55 for adjusting the part *e* of the casing A. Fig. 8 shows the screw *j* of the bracket *f* enlarged. Fig. 9 shows the bracket *q* and how it is secured to the shroud *t*. Fig. 10 is a section through the line F F of Fig. 9. Fig. 11  
60 is a view, partly in section, of the pedestal *u* through the line G G of Fig. 4, and illustrates the devices for adjusting the pedestal *u*. Fig. 12 is an enlarged view of the taker-in roller *c* and shows the plate *q*, brackets *r*, 2,  
65 and 3, and portions of the under casing A.

At *a*, Fig. 1, is one of the side framings of a carding-engine, which supports one end of the main cylinder *b* and the taker-in roller *c*. Beneath the taker-in roller *c* and the main  
70 cylinder *b* is the casing A, provided, as usual, with bars or grids. One portion *d* of the casing A is situate beneath the taker-in roller *c* and is made of a segment of a circle of somewhat greater diameter than that of the taker-  
75 in roller *c*. The other portion *e* of the casing A is situate beneath the main cylinder *b*, and is also made of a segment of a circle of somewhat greater diameter than that of the main  
80 cylinder *b*. The part *d*, Fig. 12, of the casing A, situate beneath the taker-in roller *c*, is formed with a flange *d'*, which has a round hole in it to receive the supporting-stud 2<sup>a</sup>, secured to the adjustable bracket 2. The bracket  
85 2 is also provided with a slot 2<sup>c</sup>, through which passes the screw 2<sup>b</sup>, by which it is secured to the plate or bracket *q*, and the part *e* of the casing A, situate beneath the main cylinder  
90 *b*, is formed with a flange *e'*, which has circular slots *p*, corresponding to the circle of the flange *e'*, (see Figs. 1 and 7,) cut into it to receive the supporting-studs *n*. The part *e* of the casing A, which is nearest the taker-in  
95 roller *c*, is supported by the stud 3<sup>a</sup>, passing through a hole of the same diameter as the stud 3<sup>a</sup>, formed in the flange *e'*. The stud 3<sup>a</sup> is secured to the adjustable bracket 3, which is provided with slots 3<sup>d</sup>, through which pass  
100 screws 3<sup>b</sup>, by which it is secured to the plate or bracket *q*. The stud 3<sup>a</sup>, after passing through the flange *e'*, passes through a horizontal slot 3<sup>c</sup>, formed in the side frame *a*. This



slot, while permitting of the horizontal adjustment of the stud  $3^a$ , prevents any movement in a vertical direction.

$u$ , Fig. 11, is an ordinary adjustable pedestal mounted on the side frame  $a$ , which carries the end  $c'$  of the taker-in roller  $c$ .  $u'$ , Fig. 11, is a stud secured by a nut to the side frame  $a$ . The end of this stud  $u'$  is tapped to receive an adjusting-screw  $v$ . The screw  $v$  passes through the lower part of the pedestal  $u$  and is connected thereto by means of the collar  $v'$ , fastened by a pin passing through the collar and the screw  $v$ . The bolt  $u^2$ , passing through a slot in the side frame  $a$ , secures the pedestal  $u$  to the side frame  $a$ . When it is necessary to set or adjust the pedestal  $u$ , the bolt  $u^2$  is slackened and the screw  $v$  turned either to the right or left, according to the direction in which the pedestal is required to be moved. When the necessary adjustment has been made, the pedestal  $u$  is secured to the side frame  $a$  by the bolt  $u^2$ .

$t$ , Figs. 9 and 10, is a shroud which covers the end of the taker-in roller  $c$ .

$q$ , Figs. 9, 10, and 12, is a plate or bracket capable of being slid on the side frame  $a$ .

$s$  and  $s'$ , Fig. 12, are knives ordinarily employed in conjunction with taker-in rollers.

$r$  is a bracket which carries the knives  $s$   $s'$ , and is provided with a setting-screw  $r'$  for adjusting the height of the lower knife  $s'$ . The bracket  $r$  is secured to the plate or bracket  $q$  by a screw  $r^3$  in a slot  $r^2$ , which permits of its horizontal adjustment in relation to the bracket  $q$ .

$f$ , Figs. 1, 2, 6, 7, and 8, is an adjustable bracket for adjusting the part  $e$  of the casing A, and is secured to the side framing  $a$  by means of a threaded stud  $m$ . The portion  $d$  of the casing A and the portion  $e$ , as shown in Figs. 1 and 12, are formed in separate pieces; but a shoulder is formed on the exterior of the part  $e$  opposite the star  $e^2$ , (see Fig. 12,) to rest upon the adjacent end of the part  $d$  for the support of the said part  $e$ , so that when the brackets 2 3 are secured to the plate or bracket  $q$  the said parts  $d$  and  $e$  are both supported by the said bracket  $q$ , and when the said bracket is adjusted the said parts will move together just as though they were made in one piece. The part  $d$  is hung at its rear end upon pins or projections extending from the bracket  $q$ . Sometimes for convenience of carriage we make the part  $e$  in two pieces, which are hinged together at the part marked  $e^3$  and shown in Fig. 1; or the parts  $d$  and  $e$  may be formed in one piece or be fastened together so as to constitute one piece. The portion  $d$  of the casing A and that portion  $e$  of the casing A which is situated nearest to the taker-in roller  $c$  are secured to the plate or bracket  $q$  in the same manner, whether the casing A is formed in one, two, or three pieces. By means of the slot  $3^c$  those parts of the casing A adjacent to the star  $e^2$  are prevented from being set too high and so coming in con-

tact with the wire of the cylinder  $b$  and taker-in roller  $c$ .

The casing A is supported near its front end by the plates or brackets 2 and 3, Fig. 12, secured to the bracket  $q$ , and farther to the rear by adjustable brackets  $f$ . One of such brackets  $f$  is shown in the detached views, Figs. 6 and 7 and partly in Fig. 8. Each of the brackets  $f$  is provided with a foundation part  $g$ , which is fixed to the side frame  $a$  by the threaded stud  $m$ . Mounted upon the foundation part  $g$  is a sliding part  $h$ , provided with a slot  $m'$ , through which the end of the stud  $m$  passes, the slot  $m'$  permitting the movement of the part  $h$  on the foundation part  $g$ . The part  $h$  carries the stud  $n$ , which, after passing through the opening  $o$  in the side frame  $a$ , fits into the slot  $p$ , formed in the flange  $e'$ , and by which the part  $e$  of the casing A is supported and adjusted.

Upon the foundation part  $g$  we form ribs  $g'$ , which ribs  $g'$  pass into grooves formed in the sliding part  $h$ . The ribs  $g'$  act as guides, which only permit the sliding part  $h$  to be moved lengthwise upon the foundation part  $g$ . The sliding part  $h$  is drilled and tapped at  $k$  to receive an adjusting-screw  $j$  (see Fig. 8) of a well-known type, the head of which is formed with an annular groove to receive a forked lug  $g^2$ , projecting from the foundation part  $g$ , and while allowing the screw  $j$  to be turned round prevents it from moving lengthwise. By turning the screw  $j$  in one direction or the other the sliding part  $h$  will be moved upon the foundation part  $g$ , and the part  $e$  of the casing A will be moved nearer to or farther from the card-surface of the cylinder  $b$ . When the sliding part  $h$  has been adjusted into the required position by means of the screw  $j$ , it must be secured therein by means of a nut  $l$ , screwing upon the stud  $m$ . Instead of the brackets  $f$  being secured to the outside of the side frame  $a$ , such brackets may be secured to the inside of the side frame  $a$ , and in such cases instead of each of the studs  $n$  passing through an opening  $o$  in the side frame  $a$ , such stud  $n$  will pass at once into one of the slots  $p$ , formed in one of the side flanges  $e'$  of the portion  $e$  of the casing A, situate beneath the main cylinder  $b$ .

We prefer the above construction of the bracket  $f$ ; but any kind of adjustable bracket may be used instead, so long as the bracket permits of a circumferential movement of the part  $e$  of the casing A, which will be hereinafter described.

$q$ , Figs. 9 and 10, is a plate or bracket having at its upper edge a projecting flange  $q'$ , by which it is supported upon the side frame  $a$ . The plate or bracket  $q$  is held against the side frame  $a$  by the lower part  $t^2$  of the shroud  $t$ .

$t$ , Figs. 9 and 10, is a shroud for covering the end of the taker-in roller  $c$ . The boss  $t'$  of the shroud  $t$  passes into the pedestal  $u$  and forms a bearing for one end of the taker-in



roller *c*, which passes through it. The cap of the pedestal *u*, Figs. 4 and 5, when screwed down on the boss of the shroud *t* secures the shroud in its proper position.

5 Upon the shroud *t* we form two projecting parts or lugs *w*, Figs. 9 and 10. Upon the plate or bracket *q* we form lugs *x*, which fit between the lugs *w* on the shroud *t*. By this means the plate or bracket *q* is connected to the shroud *t*, so that when the pedestal *u* and the shroud *t* are moved nearer to or farther from the cylinder *b* the plate or bracket *q* will also be moved with them. The plate or bracket *q* is kept in position against the side frame *a* by the lower part *t*<sup>2</sup> of the shroud *t* being set close up to or nearly close up to the plate or bracket *q*, as shown in section in Fig. 10. Instead of the projecting parts or lugs *w* being formed upon the shroud *t*, such projecting parts or lugs *w* may be formed upon the pedestal *u* and fit between the corresponding lugs or projections *x*, formed on the plate *q*. The knife-bracket *r*, Figs. 3 and 12, which carries or supports one end of each of the knives *s s'*, ordinarily employed in conjunction with taker-in rollers, is provided with a flange which rests on the top of the bracket *q*, and is secured to the plate or bracket *q* by the screw *r*<sup>3</sup>, which passes through the slot *r*<sup>2</sup>. (See Fig. 12.)

For convenience of description we have hitherto only referred to parts situate at one side of the carding-engine; but it will be readily understood that where necessary like parts are employed on each side of the carding-engine.

The taker-in roller *c* having been adjusted into the desired position relatively to the main cylinder *b*, we first adjust the part *e* of the casing *A* which is nearest to the taker-in roller *c* by means of the bracket 3, which carries the stud 3<sup>a</sup>, and which supports this part and especially adjusts the position of that part of the casing *A* which we have indicated by the star \* *e*<sup>2</sup>. We then, by means of the brackets *f*, which carry the studs *n*, that enter into the slots *p*, formed in the flange *e'* of the casing *A*, adjust the other portions of the part *e*, so that the entire portion *e* of the casing *A* will be concentric or nearly concentric with the card-surface of the main cylinder *b*. We then adjust the portion *d* of the casing *A* beneath the taker-in roller *c* by means of the supporting-bracket 2, which by means of the stud 2<sup>a</sup> regulates the position of the part *d*, so that such portion *d* of the casing *A* will be concentric or nearly concentric with the card-surface of the taker-in roller *c*. The bracket 2 is then securely fastened to the plate or bracket *q* by the screw 2<sup>b</sup> or other suitable means passing through the slot 2<sup>c</sup>, formed in the plates 2. The casing *A* will then be in proper working position. When it becomes necessary, from the wear of the card-surfaces of the main cylinder *b* and taker-in roller *c*, to readjust the position of the taker-in roller *c* relatively to the main cylinder *b*, the taker-

in roller *c* is again adjusted into the desired position by means of the screw *v* for adjusting the pedestal *u*, as previously explained. 70 The movement of the pedestal *u* necessary for the adjustment of the taker-in roller *c* will cause the plate or bracket *q*, with the part *d* of the casing *A*, to be moved along with the pedestal. This movement of the plate 75 or bracket *q* by means of the plate 3 and stud 3<sup>a</sup> will cause that portion *e* of the casing *A* which is situated nearest the taker-in roller *c* to be moved nearer to the cylinder *b*, and will cause the portion *e* of the casing *A*, 80 which is supported by the brackets *f*, to be slightly moved circumferentially around the main cylinder *b*, the slots *p*, formed through *e'*, the side flanges acting as guides and so permitting it to be moved; otherwise, if it 85 were not for the movement permitted by the slots *p*, the part *e* would buckle or bulge. When desirable, the portion *e* beneath the main cylinder *b* may be readjusted relatively to the card-surface of the main cylinder *b* by 90 means of the brackets *f* and 3, and the position of the part *d* may also be adjusted relatively to the card-surface of the taker-in roller *c* by means of the brackets 2. The portion *e* beneath the main cylinder *b* and the portion *d* beneath the taker-in roller *c* are prevented from moving sidewise by the side frames *a a* of the carding-engine. 95

Instead of forming the slots *p*, as above described, in the side flanges *e'* and providing 100 each of the brackets *f* with a stud *n*, we may in some cases provide the side flanges *e'* with studs, each of which passes into a slot formed in one of the brackets *f*.

We mount the adjustable knife-brackets *r* 105 upon the plates or brackets *q*, as previously mentioned, and by means of the slot *r*<sup>2</sup> in the bracket *r* adjust the bracket *r* horizontally, so as to bring the knife *s* to its proper position. We then by means of the adjusting- 110 screw *r'* adjust the knife *s'* to its proper position. Owing to their connection with the pedestal *u* by means of the plate or bracket *q* when once adjusted, the knives *s* and *s'* will remain in correct working positions in 115 relation to the taker-in roller *c*, although such taker-in roller *c* may be moved in order to be adjusted nearer to or farther from the cylinder *b*.

In some cases we dispense with the use of 120 the part *d* of the casing *A*, in which case our invention is applied solely to the adjustment of the part *e* of the casing *A* beneath the main cylinder *b*.

What we claim is—

1. The combination, with the main cylinder 125 and taker-in roller of a carding-engine, of the parts *d* and *e* of the casing *A*, the pedestals *u* and screws *v*, the shrouds *t*, with the projections or lugs *w*, the plates or brackets *q*, 130 with the lugs *x*, the knife-brackets *r*, the taker-in-roller knives *s s'*, the brackets 2, provided with the slots 2<sup>c</sup>, the screws 2<sup>b</sup>, and studs 2<sup>a</sup>, the brackets 3, with the studs 3<sup>a</sup>, the



screws  $3^b$ , and slots  $3^d$ , the side frames  $a$ , with the slots  $o$  and the horizontal slots  $3^c$  to receive the studs  $3^a$ , the part  $d$  of the casing being provided with the side flanges  $d'$ , having round holes to receive the studs  $2^a$ , the part  $e$  of the casing being provided with the side flanges  $e'$ , having slots  $p$  and round holes to receive the studs  $3^a$ , and the brackets  $f$ , provided with studs  $n$ , substantially as specified.

2. The combination, with the main cylinder and taker-in roller of a carding-engine, of the part  $e$  of the casing  $A$ , the pedestals  $u$  and screws  $v$ , the shrouds  $t$ , with the projections or lugs  $w$ , the plates or brackets  $q$ , with the lugs  $x$ , the knife-brackets  $r$ , the taker-in-roller knives  $s s'$ , the brackets  $3$ , with the studs  $3^a$ , the screws  $3^b$ , and slots  $3^d$ , the side frames  $a$ , with the slots  $o$  and the horizontal slots  $3^c$  to receive the studs  $3^a$ , the part  $e$  of the casing being provided with the side flanges  $e'$ , having slots  $p$  and round holes to receive the studs  $3^a$ , and the brackets  $f$ , provided with studs  $n$ , substantially as specified.

3. The combination, with the main cylinder and taker-in roller of a carding-engine, of the parts  $d$  and  $e$  of the casing  $A$ , the pedestals  $u$  and screws  $v$ , the shrouds  $t$ , with the projections or lugs  $w$ , the plates or brackets  $q$ , with the lugs  $x$ , the brackets  $2$ , provided with the slot  $2^c$ , the screws  $2^b$ , and studs  $2^a$ , the brackets

3, with the studs  $3^a$ , the screws  $3^b$ , and slots  $3^d$ , the side frames  $a$ , with the slots  $o$  and the horizontal slots  $3^c$  to receive the studs  $3^a$ , the part  $d$  of the casing being provided with the side flanges  $d'$ , having round holes to receive the studs  $2^a$ , and the part  $e$  of the casing being provided with the side flanges  $e'$ , having slots  $p$  and round holes to receive the studs  $3^a$ , and the brackets  $f$ , provided with studs  $n$ , substantially as specified.

4. The combination, with the main cylinder and taker-in roller of a carding-engine, of the part  $e$  of the casing  $A$ , the pedestal  $u$  and screws  $v$ , the shrouds  $t$ , with the projections or lugs  $w$ , the plates or brackets  $q$ , with the lugs  $x$ , the brackets  $3$ , with the studs  $3^a$ , the screws  $3^b$ , and slots  $3^d$ , the side frames  $a$ , with the slots  $o$  and the horizontal slots  $3^c$  to receive the studs  $3^a$ , the part  $e$  of the casing being provided with the side flanges  $e'$ , provided with slots  $p$  and round holes to receive the studs  $3^a$ , and the brackets  $f$ , provided with studs  $n$ , substantially as specified.

JAMES EDWARD PLATT.

WILLIAM HALL RICHARDSON.

Witnesses:

ARTHUR C. HALL,

9 Mount St., Manchester, Eng.

W. T. CHEETHAM,

18 St. Ann's Street, Manchester.