

(No Model.)

C. M. SYMONDS.
CAN FAUCET.

No. 455,465.

Patented July 7, 1891.




Fig. 2.





Fig. 3.



Witnesses
Thomas Jones,
Charles H. Whitney

Inventor
Clarence M. Symonds

UNITED STATES PATENT OFFICE.

CLARENCE M. SYMONDS, OF SAN FRANCISCO, CALIFORNIA.

CAN-FAUCET.

SPECIFICATION forming part of Letters Patent No. 455,465, dated July 7, 1891.

Application filed October 27, 1890. Serial No. 369,509. (No model.)

To all whom it may concern:

Be it known that I, CLARENCE M. SYMONDS, of the city and county of San Francisco, and State of California, have invented an Improvement in Can-Faucets; and I hereby declare the following to be a full, clear, and exact description thereof.

My invention relates to an improvement in that class of faucets which are placed into cans and similar receptacles containing liquids and are transferred from a can when it is empty to a can which is full; and it consists of a hollow tube, to one end of which is secured a blade and to the other end is a tap of suitable form. Upon the outer surface of said tube is formed a screw-thread, over which are arranged a thumb-nut, washer, and packing-ring, all as hereinafter described.

Referring to the accompanying drawings, Figure 1 is a side elevation. Fig. 2 is a view of the interior of the can with my device in position. Fig. 3 is a sectional view of the can after the blade has penetrated into the interior. Fig. 4 is a sectional view of my device.

A represents a hollow tube having a tap B at one end. At the other end is secured a blade C, which is quite thin and shaped similar to a spear-head, having shoulders D D.

Upon the outer surface of the tube A is formed a screw-thread, whereon is placed a thumb-nut E.

F is a metal washer having one side flat to fit against the thumb-nut E, and the other side is made concave.

G is a packing-ring made of cork or other suitable material. This packing-ring G is

slipped on over a beveled shoulder H into a recess J, formed on the end of the tube A.

In operating my device the blade C is pushed through the tin, and in so doing causes a lip I, Fig. 3, to be formed upon each side of the blade. The device is then given a quarter-turn, and the shoulders D D press down the lips I I, Fig. 2, thus forming a double thickness for the blade C to be drawn against, and thereby preventing the blade from being torn out. The thumb-nut E is then turned against the metal washer F, which in turn presses upon the cork packing-ring G, thereby fastening the shoulders D D against the inner surface of the can, and also pressing the cork packing-ring G against the outer surface of the can, and owing to the metal washer F being concaved it at the same time presses the cork-packing ring G against the beveled shoulder H, forming a perfectly-tight joint.

Having thus described my invention, what I claim as new, and desire to secure by Letters Patent, is—

A can-faucet consisting of a tube having a recess J and beveled shoulder H, in combination with a blade, a cork packing-ring fitting said recess, a metal washer bearing against the packing-ring, and a thumb-nut, substantially as described, and for the purpose specified.

In witness whereof I hereunto set my hand.
CLARENCE M. SYMONDS.

Witnesses:

FRANK A. BROOKS,
THOMAS JONES.